

**Miami County emission limits.**

- (A) No owner or operator of any coal-fired steam generating unit, unless otherwise specified below, shall cause or permit the emission of sulfur dioxide from any source to exceed a maximum of 3.2 pounds of sulfur dioxide per MM Btu actual heat input.
- (B) The "Piqua Municipal Power System" (OEPA premise number 0855100041) or any subsequent owner or operator of the "Piqua Municipal Power System" facility located at 919 South Main Street, Piqua, Ohio shall not cause or permit the emission of sulfur dioxide from the following sources to exceed the amounts indicated:
  - (1) Boiler numbers 4 through 6 (OEPA source numbers B001 through B003) a maximum of 4.8 pounds of sulfur dioxide per MM Btu actual heat input from each boiler.
  - (2) FT number 8 oil-fired boiler (OEPA source number B007); a maximum of 0.5 pounds of sulfur dioxide per MM Btu actual heat input.
- (C) The "Val Decker Packing Company" (OEPA premise number 0855100084) or any subsequent owner or operator of the "Val Decker Packing Company" facility located at 727 East Ash Street, Piqua, Ohio shall not cause or permit the emission of sulfur dioxide from boiler numbers 8163 and 8164 (OEPA source numbers B002 and B003) to exceed a maximum of 3.2 pounds of sulfur dioxide per MM Btu actual heat input from each boiler.
- (D) The "Hobart Corporation" (OEPA premise number 0855140111) or any subsequent owner or operator of the "Hobart Corporation" facility located on Lincoln Avenue, Troy, Ohio shall not cause or permit the emission of sulfur dioxide from boiler numbers 981 and 982 (OEPA source numbers B001 and B002) to exceed a maximum of 3.2 pounds of sulfur dioxide per MM Btu actual heat input from each boiler.
- (E) The "ITW Food Equipment Group 27" (OEPA premise number 0855140112) or any subsequent owner or operator of the "ITW Food Equipment Group 27" facility located at 701 Ridge Ave., Troy, Ohio shall not cause or permit the emission of sulfur dioxide from boiler numbers 1 through 3 (OEPA source numbers B001 through B003) to exceed a maximum of 3.2 pounds of sulfur dioxide per MM Btu actual heat input from each boiler.

Effective: 01/23/2006

R.C. 119.032 review dates: 10/28/2005 and 01/23/2011

CERTIFIED ELECTRONICALLY  
Certification

01/13/2006  
Date

Promulgated Under: 119.03  
Statutory Authority: 3704.03(E)  
Rule Amplifies: 3704.03(A) and 3704.03(E)  
Prior Effective Dates: 12/28/79