



State of Ohio Environmental Protection Agency

Street Address:

Lazarus Gov. Center  
50 West Town Street, Suite 700  
Columbus, OH 43215

TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov. Center  
P.O. Box 1049  
Columbus, OH 43216-1049

05/02/08

CERTIFIED MAIL

**RE: Draft Title V Chapter 3745-77  
permit**

03-69-00-0025  
Pro-tec Coating Co.  
Rick K. Rupert  
5000 County Rd. #5  
Leipsic, OH 45856-9234

Dear Rick K. Rupert:

You are hereby notified that the Ohio Environmental Protection Agency has prepared the enclosed draft of the Title V permit for the facility referenced above. The purpose of this draft is to solicit public comments. A public notice concerning the draft will appear in the Ohio EPA Weekly Review and the major newspaper in the county where the facility is located. Comments and/or a request for a public hearing from the public and any affected parties will be accepted by Northwest District Office within 30 days of the date of publication in the newspaper. You will be notified in writing if a public hearing is scheduled. **In order to facilitate our review of all the comments or concerns you may have with the enclosed draft permit, please provide a hand marked-up copy of the draft permit showing the changes you think are necessary, along with any additional summary comments, by the end of the draft public comment period. The hard marked-up copy and any additional summary comments should be submitted to the Ohio EPA District Office or local air agency identified below and to the following address:**

**Andrew Hall  
Permit Review/Development Section  
Ohio EPA, Division of Air Pollution Control  
122 South Front Street  
Columbus, Ohio 43215**

A decision on processing the Title V permit will be made after consideration of written public comments and oral testimony (if a public hearing is conducted). After the comment period, you will be provided with a Preliminary Proposed Title V permit and an opportunity to comment prior to the Proposed Title V permit submittal to USEPA.

If you have any questions concerning this draft Title V permit, please contact Northwest District Office.

Sincerely,

Michael W. Ahern, Manager  
Permit Issuance and Data Management Section  
Division of Air Pollution Control

cc: USEPA (electronically submitted)  
File, DAPC PIER  
Northwest District Office  
Indiana  
Michigan



State of Ohio Environmental Protection Agency

DRAFT TITLE V PERMIT

Issue Date: 05/02/08	Effective Date: To be entered upon final issuance	Expiration Date: To be entered upon final issuance
----------------------	---	--

This document constitutes issuance of a Title V permit for Facility ID: 03-69-00-0025 to:

Pro-tec Coating Co.  
5000 County Rd. #5  
Leipsic, OH 45856-9234

**Emissions Unit ID (Company ID)/Emissions Unit Activity Description**

B001 (B1-CGL) Hot Water Boiler #1 (14.7 MMBtu/hr)	B044 (B4-CGL2) Hot Water Boiler #4 (14.7 MMBTU/hr)	16 MMBtu/hr aux. heat input (96 MMBtu/hr total)
B002 (B2-CGL) Hot Water Boiler #2 (14.7 MMBtu/hr)	K001 (RC-CGL) Dry Film Lube Horizontal Roll Coater with infrared oven	P010 (AF-CGL2) 71.8 MMBTU/hr Continuous Annealing Furnace with 5 MMBtu/hr aux. heat input (76.8 MMBtu/hr total)
B043 (B3-CGL2) Hot Water Boiler #3 (14.7 MMBTU/hr)	P001 (AF-CGL) 80 MMBtu/hr Continuous Annealing Furnace with	

You will be contacted approximately eighteen (18) months prior to the expiration date regarding the renewal of this permit. If you are not contacted, please contact the appropriate Ohio EPA District Office or local air agency listed below. This permit and the authorization to operate the air contaminant sources (emissions units) at this facility shall expire at midnight on the expiration date shown above. If a renewal permit is not issued prior to the expiration date, the permittee may continue to operate pursuant to OAC rule 3745-77-08(E) and in accordance with the terms of this permit beyond the expiration date, provided that a complete renewal application is submitted no earlier than eighteen (18) months and no later than one-hundred eighty (180) days prior to the expiration date.

Described below is the current Ohio EPA District Office or local air agency that is responsible for processing and administering your Title V permit:

Northwest District Office  
347 North Dunbridge Road  
Bowling Green, OH 43402  
(419) 352-8461

Ohio Environmental Protection Agency

Chris Korleski  
Director

## PART I - GENERAL TERMS AND CONDITIONS

### A. *State and Federally Enforceable Section*

#### 1. **Monitoring and Related Record Keeping and Reporting Requirements**

a. Except as may otherwise be provided in the terms and conditions for a specific emissions unit, i.e., in Section A.III of Part III of this Title V permit, the permittee shall maintain records that include the following, where applicable, for any required monitoring under this permit:

- i. The date, place (as defined in the permit), and time of sampling or measurements.
- ii. The date(s) analyses were performed.
- iii. The company or entity that performed the analyses.
- iv. The analytical techniques or methods used.
- v. The results of such analyses.
- vi. The operating conditions existing at the time of sampling or measurement.  
(*Authority for term: OAC rule 3745-77-07(A)(3)(b)(i)*)

b. Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.  
(*Authority for term: OAC rule 3745-77-07(A)(3)(b)(ii)*)

c. The permittee shall submit required reports in the following manner:

- i. **All reporting required in accordance with OAC rule 3745-77-07(A)(3)(c) for deviations caused by malfunctions shall be submitted in the following manner:**

Any malfunction, as defined in OAC rule 3745-15-06(B)(1), shall be promptly reported to the Ohio EPA in accordance with OAC rule 3745-15-06. In addition, to fulfill the OAC rule 3745-77-07(A)(3)(c) deviation reporting requirements for malfunctions, written reports that identify each malfunction that occurred during each calendar quarter (including each malfunction reported only verbally in accordance with OAC rule 3745-15-06) shall be submitted (i.e., postmarked) by January 31, April 30, July 31, and October 31 of each year in accordance with General Term and Condition A.1.c.ii below; and each report shall cover the previous calendar quarter. (An exceedance of the visible emission limitations specified in OAC rule 3745-17-07(A)(1) that is caused by a malfunction is not a violation and does not need to be reported as a deviation if the owner or operator of the affected air contaminant source or air pollution control equipment complies with the requirements of OAC rule 3745-17-07(A)(3)(c).)

In accordance with OAC rule 3745-15-06, a malfunction reportable under OAC rule 3745-15-06(B) constitutes a violation of an emission limitation (or control requirement) and, therefore, is a deviation of the federally enforceable permit requirements. Even though verbal notifications and written reports are required for malfunctions pursuant to OAC rule 3745-15-06, the written reports required pursuant to this term must be submitted quarterly to satisfy the prompt reporting provision of OAC rule 3745-77-07(A)(3)(c).

In identifying each deviation caused by a malfunction, the permittee shall specify the emission limitation(s) (or control requirement(s)) for which the deviation occurred, describe each deviation, and provide the magnitude and duration of each deviation. For a specific malfunction, if this information has been provided

in a written report that was submitted in accordance with OAC rule 3745-15-06, the permittee may simply reference that written report to identify the deviation. Nevertheless, all malfunctions, including those reported only verbally in accordance with OAC rule 3745-15-06, must be reported in writing on a quarterly basis.

Any scheduled maintenance, as referenced in OAC rule 3745-15-06(A)(1), that results in a deviation from a federally enforceable emission limitation (or control requirement) shall be reported in the same manner as described above for malfunctions.

*(Authority for term: OAC rule 3745-77-07(A)(3)(c))*

- ii. **Except as may otherwise be provided in the terms and conditions for a specific emissions unit, i.e., in Section A.IV of Part III of this Title V permit or, in some cases, in Part II of this Title V permit, all reporting required in accordance with OAC rule 3745-77-07(A)(3)(c) for deviations of the emission limitations, operational restrictions, and control device operating parameter limitations shall be submitted in the following manner:**

Written reports of (a) any deviations from federally enforceable emission limitations, operational restrictions, and control device operating parameter limitations, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures taken, shall be promptly made to the appropriate Ohio EPA District Office or local air agency. Except as provided below, the written reports shall be submitted (i.e., postmarked) by January 31, April 30, July 31, and October 31 of each year; and each report shall cover the previous calendar quarter.

In identifying each deviation, the permittee shall specify the emission limitation(s), operational restriction(s), and/or control device operating parameter limitation(s) for which the deviation occurred, describe each deviation, and provide the estimated magnitude and duration of each deviation.

These written deviation reports shall satisfy the requirements of OAC rule 3745-77-07(A)(3)(c) pertaining to the submission of monitoring reports every six months and to the prompt reporting of all deviations. Full compliance with OAC rule 3745-77-07(A)(3)(c) requires reporting of all other deviations of the federally enforceable requirements specified in the permit as required by such rule.

If an emissions unit has a deviation reporting requirement for a specific emission limitation, operational restriction, or control device operating parameter limitation that is not on a quarterly basis (e.g., within 30 days following the end of the calendar month, or within 30 or 45 days after the exceedance occurs), that deviation reporting requirement satisfies the reporting requirements specified in this General Term and Condition for that specific emission limitation, operational restriction, or control device parameter limitation. Following the provisions of that non-quarterly deviation reporting requirement will also satisfy (for the deviations so reported) the requirements of OAC rule 3745-77-07(A)(3)(c) pertaining to the submission of monitoring reports every six months and to the prompt reporting of all deviations, and additional quarterly deviation reports for that specific emission limitation, operational restriction, or control device parameter limitation are not required pursuant to this General Term and Condition.

See B.6 below if no deviations occurred during the quarter.

*(Authority for term: OAC rule 3745-77-07(A)(3)(c))*

- iii. **All reporting required in accordance with the OAC rule 3745-77-07(A)(3)(c) for other deviations of the federally enforceable permit requirements which are not reported in accordance with General Term and Condition A.1.c.ii above shall be submitted in the following manner:**

Unless otherwise specified by rule, written reports that identify deviations of the following federally enforceable requirements contained in this permit; General Terms and Conditions: A.2, A.3, A.4, A.6.e, A.7, A.12, A.14, A.18, A.19, A.20, and A.22 of Part I of this Title V permit, as well as any deviations from the requirements in Section A.V or A.VI of Part III of this Title V permit, and any monitoring, record keeping, and reporting requirements, which are not reported in accordance with General Term and Condition A.1.c.ii above shall be submitted (i.e., postmarked) to the appropriate Ohio EPA District Office

or local air agency by January 31 and July 31 of each year; and each report shall cover the previous six calendar months. Unless otherwise specified by rule, all other deviations from federally enforceable requirements identified in this permit shall be submitted annually as part of the annual compliance certification, including deviations of federally enforceable requirements not specifically addressed by permit or rule for the insignificant activities or emissions levels (IEU) identified in Part II.A of this Title V permit. Annual reporting of deviations is deemed adequate to meet the deviation reporting requirements for IEUs unless otherwise specified by permit or rule.

In identifying each deviation, the permittee shall specify the federally enforceable requirement for which the deviation occurred, describe each deviation, and provide the magnitude and duration of each deviation.

These semi-annual and annual written reports shall satisfy the reporting requirements of OAC rule 3745-77-07(A)(3)(c) for any deviations from the federally enforceable requirements contained in this permit that are not reported in accordance with General Term and Condition A.1.c.ii above.

If no such deviations occurred during a six-month period, the permittee shall submit a semi-annual report which states that no such deviations occurred during that period.

*(Authority for term: OAC rules 3745-77-07(A)(3)(c)(i) and (ii) and OAC rule 3745-77-07(A)(13)(b))*

- iv. Each written report shall be signed by a responsible official certifying that, "based on information and belief formed after reasonable inquiry, the statements and information in the report (including any written malfunction reports required by OAC rule 3745-15-06 that are referenced in the deviation reports) are true, accurate, and complete."

*(Authority for term: OAC rule 3745-77-07(A)(3)(c)(iv))*

- v. Reports of any required monitoring and/or record keeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.

*(Authority for term: OAC rule 3745-77-07(A)(3)(c))*

## 2. Scheduled Maintenance

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. Except as provided in OAC rule 3745-15-06(A)(3), any scheduled maintenance necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s). Any scheduled maintenance, as defined in OAC rule 3745-15-06(A)(1), that results in a deviation from a federally enforceable emission limitation (or control requirement) shall be reported in the same manner as described for malfunctions in General Term and Condition A.1.c.i above.

*(Authority for term: OAC rule 3745-77-07(A)(3)(c))*

## 3. Risk Management Plans

If applicable, the permittee shall develop and register a risk management plan pursuant to section 112(r) of the Clean Air Act, as amended, 42 U.S.C. § 7401 et seq. ("Act"); and, pursuant to 40 C.F.R. 68.215(a), the permittee shall submit either of the following:

- a. a compliance plan for meeting the requirements of 40 C.F.R. Part 68 by the date specified in 40 C.F.R. 68.10(a) and OAC 3745-104-05(A); or
- b. as part of the compliance certification submitted under 40 C.F.R. 70.6(c)(5), a certification statement that the source is in compliance with all requirements of 40 C.F.R. Part 68 and OAC Chapter 3745-104, including the registration and submission of the risk management plan.

*(Authority for term: OAC rule 3745-77-07(A)(4))*

## 4. Title IV Provisions

If the permittee is subject to the requirements of 40 CFR Part 72 concerning acid rain, the permittee shall ensure that any affected emissions unit complies with those requirements. Emissions exceeding any allowances that are lawfully held under Title IV of the Act, or any regulations adopted thereunder, are prohibited.

*(Authority for term: OAC rule 3745-77-07(A)(5))*

**5. Severability Clause**

A determination that any term or condition of this permit is invalid shall not invalidate the force or effect of any other term or condition thereof, except to the extent that any other term or condition depends in whole or in part for its operation or implementation upon the term or condition declared invalid.

*(Authority for term: OAC rule 3745-77-07(A)(6))*

**6. General Requirements**

- a. The permittee must comply with all terms and conditions of this permit. Any noncompliance with the federally enforceable terms and conditions of this permit constitutes a violation of the Act, and is grounds for enforcement action or for permit revocation, revocation and reissuance, or modification, or for denial of a permit renewal application.
- b. It shall not be a defense for the permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the federally enforceable terms and conditions of this permit.
- c. This permit may be modified, reopened, revoked, or revoked and reissued, for cause, in accordance with A.10 below. The filing of a request by the permittee for a permit modification, revocation and reissuance, or revocation, or of a notification of planned changes or anticipated noncompliance does not stay any term and condition of this permit.
- d. This permit does not convey any property rights of any sort, or any exclusive privilege.
- e. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon request, the permittee shall also furnish to the Director or an authorized representative of the Director, copies of records required to be kept by this permit. For information claimed to be confidential in the submittal to the Director, if the Administrator of the U.S. EPA requests such information, the permittee may furnish such records directly to the Administrator along with a claim of confidentiality.
- f. Except as otherwise indicated below, this Title V permit, or permit modification, is effective for five years from the original effective date specified in the permit. In the event that this facility becomes eligible for non-title V permits, this permit shall cease to be enforceable upon final issuance of all applicable OAC Chapter 3745-35 operating permits and/or registrations for all subject emissions units located at the facility and:
  - i. the permittee submits an approved facility-wide potential to emit analysis supporting a claim that the facility no longer meets the definition of a “major source” as defined in OAC rule 3745-77-01(W) based on the permanent shutdown and removal of one or more emissions units identified in this permit; or
  - ii. the permittee no longer meets the definition of a “major source” as defined in OAC rule 3745-77-01(W) based on obtaining restrictions on the facility-wide potential(s) to emit that are federally enforceable or legally and practically enforceable ; or
  - iii. a combination of i. and ii. above.

The permittee shall comply with any residual requirements, such as quarterly deviation reports, semi-annual deviation reports, and annual compliance certifications covering the period during which this Title V permit was enforceable. All records relating to this permit must be maintained in accordance with law.

*(Authority for term: OAC rule 3745-77-01(W), OAC rule 3745-77-07(A)(3)(b)(ii), OAC rule 3745-77(A)(7))*

**7. Fees**

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78.

*(Authority for term: OAC rule 3745-77-07(A)(8))*

**8. Marketable Permit Programs**

No revision of this permit is required under any approved economic incentive, marketable permits, emissions trading, and other similar programs or processes for changes that are provided for in this permit.  
(Authority for term: OAC rule 3745-77-07(A)(9))

**9. Reasonably Anticipated Operating Scenarios**

The permittee is hereby authorized to make changes among operating scenarios authorized in this permit without notice to the Ohio EPA, but, contemporaneous with making a change from one operating scenario to another, the permittee must record in a log at the permitted facility the scenario under which the permittee is operating. The permit shield provided in these general terms and conditions shall apply to all operating scenarios authorized in this permit.  
(Authority for term: OAC rule 3745-77-07(A)(10))

**10. Reopening for Cause**

This Title V permit will be reopened prior to its expiration date under the following conditions:

- a. Additional applicable requirements under the Act become applicable to one or more emissions units covered by this permit, and this permit has a remaining term of three or more years. Such a reopening shall be completed not later than eighteen (18) months after promulgation of the applicable requirement. No such reopening is required if the effective date of the requirement is later than the date on which the permit is due to expire, unless the original permit or any of its terms and conditions has been extended pursuant to paragraph (E)(1) of OAC rule 3745-77-08.
- b. This permit is issued to an affected source under the acid rain program and additional requirements (including excess emissions requirements) become applicable. Upon approval by the Administrator, excess emissions offset plans shall be deemed to be incorporated into the permit, and shall not require a reopening of this permit.
- c. The Director of the Ohio EPA or the Administrator of the U.S. EPA determines that the federally applicable requirements in this permit are based on a material mistake, or that inaccurate statements were made in establishing the emissions standards or other terms and conditions of this permit related to such federally applicable requirements.
- d. The Administrator of the U.S. EPA or the Director of the Ohio EPA determines that this permit must be revised or revoked to assure compliance with the applicable requirements.  
(Authority for term: OAC rules 3745-77-07(A)(12) and 3745-77-08(D))

**11. Federal and State Enforceability**

Only those terms and conditions designated in this permit as federally enforceable, that are required under the Act, or any of its applicable requirements, including relevant provisions designed to limit the potential to emit of a source, are enforceable by the Administrator of the U.S. EPA, the State, and citizens under the Act. All other terms and conditions of this permit shall not be federally enforceable and shall be enforceable under State law only.  
(Authority for term: OAC rule 3745-77-07(B))

**12. Compliance Requirements**

- a. Any document (including reports) required to be submitted and required by a federally applicable requirement in this Title V permit shall include a certification by a responsible official that, based on information and belief formed after reasonable inquiry, the statements in the document are true, accurate, and complete.
- b. Upon presentation of credentials and other documents as may be required by law, the permittee shall allow the Director of the Ohio EPA or an authorized representative of the Director to:
  - i. At reasonable times, enter upon the permittee's premises where a source is located or the emissions-related activity is conducted, or where records must be kept under the conditions of this permit.
  - ii. Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit, subject to the protection from disclosure to the public of confidential information consistent with paragraph (E) of OAC rule 3745-77-03.

- iii. Inspect at reasonable times any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit.
  - iv. As authorized by the Act, sample or monitor at reasonable times substances or parameters for the purpose of assuring compliance with the permit and applicable requirements.
- c. The permittee shall submit progress reports to the appropriate Ohio EPA District Office or local air agency concerning any schedule of compliance for meeting an applicable requirement. Progress reports shall be submitted semiannually, or more frequently if specified in the applicable requirement or by the Director of the Ohio EPA. Progress reports shall contain the following:
- i. Dates for achieving the activities, milestones, or compliance required in any schedule of compliance, and dates when such activities, milestones, or compliance were achieved.
  - ii. An explanation of why any dates in any schedule of compliance were not or will not be met, and any preventive or corrective measures adopted.
- d. Compliance certifications concerning the terms and conditions contained in this permit that are federally enforceable emission limitations, standards, or work practices, shall be submitted to the Director (the appropriate Ohio EPA District Office or local air agency) and the Administrator of the U.S. EPA in the following manner and with the following content:
- i. Compliance certifications shall be submitted annually on a calendar year basis. The annual certification shall be submitted (i.e., postmarked) on or before April 30th of each year during the permit term.
  - ii. Compliance certifications shall include the following:
    - (a) An identification of each term or condition of this permit that is the basis of the certification.
    - (b) The permittee's current compliance status.
    - (c) Whether compliance was continuous or intermittent.
    - (d) The method(s) used for determining the compliance status of the source currently and over the required reporting period.
    - (e) Such other facts as the Director of the Ohio EPA may require in the permit to determine the compliance status of the source.
  - iii. Compliance certifications shall contain such additional requirements as may be specified pursuant to sections 114(a)(3) and 504(b) of the Act.

*(Authority for term: OAC rules 3745-77-07(C)(1),(2),(4) and (5) and ORC section 3704.03(L))*

### **13. Permit Shield**

- a. Compliance with the terms and conditions of this permit (including terms and conditions established for alternate operating scenarios, emissions trading, and emissions averaging, but excluding terms and conditions for which the permit shield is expressly prohibited under OAC rule 3745-77-07) shall be deemed compliance with the applicable requirements identified and addressed in this permit as of the date of permit issuance.
  - b. This permit shield provision shall apply to any requirement identified in this permit pursuant to OAC rule 3745-77-07(F)(2), as a requirement that does not apply to the source or to one or more emissions units within the source.
- (Authority for term: OAC rule 3745-77-07(F))*

### **14. Operational Flexibility**

The permittee is authorized to make the changes identified in OAC rule 3745-77-07(H)(1)(a) to (H)(1)(c) within the permitted stationary source without obtaining a permit revision, if such change is not a modification under any provision of Title I of the Act [as defined in OAC rule 3745-77-01(JJ)], and does not result in an exceedance of the emissions allowed

under this permit (whether expressed therein as a rate of emissions or in terms of total emissions), and the permittee provides the Administrator of the U.S. EPA and the appropriate Ohio EPA District Office or local air agency with written notification within a minimum of seven days in advance of the proposed changes, unless the change is associated with, or in response to, emergency conditions. If less than seven days notice is provided because of a need to respond more quickly to such emergency conditions, the permittee shall provide notice to the Administrator of the U.S. EPA and the appropriate District Office of the Ohio EPA or local air agency as soon as possible after learning of the need to make the change. The notification shall contain the items required under OAC rule 3745-77-07(H)(2)(d).

*(Authority for term: OAC rules 3745-77-07(H)(1) and (2))*

**15. Emergencies**

The permittee shall have an affirmative defense of emergency to an action brought for noncompliance with technology-based emission limitations if the conditions of OAC rule 3745-77-07(G)(3) are met. This emergency defense provision is in addition to any emergency or upset provision contained in any applicable requirement.

*(Authority for term: OAC rule 3745-77-07(G))*

**16. Off-Permit Changes**

The owner or operator of a Title V source may make any change in its operations or emissions at the source that is not specifically addressed or prohibited in the Title V permit, without obtaining an amendment or modification of the permit, provided that the following conditions are met:

- a. The change does not result in conditions that violate any applicable requirements or that violate any existing federally enforceable permit term or condition.
- b. The permittee provides contemporaneous written notice of the change to the Director and the Administrator of the U.S. EPA, except that no such notice shall be required for changes that qualify as insignificant emissions levels or activities as defined in OAC rule 3745-77-01(U). Such written notice shall describe each such change, the date of such change, any change in emissions or pollutants emitted, and any federally applicable requirement that would apply as a result of the change.
- c. The change shall not qualify for the permit shield under OAC rule 3745-77-07(F).
- d. The permittee shall keep a record describing all changes made at the source that result in emissions of a regulated air pollutant subject to an applicable requirement, but not otherwise regulated under the permit, and the emissions resulting from those changes.
- e. The change is not subject to any applicable requirement under Title IV of the Act or is not a modification under any provision of Title I of the Act.

Paragraph (I) of rule 3745-77-07 of the Administrative Code applies only to modification or amendment of the permittee's Title V permit. The change made may require a permit to install under Chapter 3745-31 of the Administrative Code if the change constitutes a modification as defined in that Chapter. Nothing in paragraph (I) of rule 3745-77-07 of the Administrative Code shall affect any applicable obligation under Chapter 3745-31 of the Administrative Code.

*(Authority for term: OAC rule 3745-77-07(I))*

**17. Compliance Method Requirements**

Nothing in this permit shall alter or affect the ability of any person to establish compliance with, or a violation of, any applicable requirement through the use of credible evidence to the extent authorized by law. Nothing in this permit shall be construed to waive any defenses otherwise available to the permittee, including but not limited to, any challenge to the Credible Evidence Rule (see 62 Fed. Reg. 8314, Feb. 24, 1997), in the context of any future proceeding.

*(This term is provided for informational purposes only.)*

**18. Insignificant Activities or Emissions Levels**

Each IEU that has one or more applicable requirements shall comply with those applicable requirements.

*(Authority for term: OAC rule 3745-77-07(A)(1))*

**19. Permit to Install Requirement**

Prior to the “installation” or “modification” of any “air contaminant source,” as those terms are defined in OAC rule 3745-31-01, a permit to install must be obtained from the Ohio EPA pursuant to OAC Chapter 3745-31.

*(Authority for term: OAC rule 3745-77-07(A)(1))*

**20. Air Pollution Nuisance**

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

*(Authority for term: OAC rule 3745-77-07(A)(1))*

**21. Permanent Shutdown of an Emissions Unit**

The permittee may notify Ohio EPA of any emissions unit that is permanently shut down by submitting a certification from the responsible official that identifies the date on which the emissions unit was permanently shut down. Authorization to operate the affected emissions unit shall cease upon the date certified by the responsible official that the emissions unit was permanently shut down.

After the date on which an emissions unit is permanently shut down (i.e., that has been physically removed from service or has been altered in such a way that it can no longer operate without a subsequent “modification” or “installation” as defined in OAC Chapter 3745-31 and therefore ceases to meet the definition of an “emissions unit” as defined in OAC rule 3745-77-01(O)), rendering existing permit terms and conditions irrelevant, the permittee shall not be required, after the date of the certification and submission to Ohio EPA, to meet any Title V permit requirements applicable to that emissions unit, except for any residual requirements, such as the quarterly deviation reports, semi-annual deviation reports and annual compliance certification covering the period during which the emissions unit last operated. All records relating to the shutdown emissions unit, generated while the emissions unit was in operation, must be maintained in accordance with law.

No emissions unit certified by the responsible official as being permanently shut down may resume operation without first applying for and obtaining a permit to install pursuant to OAC Chapter 3745-31.

*(Authority for term: OAC rule 3745-77-01)*

**22. Title VI Provisions**

If applicable, the permittee shall comply with the standards for recycling and reducing emissions of ozone depleting substances pursuant to 40 CFR Part 82, Subpart F, except as provided for motor vehicle air conditioners in Subpart B of 40 CFR Part 82:

- a. Persons opening appliances for maintenance, service, repair, or disposal must comply with the required practices specified in 40 CFR 82.156.
- b. Equipment used during the maintenance, service, repair, or disposal of appliances must comply with the standards for recycling and recovery equipment specified in 40 CFR 82.158.
- c. Persons performing maintenance, service, repair, or disposal of appliances must be certified by an approved technician certification program pursuant to 40 CFR 82.161.

*(Authority for term: OAC rule 3745-77-01(H)(11))*

**B. State Only Enforceable Section**

**1. Reporting Requirements Related to Monitoring and Record Keeping Requirements**

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or record keeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (i) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and record keeping requirements specified in this permit, (ii) the probable cause of such deviations, and (iii) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. In identifying each deviation, the permittee shall specify the applicable requirement for which the deviation occurred, describe each deviation, and provide the magnitude and duration of each deviation. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted (i.e., postmarked) quarterly, by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

**2. Records Retention Requirements**

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

**3. Inspections and Information Requests**

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

**4. Scheduled Maintenance/Malfunction Reporting**

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

**5. Permit Transfers**

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

**6. Additional Reporting Requirements When There Are No Deviations of Federally Enforceable Emission Limitations, Operational Restrictions, or Control Device Operating Parameter Limitations (See Section A of This Permit)**

If no emission limitation (or control requirement), operational restriction and/or control device parameter limitation deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations

occurred during that quarter. The reports shall be submitted (i.e., postmarked) by January 31, April 30, July 31, and October 31 of each year; and each report shall cover the previous calendar quarter.

The permittee is not required to submit a quarterly report which states that no deviations occurred during that quarter for the following situations:

- a. where an emissions unit has deviation reporting requirements for a specific emission limitation, operational restriction, or control device parameter limitation that override the deviation reporting requirements specified in General Term and Condition A.1.c.ii; or
- b. where an uncontrolled emissions unit has no monitoring, record keeping, or reporting requirements and the emissions unit's applicable emission limitations are established at the potentials to emit; or
- c. where the company's responsible official has certified that an emissions unit has been permanently shut down.

## Part II - Specific Facility Terms and Conditions

### A. State and Federally Enforceable Section

1. Pursuant to 40 CFR Part 64, the permittee has submitted, and the Ohio EPA has approved a compliance assurance monitoring plan for emissions units P001 and P010 at this facility. The permittee shall comply with the provisions of the plan during any operation of the aforementioned emissions units.

(Authority for term: 40 CFR Part 64)

2. The following insignificant emissions units are located at this facility:

B016-natural gas fired make-up air heater #1-process building (permit to install 03-6093);  
B017-natural gas fired make-up air heater #2-process building (permit to install 03-6093);  
B018-natural gas fired make-up air heater #3-process building (permit to install 03-6093);  
B019-natural gas fired make-up air heater #4-process building (permit to install 03-6093);  
B020-natural gas fired make-up air heater #5-process building (permit to install 03-6093);  
B021-natural gas fired make-up air heater #6-process building (permit to install 03-6093);  
B022-natural gas fired make-up air heater #7-process building (permit to install 03-6093);  
B031-natural gas fired make-up air heater #8-process building (permit to install 03-6093);  
B032-natural gas fired make-up air heater #9-process building (permit to install 03-6093);  
B033-natural gas fired make-up air heater #10-process building (permit to install 03-6093);  
B034-natural gas fired make-up air heater #11-process building (permit to install 03-6093);  
B035-natural gas fired make-up air heater #12-process building (permit to install 03-6093);  
B036-natural gas fired make-up air heater #13-process building (permit to install 03-6093);  
P003-cleaner strip dryer #2 (permit to install 03-6093);  
P004-tension leveler strip dryer #4 (permit to install 03-6093);  
P007-zinc induction pot (permit to install 03-5443);  
P008-galvanneal induction furnace (permit to install 03-5443) and  
P009-continuous alkaline cleaner with packer tower scrubber (permit to install 03-5443).

Each insignificant emissions unit at this facility must comply with all applicable State and federal regulations, and well as any emission limitations and/or control requirements contained within the identified permit to install for the emissions unit. Insignificant emissions units listed above that are not subject to specific permit to install requirements are subject to one or more applicable requirements contained in the federally-approved versions of OAC Chapters 3745-17, 3745-18, and/or 3745-21.

### B. State Only Enforceable Section

1. The following insignificant emissions units located at this facility are exempt from permit requirements because they are not subject to any applicable requirements (as defined in OAC rule 3745-77-01(H)), or because they meet the "de minimis" criteria established in OAC rule 3745-15-05:

electrostatic oiler-CGL (Z001);  
electrostatic oiler-SST (Z002);  
matthews strip ink jet printer (Z004);  
strip dryer #1 cleaner section (Z011);  
matthews strip ink jet printer CGL2 (Z047);  
emergency generator CGL1 (Z048);  
emergency generator CGL2 (Z049);  
firewater pump engine (Z050);  
cold cleaner/parts washer C208 (Z051);  
cold cleaner/parts washer C234 (Z052);  
CGL2 delivery electrostatic oiler (Z054) and  
IST electrostack oiler (Z055).

### Part III - Terms and Conditions for Emissions Units

**Emissions Unit ID:** B1-CGL (B001)  
**Activity Description:** Hot Water Boiler #1 (14.7 MMBtu/hr)

#### A. State and Federally Enforceable Section

##### I. Applicable Emissions Limitations and/or Control Requirements

- The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
14.7 mm Btu/hr, natural gas-fired boiler, with low NOx burners	OAC rule 3745-31-05(A)(3) (PTI #03-14070, issued November 8, 2007 corrected copy issued January 24, 2008)	0.49 lb nitrogen oxide (NOx)/hr; 2.15 tons NOx/yr
		0.54 lb carbon monoxide (CO)/hr; 2.4 tons CO/yr
		0.11 lb particulate emissions (PE)/hr; 0.5 ton PE/yr
		control requirements (See A.I.2.a.)
		See A.I.2.b.
	40 CFR, Part 60, Subpart Dc	recordkeeping requirements (See A.III.2.)
	OAC rule 3745-17-07(A)(1)	Visible PE shall not exceed 20% opacity as a 6-minute average, except as provided by rule.
	OAC rule 3745-18-06	Exempt (See A.I.2.c.)
	OAC rule 3745-17-10(B)(1)	See A.I.2.d.
	OAC rule 3745-21-08(B)	See A.I.2.e.

##### 2. Additional Terms and Conditions

- Best available technology (BAT) control requirements for this emissions unit has been determined to be use of low NOx burners. BAT also includes compliance with the terms and conditions of this permit.

Pro Tec Company agreed and consented to entry into a Consent Decree with the United States of America (Civil Action No. 3:98CV 7749, entered 2/11/98) requiring the permittee to install natural gas fired low NOx burners on this emissions unit. The consent decree also required this emissions unit to achieve an emission rate not to exceed 0.033 lbs NOx/mmBtu, which is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05 (A)(3).

- The requirements of this rule also include compliance with the requirements of OAC rule 3745-17-07(A)(1) and 40 CFR, Part 60, Subpart Dc.

## 2. Additional Terms and Conditions (continued)

- 2.c This emissions unit is exempt from the requirements of OAC rule 3745-18-06 pursuant to OAC rule 3745-18-06(A).
- 2.d The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
- 2.e The permittee has satisfied the "best available control techniques and operating practices" required pursuant to OAC rule 3745-21-08(B) by committing to comply with the best available technology requirements established pursuant to OAC rule 3745-31-05 (A)(3) in Permit to Install 03-14070.

On November 5, 2002, OAC rule 3745-21-08 was revised to delete paragraph (B); therefore, paragraph (B) is no longer part of the State regulations. However, that rule revision has not yet been submitted to the U.S. EPA as a revision to Ohio's State Implementation Plan (SIP). Therefore, until the SIP revision occurs and the U.S. EPA approves the revisions to OAC rule 3745-21-08, the requirement to satisfy the "best available control techniques and operating practices" still exists as part of the federally-approved SIP for Ohio.

## II. Operational Restrictions

- 1. The permittee shall burn only natural gas in this emissions unit.

[Authority for term: OAC rule 3745-77-07(A)(1) and PTI 03-14070]

## III. Monitoring and/or Record Keeping Requirements

- 1. For each day during which the permittee burns a fuel other than natural gas, the permittee shall maintain a record of the type and quantity of fuel burned in this emissions unit.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

- 2. The permittee shall record and maintain records of the amounts of each fuel combusted during each day.

[Authority for term: OAC rule 3745-77-07(C)(1), 40 CFR 60.48c(g) and PTI 03-14070]

- 3. While performing each burner tuning, the permittee shall record the results of the burner tuning using the Burner Tuning Reporting Form for Boilers form (as found in term VI.3). An alternative form may be used upon approval of the appropriate Ohio EPA District Office or local air agency.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

## IV. Reporting Requirements

- 1. The permittee shall submit deviation (excursion) reports that identify each day when a fuel other than natural gas was burned in this emissions unit. Each report shall be submitted within 30 days after the deviation occurs.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

- 2. The permittee shall submit notification of the following:

- 2.a date maximum capacity of this emissions unit was physically and permanently reduced (no later than 30 days after such date);
- 2.b the maximum heat input capacity of and identification of fuels to be combusted in this emissions unit (same due date as in A.IV.3.a above); and

#### **IV. Reporting Requirements (continued)**

- 2.c** actual start-up date under reduced maximum capacity (within 15 days after such date).

Notifications are to be sent to:

Ohio Environmental Protection Agency  
DAPC - Permit Management Unit  
P. O. Box 163669  
Columbus, Ohio 43216-3669

and

Ohio Environmental Protection Agency  
Northwest District Office  
Division of Air Pollution Control  
347 North Dunbridge Road  
Bowling Green, OH 43402

[Authority for term: OAC rule 3745-77-07(C)(1) and 40 CFR Part 60.48c(j)]

- 3.** The permittee shall submit a copy of the Burner Tuning Reporting Form for Boilers form to the appropriate Ohio EPA district office or local air agency to summarize the results of each burner tuning procedure. These reports shall be submitted to the Ohio EPA district office or local air agency by January 31 of each year and shall cover the previous calendar year.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

#### **V. Testing Requirements**

- 1.** Compliance with the emission limitations in section A.I. of the terms and conditions of this permit shall be determined in accordance with the following methods:

- 1.a** Emission Limitations:  
0.49 lb NO<sub>x</sub>/hr and 2.15 TPY

Applicable Compliance Method:

The hourly and annual emission limitations represent the potential to emit (PTE)\* of the emissions unit. Therefore, no monitoring and record keeping, reporting, or compliance method calculations are required to demonstrate compliance with these limitations. If required, the permittee shall demonstrate compliance with the hourly limitation in accordance with the test methods and procedures in Methods 1 through 4 and 7 of 40 CFR Part 60, Appendix A.

\*The PTE for this emissions unit is based on the maximum capacity of the boiler of 14.7 mm Btu/hr and the vendor supplied emission factor of 0.0241 lbs NO<sub>x</sub>/mm Btu. The annual PTE is based on the hourly PTE and a maximum operating schedule of 8,760 hrs/yr.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

## V. Testing Requirements (continued)

- 1.b** Emission Limitations:  
0.54 lb CO/hr and 2.4 TPY

**Applicable Compliance Method:**

The hourly and annual emission limitations represent the PTE\* of the emissions unit. Therefore, no monitoring and record keeping, reporting, or compliance method calculations are required to demonstrate compliance with these limitations. If required, the permittee shall demonstrate compliance with the hourly limitation in accordance with the test methods and procedures in Methods 1 through 4 and 10 of 40 CFR Part 60, Appendix A.

\*The PTE for this emissions unit is based on the maximum capacity of the boiler of 14.7 mm Btu/hr and the vendor supplied emission factor of 0.0367 lb CO/mm Btu. The annual PTE is based on the hourly PTE and a maximum operating schedule of 8,760 hrs/yr.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

- 1.c** Emission Limitations:  
0.11 lb PE/hr and 0.5 TPY

**Applicable Compliance Method:**

The hourly and annual emission limitations represent the PTE\* of the emissions unit. Therefore, no monitoring and record keeping, reporting, or compliance method calculations are required to demonstrate compliance with these limitations. If required, the permittee shall demonstrate compliance with the test methods and procedures in Methods 1 through 5 of 40 CFR Part 60, Appendix A.

\*The PTE for this emissions unit is based on the maximum capacity of the boiler (14.7 mm Btu/hr), the heat content of natural gas (1020 Btu/mmft<sup>3</sup>), and an emission factor of 7.6 lbs PE/1000 mmft<sup>3</sup> of natural gas burned (AP-42 Table 1.4-2, dated 9/98). The annual PTE is based on the hourly PTE and a maximum operating schedule of 8,760 hrs/yr.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

- 1.d** Emission Limitation:  
Visible PE shall not exceed 20% opacity, as a 6-minute average, except as provided by the rule.

**Applicable Compliance Method:** If required, the method to be employed to demonstrate compliance with the visible PE limitation shall be OAC rule 3745-17-03(B)(1).

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

- 2.** The permittee may conduct periodic tuning of the boiler burner. The purpose of this tuning is to ensure that the burner is adjusted properly so that air pollution emissions remain in compliance with allowable emission rates and are minimized.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

- 3.** Technicians who conduct the burner tuning must be qualified to perform the expected tasks. The permittee is required to provide training to the technicians who perform the burner tuning procedure. Technicians who are qualified shall, at a minimum, have passed manufacturer's training concerning burner tuning, or have been trained by someone who has completed the manufacturer's training concerning burner tuning.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

- 4.** The permittee shall properly operate and maintain portable device(s) to monitor the concentration of NO<sub>x</sub> in the stack exhaust gases from this emissions unit. The monitor(s) shall be capable of measuring the expected concentrations of the measured gases. The monitoring equipment shall be calibrated, operated and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall maintain records of each portable monitoring device's calibration.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

## V. Testing Requirements (continued)

5. The first steps concerning burner tuning involve setting the pollutant baseline levels (concentrations) utilizing the portable monitor. These baselines shall be set during the initial U.S. EPA approved emissions testing that demonstrated the emissions unit was in compliance with all applicable emissions limitations as described in E.1.a. The baselines shall be determined for NO<sub>x</sub>. Sampling should measure the exhaust gas values exiting the baghouse. The duration of each sample shall follow the portable monitor manufacturer's recommendations. Record these values on the Burner Tuning Reporting Form for Boilers form (as found in F.3) in the "Recent Stack Test Basis Values" column.

Once the pollutant baseline levels are set, the burner shall be next tuned based on the frequency described in E.2.e. The general procedure for tuning the burner involves the following steps:

- 5.a Review the plant operations to ensure the boiler is operating normally.
- 5.b Confirm that the portable monitor is calibrated per the manufacturer's specifications.
- 5.c Using the calibrated monitor and monitor manufacturer's recommended sampling duration, measure the stack exhaust gas values for NO<sub>x</sub>. These measurements shall be taken at the same location as the location where the baseline samples were taken. Record the values in the "Pre Tuning" results column on the Burner Tuning Reporting Form for Boilers form.
- 5.d Compare the measured stack exhaust gas values with the pollutant baseline values. If all of the measured stack exhaust gas values are equal to or less than 115 percent of the pollutant baseline values, then it is not necessary to tune the burner. Go on to section v. below. The permittee shall have the burners tuned within two calendar weeks of any measured stack exhaust values greater than 115 percent of the baseline values. Make any necessary adjustments and repairs. Repeat sections iii. and iv. until the measured stack exhaust gas values are equal to or less than 115 percent of the pollutant baseline values.
- 5.e Once all of the measured stack exhaust gas values are within the 115 percent of the pollutant baseline values, record the measured stack exhaust gas values in the "Post Tuning" results column on the Burner Tuning Reporting Form for Boilers form.
- 5.f By January 31st of each year, submit a copy of all Burner Tuning Reporting Form for Boilers forms produced during the past calendar year to the Ohio EPA District Office or local air agency responsible for the permitting of the facility.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

6. The permittee shall conduct the burner tuning procedure at a frequency to be determined and approved by the Ohio EPA Northwest District Office.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

7. The firing rate of the boiler shall be at least 11.0 mmBtu/hr and such to maintain a steady-state water temperature of 179 degrees F at the cleaner section of the continuous galvanizing line when stack testing or burner tuning is being conducted.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

## VI. Miscellaneous Requirements

None

**B. State Enforceable Section**

**I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
14.7 mm Btu/hr, natural gas-fired boiler, with low NOx burners	none	none

**2. Additional Terms and Conditions**

None

**II. Operational Restrictions**

None

**III. Monitoring and/or Record Keeping Requirements**

None

**IV. Reporting Requirements**

None

**V. Testing Requirements**

None

**VI. Miscellaneous Requirements**

None

### Part III - Terms and Conditions for Emissions Units

**Emissions Unit ID:** B2-CGL (B002)  
**Activity Description:** Hot Water Boiler #2 (14.7 MMBtu/hr)

#### A. State and Federally Enforceable Section

##### I. Applicable Emissions Limitations and/or Control Requirements

- The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
14.7 mm Btu/hr, natural gas-fired boiler, with low NOx burners	OAC rule 3745-31-05(A)(3) (PTI #03-14070, issued November 8, 2007 corrected copy issued January 24, 2008)	0.49 lb nitrogen oxide (NOx)/hr; 2.15 tons NOx/yr
		0.54 lb carbon monoxide (CO)/hr; 2.4 tons CO/yr
		0.11 lb particulate emissions (PE)/hr; 0.5 ton PE/yr
		control requirements (See A.I.2.a.)
		See A.I.2.b.
	40 CFR, Part 60, Subpart Dc	recordkeeping requirements (See A.III.2.)
	OAC rule 3745-17-07(A)(1)	Visible PE shall not exceed 20% opacity as a 6-minute average, except as provided by rule.
	OAC rule 3745-18-06	Exempt (See A.I.2.c.)
	OAC rule 3745-17-10(B)(1)	See A.I.2.d.
	OAC rule 3745-21-08(B)	See A.I.2.e.

##### 2. Additional Terms and Conditions

- Best available technology (BAT) control requirements for this emissions unit has been determined to be use of low NOx burners. BAT also includes compliance with the terms and conditions of this permit.

Pro Tec Company agreed and consented to entry into a Consent Decree with the United States of America (Civil Action No. 3:98CV 7749, entered 2/11/98) requiring the permittee to install natural gas fired low NOx burners on this emissions unit. The consent decree also required this emissions unit to achieve an emission rate not to exceed 0.033 lbs NOx/mmBtu, which is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05 (A)(3).

- The requirements of this rule also include compliance with the requirements of OAC rule 3745-17-07(A)(1) and 40 CFR, Part 60, Subpart Dc.

## 2. Additional Terms and Conditions (continued)

- 2.c This emissions unit is exempt from the requirements of OAC rule 3745-18-06 pursuant to OAC rule 3745-18-06(A).
- 2.d The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
- 2.e The permittee has satisfied the "best available control techniques and operating practices" required pursuant to OAC rule 3745-21-08(B) by committing to comply with the best available technology requirements established pursuant to OAC rule 3745-31-05 (A)(3) in Permit to Install 03-14070.

On November 5, 2002, OAC rule 3745-21-08 was revised to delete paragraph (B); therefore, paragraph (B) is no longer part of the State regulations. However, that rule revision has not yet been submitted to the U.S. EPA as a revision to Ohio's State Implementation Plan (SIP). Therefore, until the SIP revision occurs and the U.S. EPA approves the revisions to OAC rule 3745-21-08, the requirement to satisfy the "best available control techniques and operating practices" still exists as part of the federally-approved SIP for Ohio.

## II. Operational Restrictions

- 1. The permittee shall burn only natural gas in this emissions unit.

[Authority for term: OAC rule 3745-77-07(A)(1) and PTI 03-14070]

## III. Monitoring and/or Record Keeping Requirements

- 1. For each day during which the permittee burns a fuel other than natural gas, the permittee shall maintain a record of the type and quantity of fuel burned in this emissions unit.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

- 2. The permittee shall record and maintain records of the amounts of each fuel combusted during each day.

[Authority for term: OAC rule 3745-77-07(C)(1), 40 CFR 60.48c(g) and PTI 03-14070]

- 3. While performing each burner tuning, the permittee shall record the results of the burner tuning using the Burner Tuning Reporting Form for Boilers form (as found in term VI.3). An alternative form may be used upon approval of the appropriate Ohio EPA District Office or local air agency.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

## IV. Reporting Requirements

- 1. The permittee shall submit deviation (excursion) reports that identify each day when a fuel other than natural gas was burned in this emissions unit. Each report shall be submitted within 30 days after the deviation occurs.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

- 2. The permittee shall submit notification of the following:

- 2.a date maximum capacity of this emissions unit was physically and permanently reduced (no later than 30 days after such date);
- 2.b the maximum heat input capacity of and identification of fuels to be combusted in this emissions unit (same due date as in A.IV.3.a above); and

#### IV. Reporting Requirements (continued)

- 2.c** actual start-up date under reduced maximum capacity (within 15 days after such date).

Notifications are to be sent to:

Ohio Environmental Protection Agency  
DAPC - Permit Management Unit  
P. O. Box 163669  
Columbus, Ohio 43216-3669

and

Ohio Environmental Protection Agency  
Northwest District Office  
Division of Air Pollution Control  
347 North Dunbridge Road  
Bowling Green, OH 43402

[Authority for term: OAC rule 3745-77-07(C)(1) and 40 CFR Part 60.48c(j)]

- 3.** The permittee shall submit a copy of the Burner Tuning Reporting Form for Boilers form to the appropriate Ohio EPA district office or local air agency to summarize the results of each burner tuning procedure. These reports shall be submitted to the Ohio EPA district office or local air agency by January 31 of each year and shall cover the previous calendar year.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

#### V. Testing Requirements

- 1.** Compliance with the emission limitations in section A.I. of the terms and conditions of this permit shall be determined in accordance with the following methods:

- 1.a** Emission Limitations:  
0.49 lb NO<sub>x</sub>/hr and 2.15 TPY

Applicable Compliance Method:

The hourly and annual emission limitations represent the potential to emit (PTE)\* of the emissions unit. Therefore, no monitoring and record keeping, reporting, or compliance method calculations are required to demonstrate compliance with these limitations. If required, the permittee shall demonstrate compliance with the hourly limitation in accordance with the test methods and procedures in Methods 1 through 4 and 7 of 40 CFR Part 60, Appendix A.

\*The PTE for this emissions unit is based on the maximum capacity of the boiler of 14.7 mm Btu/hr and the vendor supplied emission factor of 0.0241 lbs NO<sub>x</sub>/mm Btu. The annual PTE is based on the hourly PTE and a maximum operating schedule of 8,760 hrs/yr.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

## V. Testing Requirements (continued)

- 1.b** Emission Limitations:  
0.54 lb CO/hr and 2.4 TPY

**Applicable Compliance Method:**

The hourly and annual emission limitations represent the PTE\* of the emissions unit. Therefore, no monitoring and record keeping, reporting, or compliance method calculations are required to demonstrate compliance with these limitations. If required, the permittee shall demonstrate compliance with the hourly limitation in accordance with the test methods and procedures in Methods 1 through 4 and 10 of 40 CFR Part 60, Appendix A.

\*The PTE for this emissions unit is based on the maximum capacity of the boiler of 14.7 mm Btu/hr and the vendor supplied emission factor of 0.0367 lb CO/mm Btu. The annual PTE is based on the hourly PTE and a maximum operating schedule of 8,760 hrs/yr.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

- 1.c** Emission Limitations:  
0.11 lb PE/hr and 0.5 TPY

**Applicable Compliance Method:**

The hourly and annual emission limitations represent the PTE\* of the emissions unit. Therefore, no monitoring and record keeping, reporting, or compliance method calculations are required to demonstrate compliance with these limitations. If required, the permittee shall demonstrate compliance with the test methods and procedures in Methods 1 through 5 of 40 CFR Part 60, Appendix A.

\*The PTE for this emissions unit is based on the maximum capacity of the boiler (14.7 mm Btu/hr), the heat content of natural gas (1020 Btu/mmft<sup>3</sup>), and an emission factor of 7.6 lbs PE/1000 mmft<sup>3</sup> of natural gas burned (AP-42 Table 1.4-2, dated 9/98). The annual PTE is based on the hourly PTE and a maximum operating schedule of 8,760 hrs/yr.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

- 1.d** Emission Limitation:  
Visible PE shall not exceed 20% opacity, as a 6-minute average, except as provided by the rule.

**Applicable Compliance Method:** If required, the method to be employed to demonstrate compliance with the visible PE limitation shall be OAC rule 3745-17-03(B)(1).

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

- 2.** The permittee may conduct periodic tuning of the boiler burner. The purpose of this tuning is to ensure that the burner is adjusted properly so that air pollution emissions remain in compliance with allowable emission rates and are minimized.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

- 3.** Technicians who conduct the burner tuning must be qualified to perform the expected tasks. The permittee is required to provide training to the technicians who perform the burner tuning procedure. Technicians who are qualified shall, at a minimum, have passed manufacturer's training concerning burner tuning, or have been trained by someone who has completed the manufacturer's training concerning burner tuning.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

- 4.** The permittee shall properly operate and maintain portable device(s) to monitor the concentration of NO<sub>x</sub> in the stack exhaust gases from this emissions unit. The monitor(s) shall be capable of measuring the expected concentrations of the measured gases. The monitoring equipment shall be calibrated, operated and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall maintain records of each portable monitoring device's calibration.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

## V. Testing Requirements (continued)

5. The first steps concerning burner tuning involve setting the pollutant baseline levels (concentrations) utilizing the portable monitor. These baselines shall be set during the initial U.S. EPA approved emissions testing that demonstrated the emissions unit was in compliance with all applicable emissions limitations as described in E.1.a. The baselines shall be determined for NO<sub>x</sub>. Sampling should measure the exhaust gas values exiting the baghouse. The duration of each sample shall follow the portable monitor manufacturer's recommendations. Record these values on the Burner Tuning Reporting Form for Boilers form (as found in F.3) in the "Recent Stack Test Basis Values" column.

Once the pollutant baseline levels are set, the burner shall be next tuned based on the frequency described in E.2.e. The general procedure for tuning the burner involves the following steps:

- 5.a Review the plant operations to ensure the boiler is operating normally.
- 5.b Confirm that the portable monitor is calibrated per the manufacturer's specifications.
- 5.c Using the calibrated monitor and monitor manufacturer's recommended sampling duration, measure the stack exhaust gas values for NO<sub>x</sub>. These measurements shall be taken at the same location as the location where the baseline samples were taken. Record the values in the "Pre Tuning" results column on the Burner Tuning Reporting Form for Boilers form.
- 5.d Compare the measured stack exhaust gas values with the pollutant baseline values. If all of the measured stack exhaust gas values are equal to or less than 115 percent of the pollutant baseline values, then it is not necessary to tune the burner. Go on to section v. below. The permittee shall have the burners tuned within two calendar weeks of any measured stack exhaust values greater than 115 percent of the baseline values. Make any necessary adjustments and repairs. Repeat sections iii. and iv. until the measured stack exhaust gas values are equal to or less than 115 percent of the pollutant baseline values.
- 5.e Once all of the measured stack exhaust gas values are within the 115 percent of the pollutant baseline values, record the measured stack exhaust gas values in the "Post Tuning" results column on the Burner Tuning Reporting Form for Boilers form.
- 5.f By January 31st of each year, submit a copy of all Burner Tuning Reporting Form for Boilers forms produced during the past calendar year to the Ohio EPA District Office or local air agency responsible for the permitting of the facility.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

6. The permittee shall conduct the burner tuning procedure at a frequency to be determined and approved by the Ohio EPA Northwest District Office.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

7. The firing rate of the boiler shall be at least 11.0 mmBtu/hr and such to maintain a steady-state water temperature of 179 degrees F at the cleaner section of the continuous galvanizing line when stack testing or burner tuning is being conducted.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

## VI. Miscellaneous Requirements

None

**B. State Enforceable Section**

**I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
14.7 mm Btu/hr, natural gas-fired boiler, with low NOx burners	none	none

**2. Additional Terms and Conditions**

None

**II. Operational Restrictions**

None

**III. Monitoring and/or Record Keeping Requirements**

None

**IV. Reporting Requirements**

None

**V. Testing Requirements**

None

**VI. Miscellaneous Requirements**

None

### Part III - Terms and Conditions for Emissions Units

**Emissions Unit ID:** B3-CGL2 (B043)  
**Activity Description:** Hot Water Boiler #3 (14.7 MMBTU/hr)

#### A. State and Federally Enforceable Section

##### I. Applicable Emissions Limitations and/or Control Requirements

- The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
14.7 mm Btu/hr, natural gas-fired boiler, with low NOx burners	OAC rule 3745-31-05(A)(3) (PTI #03-14070, issued November 8, 2007 corrected copy issued January 24, 2008)	0.49 lb nitrogen oxide (NOx)/hr; 2.15 tons NOx/yr
		0.54 lb carbon monoxide (CO)/hr; 2.4 tons CO/yr
		0.11 lb particulate emissions (PE)/hr; 0.5 ton PE/yr
		control requirements (See A.I.2.a.)
		See A.I.2.b.
		recordkeeping requirements (See A.III.2.)
	OAC rule 3745-17-07(A)(1)	Visible PE shall not exceed 20% opacity as a 6-minute average, except as provided by rule.
	OAC rule 3745-18-06	Exempt (See A.I.2.c.)
	OAC rule 3745-17-10(B)(1)	See A.I.2.d.
	OAC rule 3745-21-08(B)	See A.I.2.e.

##### 2. Additional Terms and Conditions

- Best available technology (BAT) control requirements for this emissions unit has been determined to be use of low NOx burners. BAT also includes compliance with the terms and conditions of this permit.

Pro Tec Company agreed and consented to entry into a Consent Decree with the United States of America (Civil Action No. 3:98CV 7749, entered 2/11/98) requiring the permittee to install natural gas fired low NOx burners on this emissions unit. The consent decree also required this emissions unit to achieve an emission rate not to exceed 0.033 lbs NOx/mmBtu, which is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05 (A)(3).

- The requirements of this rule also include compliance with the requirements of OAC rule 3745-17-07(A)(1) and 40 CFR, Part 60, Subpart Dc.

## 2. Additional Terms and Conditions (continued)

- 2.c This emissions unit is exempt from the requirements of OAC rule 3745-18-06 pursuant to OAC rule 3745-18-06(A).
- 2.d The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
- 2.e The permittee has satisfied the "best available control techniques and operating practices" required pursuant to OAC rule 3745-21-08(B) by committing to comply with the best available technology requirements established pursuant to OAC rule 3745-31-05 (A)(3) in Permit to Install 03-14070.

On November 5, 2002, OAC rule 3745-21-08 was revised to delete paragraph (B); therefore, paragraph (B) is no longer part of the State regulations. However, that rule revision has not yet been submitted to the U.S. EPA as a revision to Ohio's State Implementation Plan (SIP). Therefore, until the SIP revision occurs and the U.S. EPA approves the revisions to OAC rule 3745-21-08, the requirement to satisfy the "best available control techniques and operating practices" still exists as part of the federally-approved SIP for Ohio.

## II. Operational Restrictions

- 1. The permittee shall burn only natural gas in this emissions unit.

[Authority for term: OAC rule 3745-77-07(A)(1) and PTI 03-14070]

## III. Monitoring and/or Record Keeping Requirements

- 1. For each day during which the permittee burns a fuel other than natural gas, the permittee shall maintain a record of the type and quantity of fuel burned in this emissions unit.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

- 2. The permittee shall record and maintain records of the amounts of each fuel combusted during each day.

[Authority for term: OAC rule 3745-77-07(C)(1), 40 CFR 60.48c(g) and PTI 03-14070]

- 3. While performing each burner tuning, the permittee shall record the results of the burner tuning using the Burner Tuning Reporting Form for Boilers form (as found in term VI.3). An alternative form may be used upon approval of the appropriate Ohio EPA District Office or local air agency.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

## IV. Reporting Requirements

- 1. The permittee shall submit deviation (excursion) reports that identify each day when a fuel other than natural gas was burned in this emissions unit. Each report shall be submitted within 30 days after the deviation occurs.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

- 2. The permittee shall submit notification of the following:

- 2.a date maximum capacity of this emissions unit was physically and permanently reduced (no later than 30 days after such date);
- 2.b the maximum heat input capacity of and identification of fuels to be combusted in this emissions unit (same due date as in A.IV.3.a above); and

#### IV. Reporting Requirements (continued)

- 2.c** actual start-up date under reduced maximum capacity (within 15 days after such date).

Notifications are to be sent to:

Ohio Environmental Protection Agency  
DAPC - Permit Management Unit  
P. O. Box 163669  
Columbus, Ohio 43216-3669

and

Ohio Environmental Protection Agency  
Northwest District Office  
Division of Air Pollution Control  
347 North Dunbridge Road  
Bowling Green, OH 43402

[Authority for term: OAC rule 3745-77-07(C)(1) and 40 CFR Part 60.48c(j)]

- 3.** The permittee shall submit a copy of the Burner Tuning Reporting Form for Boilers form to the appropriate Ohio EPA district office or local air agency to summarize the results of each burner tuning procedure. These reports shall be submitted to the Ohio EPA district office or local air agency by January 31 of each year and shall cover the previous calendar year.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

#### V. Testing Requirements

- 1.** Compliance with the emission limitations in section A.I. of the terms and conditions of this permit shall be determined in accordance with the following methods:

- 1.a** Emission Limitations:  
0.49 lb NO<sub>x</sub>/hr and 2.15 TPY

Applicable Compliance Method:

The hourly and annual emission limitations represent the potential to emit (PTE)\* of the emissions unit. Therefore, no monitoring and record keeping, reporting, or compliance method calculations are required to demonstrate compliance with these limitations. If required, the permittee shall demonstrate compliance with the hourly limitation in accordance with the test methods and procedures in Methods 1 through 4 and 7 of 40 CFR Part 60, Appendix A.

\*The PTE for this emissions unit is based on the maximum capacity of the boiler of 14.7 mm Btu/hr and the vendor supplied emission factor of 0.0241 lbs NO<sub>x</sub>/mm Btu. The annual PTE is based on the hourly PTE and a maximum operating schedule of 8,760 hrs/yr.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

## V. Testing Requirements (continued)

- 1.b** Emission Limitations:  
0.54 lb CO/hr and 2.4 TPY

**Applicable Compliance Method:**

The hourly and annual emission limitations represent the PTE\* of the emissions unit. Therefore, no monitoring and record keeping, reporting, or compliance method calculations are required to demonstrate compliance with these limitations. If required, the permittee shall demonstrate compliance with the hourly limitation in accordance with the test methods and procedures in Methods 1 through 4 and 10 of 40 CFR Part 60, Appendix A.

\*The PTE for this emissions unit is based on the maximum capacity of the boiler of 14.7 mm Btu/hr and the vendor supplied emission factor of 0.0367 lb CO/mm Btu. The annual PTE is based on the hourly PTE and a maximum operating schedule of 8,760 hrs/yr.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

- 1.c** Emission Limitations:  
0.11 lb PE/hr and 0.5 TPY

**Applicable Compliance Method:**

The hourly and annual emission limitations represent the PTE\* of the emissions unit. Therefore, no monitoring and record keeping, reporting, or compliance method calculations are required to demonstrate compliance with these limitations. If required, the permittee shall demonstrate compliance with the test methods and procedures in Methods 1 through 5 of 40 CFR Part 60, Appendix A.

\*The PTE for this emissions unit is based on the maximum capacity of the boiler (14.7 mm Btu/hr), the heat content of natural gas (1020 Btu/mmft<sup>3</sup>), and an emission factor of 7.6 lbs PE/1000 mmft<sup>3</sup> of natural gas burned (AP-42 Table 1.4-2, dated 9/98). The annual PTE is based on the hourly PTE and a maximum operating schedule of 8,760 hrs/yr.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

- 1.d** Emission Limitation:  
Visible PE shall not exceed 20% opacity, as a 6-minute average, except as provided by the rule.

**Applicable Compliance Method:** If required, the method to be employed to demonstrate compliance with the visible PE limitation shall be OAC rule 3745-17-03(B)(1).

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

- 2.** The permittee may conduct periodic tuning of the boiler burner. The purpose of this tuning is to ensure that the burner is adjusted properly so that air pollution emissions remain in compliance with allowable emission rates and are minimized.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

- 3.** Technicians who conduct the burner tuning must be qualified to perform the expected tasks. The permittee is required to provide training to the technicians who perform the burner tuning procedure. Technicians who are qualified shall, at a minimum, have passed manufacturer's training concerning burner tuning, or have been trained by someone who has completed the manufacturer's training concerning burner tuning.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

- 4.** The permittee shall properly operate and maintain portable device(s) to monitor the concentration of NO<sub>x</sub> in the stack exhaust gases from this emissions unit. The monitor(s) shall be capable of measuring the expected concentrations of the measured gases. The monitoring equipment shall be calibrated, operated and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall maintain records of each portable monitoring device's calibration.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

## V. Testing Requirements (continued)

5. The first steps concerning burner tuning involve setting the pollutant baseline levels (concentrations) utilizing the portable monitor. These baselines shall be set during the initial U.S. EPA approved emissions testing that demonstrated the emissions unit was in compliance with all applicable emissions limitations as described in E.1.a. The baselines shall be determined for NO<sub>x</sub>. Sampling should measure the exhaust gas values exiting the baghouse. The duration of each sample shall follow the portable monitor manufacturer's recommendations. Record these values on the Burner Tuning Reporting Form for Boilers form (as found in F.3) in the "Recent Stack Test Basis Values" column.

Once the pollutant baseline levels are set, the burner shall be next tuned based on the frequency described in E.2.e. The general procedure for tuning the burner involves the following steps:

- 5.a Review the plant operations to ensure the boiler is operating normally.
- 5.b Confirm that the portable monitor is calibrated per the manufacturer's specifications.
- 5.c Using the calibrated monitor and monitor manufacturer's recommended sampling duration, measure the stack exhaust gas values for NO<sub>x</sub>. These measurements shall be taken at the same location as the location where the baseline samples were taken. Record the values in the "Pre Tuning" results column on the Burner Tuning Reporting Form for Boilers form.
- 5.d Compare the measured stack exhaust gas values with the pollutant baseline values. If all of the measured stack exhaust gas values are equal to or less than 115 percent of the pollutant baseline values, then it is not necessary to tune the burner. Go on to section v. below. The permittee shall have the burners tuned within two calendar weeks of any measured stack exhaust values greater than 115 percent of the baseline values. Make any necessary adjustments and repairs. Repeat sections iii. and iv. until the measured stack exhaust gas values are equal to or less than 115 percent of the pollutant baseline values.
- 5.e Once all of the measured stack exhaust gas values are within the 115 percent of the pollutant baseline values, record the measured stack exhaust gas values in the "Post Tuning" results column on the Burner Tuning Reporting Form for Boilers form.
- 5.f By January 31st of each year, submit a copy of all Burner Tuning Reporting Form for Boilers forms produced during the past calendar year to the Ohio EPA District Office or local air agency responsible for the permitting of the facility.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

6. The permittee shall conduct the burner tuning procedure at a frequency to be determined and approved by the Ohio EPA Northwest District Office.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

7. The firing rate of the boiler shall be at least 7.0 mmBtu/hr and such to maintain a steady-state water temperature of 179 degrees F at the cleaner section of the continuous galvanizing line when stack testing or burner tuning is being conducted.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

## VI. Miscellaneous Requirements

None

**B. State Enforceable Section**

**I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
14.7 mm Btu/hr, natural gas-fired boiler, with low NOx burners	none	none

**2. Additional Terms and Conditions**

None

**II. Operational Restrictions**

None

**III. Monitoring and/or Record Keeping Requirements**

None

**IV. Reporting Requirements**

None

**V. Testing Requirements**

None

**VI. Miscellaneous Requirements**

None

### Part III - Terms and Conditions for Emissions Units

**Emissions Unit ID:** B4-CGL2 (B044)

**Activity Description:** Hot Water Boiler #4 (14.7 MMBTU/hr)

#### A. State and Federally Enforceable Section

##### I. Applicable Emissions Limitations and/or Control Requirements

- The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
14.7 mm Btu/hr, natural gas-fired boiler, with low NOx burners	OAC rule 3745-31-05(A)(3) (PTI #03-14070, issued November 8, 2007 corrected copy issued January 24, 2008)	0.49 lb nitrogen oxide (NOx)/hr; 2.15 tons NOx/yr
		0.54 lb carbon monoxide (CO)/hr; 2.4 tons CO/yr
		0.11 lb particulate emissions (PE)/hr; 0.5 ton PE/yr
		control requirements (See A.I.2.a.)
		See A.I.2.b.
		recordkeeping requirements (See A.III.2.)
	OAC rule 3745-17-07(A)(1)	Visible PE shall not exceed 20% opacity as a 6-minute average, except as provided by rule.
	OAC rule 3745-18-06	Exempt (See A.I.2.c.)
	OAC rule 3745-17-10(B)(1)	See A.I.2.d.
	OAC rule 3745-21-08(B)	See A.I.2.e.

##### 2. Additional Terms and Conditions

- Best available technology (BAT) control requirements for this emissions unit has been determined to be use of low NOx burners. BAT also includes compliance with the terms and conditions of this permit.

Pro Tec Company agreed and consented to entry into a Consent Decree with the United States of America (Civil Action No. 3:98CV 7749, entered 2/11/98) requiring the permittee to install natural gas fired low NOx burners on this emissions unit. The consent decree also required this emissions unit to achieve an emission rate not to exceed 0.033 lbs NOx/mmBtu, which is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05 (A)(3).

- The requirements of this rule also include compliance with the requirements of OAC rule 3745-17-07(A)(1) and 40 CFR, Part 60, Subpart Dc.

## 2. Additional Terms and Conditions (continued)

- 2.c This emissions unit is exempt from the requirements of OAC rule 3745-18-06 pursuant to OAC rule 3745-18-06(A).
- 2.d The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
- 2.e The permittee has satisfied the "best available control techniques and operating practices" required pursuant to OAC rule 3745-21-08(B) by committing to comply with the best available technology requirements established pursuant to OAC rule 3745-31-05 (A)(3) in Permit to Install 03-14070.

On November 5, 2002, OAC rule 3745-21-08 was revised to delete paragraph (B); therefore, paragraph (B) is no longer part of the State regulations. However, that rule revision has not yet been submitted to the U.S. EPA as a revision to Ohio's State Implementation Plan (SIP). Therefore, until the SIP revision occurs and the U.S. EPA approves the revisions to OAC rule 3745-21-08, the requirement to satisfy the "best available control techniques and operating practices" still exists as part of the federally-approved SIP for Ohio.

## II. Operational Restrictions

- 1. The permittee shall burn only natural gas in this emissions unit.

[Authority for term: OAC rule 3745-77-07(A)(1) and PTI 03-14070]

## III. Monitoring and/or Record Keeping Requirements

- 1. For each day during which the permittee burns a fuel other than natural gas, the permittee shall maintain a record of the type and quantity of fuel burned in this emissions unit.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

- 2. The permittee shall record and maintain records of the amounts of each fuel combusted during each day.

[Authority for term: OAC rule 3745-77-07(C)(1), 40 CFR 60.48c(g) and PTI 03-14070]

- 3. While performing each burner tuning, the permittee shall record the results of the burner tuning using the Burner Tuning Reporting Form for Boilers form (as found in term VI.3). An alternative form may be used upon approval of the appropriate Ohio EPA District Office or local air agency.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

## IV. Reporting Requirements

- 1. The permittee shall submit deviation (excursion) reports that identify each day when a fuel other than natural gas was burned in this emissions unit. Each report shall be submitted within 30 days after the deviation occurs.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

- 2. The permittee shall submit notification of the following:

- 2.a date maximum capacity of this emissions unit was physically and permanently reduced (no later than 30 days after such date);
- 2.b the maximum heat input capacity of and identification of fuels to be combusted in this emissions unit (same due date as in A.IV.3.a above); and

#### IV. Reporting Requirements (continued)

- 2.c** actual start-up date under reduced maximum capacity (within 15 days after such date).

Notifications are to be sent to:

Ohio Environmental Protection Agency  
DAPC - Permit Management Unit  
P. O. Box 163669  
Columbus, Ohio 43216-3669

and

Ohio Environmental Protection Agency  
Northwest District Office  
Division of Air Pollution Control  
347 North Dunbridge Road  
Bowling Green, OH 43402

[Authority for term: OAC rule 3745-77-07(C)(1) and 40 CFR Part 60.48c(j)]

- 3.** The permittee shall submit a copy of the Burner Tuning Reporting Form for Boilers form to the appropriate Ohio EPA district office or local air agency to summarize the results of each burner tuning procedure. These reports shall be submitted to the Ohio EPA district office or local air agency by January 31 of each year and shall cover the previous calendar year.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

#### V. Testing Requirements

- 1.** Compliance with the emission limitations in section A.I. of the terms and conditions of this permit shall be determined in accordance with the following methods:

- 1.a** Emission Limitations:  
0.49 lb NOx/hr and 2.15 TPY

Applicable Compliance Method:

The hourly and annual emission limitations represent the potential to emit (PTE)\* of the emissions unit. Therefore, no monitoring and record keeping, reporting, or compliance method calculations are required to demonstrate compliance with these limitations. If required, the permittee shall demonstrate compliance with the hourly limitation in accordance with the test methods and procedures in Methods 1 through 4 and 7 of 40 CFR Part 60, Appendix A.

\*The PTE for this emissions unit is based on the maximum capacity of the boiler of 14.7 mm Btu/hr and the vendor supplied emission factor of 0.0241 lbs NOx/mm Btu. The annual PTE is based on the hourly PTE and a maximum operating schedule of 8,760 hrs/yr.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

## V. Testing Requirements (continued)

- 1.b** Emission Limitations:  
0.54 lb CO/hr and 2.4 TPY

**Applicable Compliance Method:**

The hourly and annual emission limitations represent the PTE\* of the emissions unit. Therefore, no monitoring and record keeping, reporting, or compliance method calculations are required to demonstrate compliance with these limitations. If required, the permittee shall demonstrate compliance with the hourly limitation in accordance with the test methods and procedures in Methods 1 through 4 and 10 of 40 CFR Part 60, Appendix A.

\*The PTE for this emissions unit is based on the maximum capacity of the boiler of 14.7 mm Btu/hr and the vendor supplied emission factor of 0.0367 lb CO/mm Btu. The annual PTE is based on the hourly PTE and a maximum operating schedule of 8,760 hrs/yr.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

- 1.c** Emission Limitations:  
0.11 lb PE/hr and 0.5 TPY

**Applicable Compliance Method:**

The hourly and annual emission limitations represent the PTE\* of the emissions unit. Therefore, no monitoring and record keeping, reporting, or compliance method calculations are required to demonstrate compliance with these limitations. If required, the permittee shall demonstrate compliance with the test methods and procedures in Methods 1 through 5 of 40 CFR Part 60, Appendix A.

\*The PTE for this emissions unit is based on the maximum capacity of the boiler (14.7 mm Btu/hr), the heat content of natural gas (1020 Btu/mmft<sup>3</sup>), and an emission factor of 7.6 lbs PE/1000 mmft<sup>3</sup> of natural gas burned (AP-42 Table 1.4-2, dated 9/98). The annual PTE is based on the hourly PTE and a maximum operating schedule of 8,760 hrs/yr.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

- 1.d** Emission Limitation:  
Visible PE shall not exceed 20% opacity, as a 6-minute average, except as provided by the rule.

**Applicable Compliance Method:** If required, the method to be employed to demonstrate compliance with the visible PE limitation shall be OAC rule 3745-17-03(B)(1).

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

- 2.** The permittee may conduct periodic tuning of the boiler burner. The purpose of this tuning is to ensure that the burner is adjusted properly so that air pollution emissions remain in compliance with allowable emission rates and are minimized.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

- 3.** Technicians who conduct the burner tuning must be qualified to perform the expected tasks. The permittee is required to provide training to the technicians who perform the burner tuning procedure. Technicians who are qualified shall, at a minimum, have passed manufacturer's training concerning burner tuning, or have been trained by someone who has completed the manufacturer's training concerning burner tuning.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

- 4.** The permittee shall properly operate and maintain portable device(s) to monitor the concentration of NO<sub>x</sub> in the stack exhaust gases from this emissions unit. The monitor(s) shall be capable of measuring the expected concentrations of the measured gases. The monitoring equipment shall be calibrated, operated and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall maintain records of each portable monitoring device's calibration.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

## V. Testing Requirements (continued)

5. The first steps concerning burner tuning involve setting the pollutant baseline levels (concentrations) utilizing the portable monitor. These baselines shall be set during the initial U.S. EPA approved emissions testing that demonstrated the emissions unit was in compliance with all applicable emissions limitations as described in E.1.a. The baselines shall be determined for NO<sub>x</sub>. Sampling should measure the exhaust gas values exiting the baghouse. The duration of each sample shall follow the portable monitor manufacturer's recommendations. Record these values on the Burner Tuning Reporting Form for Boilers form (as found in F.3) in the "Recent Stack Test Basis Values" column.

Once the pollutant baseline levels are set, the burner shall be next tuned based on the frequency described in E.2.e. The general procedure for tuning the burner involves the following steps:

- 5.a Review the plant operations to ensure the boiler is operating normally.
- 5.b Confirm that the portable monitor is calibrated per the manufacturer's specifications.
- 5.c Using the calibrated monitor and monitor manufacturer's recommended sampling duration, measure the stack exhaust gas values for NO<sub>x</sub>. These measurements shall be taken at the same location as the location where the baseline samples were taken. Record the values in the "Pre Tuning" results column on the Burner Tuning Reporting Form for Boilers form.
- 5.d Compare the measured stack exhaust gas values with the pollutant baseline values. If all of the measured stack exhaust gas values are equal to or less than 115 percent of the pollutant baseline values, then it is not necessary to tune the burner. Go on to section v. below. The permittee shall have the burners tuned within two calendar weeks of any measured stack exhaust values greater than 115 percent of the baseline values. Make any necessary adjustments and repairs. Repeat sections iii. and iv. until the measured stack exhaust gas values are equal to or less than 115 percent of the pollutant baseline values.
- 5.e Once all of the measured stack exhaust gas values are within the 115 percent of the pollutant baseline values, record the measured stack exhaust gas values in the "Post Tuning" results column on the Burner Tuning Reporting Form for Boilers form.
- 5.f By January 31st of each year, submit a copy of all Burner Tuning Reporting Form for Boilers forms produced during the past calendar year to the Ohio EPA District Office or local air agency responsible for the permitting of the facility.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

6. The permittee shall conduct the burner tuning procedure at a frequency to be determined and approved by the Ohio EPA Northwest District Office.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

7. The firing rate of the boiler shall be at least 7.0 mmBtu/hr and such to maintain a steady-state water temperature of 179 degrees F at the cleaner section of the continuous galvanizing line when stack testing or burner tuning is being conducted.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-14070]

## VI. Miscellaneous Requirements

None

**B. State Enforceable Section**

**I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
14.7 mm Btu/hr, natural gas-fired boiler, with low NOx burners	none	none

**2. Additional Terms and Conditions**

None

**II. Operational Restrictions**

None

**III. Monitoring and/or Record Keeping Requirements**

None

**IV. Reporting Requirements**

None

**V. Testing Requirements**

None

**VI. Miscellaneous Requirements**

None

### Part III - Terms and Conditions for Emissions Units

**Emissions Unit ID:** RC-CGL (K001)

**Activity Description:** Dry Film Lube Horizontal Roll Coater with infrared oven

#### A. State and Federally Enforceable Section

##### I. Applicable Emissions Limitations and/or Control Requirements

- The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
dry film lube horizontal roll coater, with infrared oven	OAC rule 3745-17-07(A)	See A.I.2.a.
	OAC rule 3745-17-11(B)(2)	See A.I.2.b.
	OAC rule 3745-21-09(E)	2.6 pounds of volatile organic compounds (VOC) per gallon of coating, excluding water and exempt solvent
	OAC rule 3745-31-05(A)(3) (PTI #03-9977, issued February 26, 1997)	42 lbs VOC/hr and 24.44 tons VOC/yr
		See A.I.2.c.
		0.10 lb particulate emissions (PE)/hr and 0.44 ton PE/year
		The requirements of this rule also include compliance with the requirements of OAC rule 3745-21-09(E) and 40 CFR, Part 60, Subpart TT.
	40 CFR, Part 60, Subpart TT	0.28 kilogram VOC per liter of coating solids applied (based on a monthly, volume-weighted average)

##### 2. Additional Terms and Conditions

- The emission unit is exempt from the visible PE limitations specified in OAC rule 3745-17-07(A), pursuant to OAC rule 3745-17-07(A)(3)(h), because the emissions unit is not subject to the requirements of OAC rule 3745-17-11.
- The uncontrolled mass rate of particulate emissions from this emissions unit is less than 10 pounds/hour. Therefore, pursuant to OAC rule 3745-17-11(A)(2)(a)(ii), Figure II of OAC rule 3745-17-11 does not apply. In addition, Table I of OAC rule 3745-17-11 does not apply since the facility is located in Putnam County, which is identified as a P-2 county.

**2. Additional Terms and Conditions (continued)**

- 2.c** The 42 lbs VOC/hr emission limitation was established for PTI purposes to reflect the potential to emit for this emissions unit. Therefore, it is not necessary to develop record keeping and/or reporting requirements to ensure compliance with this limitation.

**II. Operational Restrictions**

- 1.** The permittee shall not employ any cleanup material in this emissions unit that is a liquid organic material. The emissions unit shall employ only water and alkaline cleaner, or a cleaning agent that does not result in the emissions of organic compounds. "Liquid organic material" is defined in OAC rule 3745-21-01(C)(3).

[Authority for term: OAC rule 3745-77-07(A)(1) and PTI 03-9977]

**III. Monitoring and/or Record Keeping Requirements**

- 1.** Each month, the permittee shall determine the monthly, volume-weighted average of the total mass of VOCs emitted to the atmosphere per volume of applied coating solids, in kilogram per liter, as follows, and record the results:

- 1.a** Calculate the mass of VOCs consumed (Mo+Md) during the calendar month by the following equation:

$$Mo+Md = [\text{summation of } (L_{ci} \times D_{ci} \times W_{oi}) \text{ for } i = 1, 2, \dots, n + \text{summation of } (L_{dj} \times D_{dj})^* \text{ for } j = 1, 2, \dots, m]$$

where:

Mo = the total VOC emissions, in kilograms, from all the coatings consumed, as received

Md = the total VOC emissions, in kilograms, from all the solvents added to the coatings

Lci = the total volume, in liters, of coating i consumed, as received

Ldj = the total volume, in liters, of solvent j added to coatings

Dci = density of coating i, as received (kilograms per liter)

Ddj = density of solvent j added to coatings (kilograms per liter)

Woi = the fraction, by weight, of the VOCs in coating i, as received

n = the number of different coatings used during the calendar month

m = the number of different solvents added to coatings during the calendar month

\* the summation of (Ldj x Ddj) for j = 1, 2,...,m will be zero if no VOC-based solvent is added to the coatings, as received)

- 1.b** Calculate the total volume of coatings solids used (Ls) in the calendar month by the following equation:

$$Ls = \text{summation of } (L_{ci} \times V_{si}) \text{ for } i = 1, 2, \dots, n$$

where:

Ls = the volume of all the coatings solids consumed (liters)

Lci = the volume of coating i consumed, as received (liters)

Vsi = the fraction, by volume, of the solids in coating i, as received

n = the number of different coatings used during the calendar month

### III. Monitoring and/or Record Keeping Requirements (continued)

- 1.c Calculate the volume-weighted average mass of VOCs consumed per unit volume of coating solids applied during the calendar month by the following equation:

$$G = (M_o + M_d) / (L_s)$$

where:

G = the volume-weighted average mass of VOCs in coatings consumed in a calendar month per unit volume of applied coating solids (kilograms per liter)

[Authority for term: OAC rule 3745-77-07(C)(1), 40 CFR Part 60.463(c) and PTI 03-9977]

2. If each individual coating used by the emissions unit has a VOC content, as received, that is equal to or less than 0.28 kg/liter of coating solids, no monthly, volume-weighted average calculations are necessary to show compliance with the 0.28 kg/liter of coating solids.

[Authority for term: OAC rule 3745-77-07(C)(1), 40 CFR Part 60.463(c) and PTI 03-9977]

3. The permittee shall collect and record the following information each month for the line:

- a. The name and identification number of each coating and cleanup material employed.
- b. Documentation on whether or not each cleanup material employed is a liquid organic material.
- c. The VOC content of each coating employed, in lbs/gallon and in lbs/gallon excluding water and exempt solvents, as applied.
- d. The number of gallons of each coating employed.
- e. The total VOC emissions for all the coatings employed [summation of (c x d) for all coatings], in pounds.

[Authority for term: OAC rule 3745-77-07(C)(1), OAC rule 3745-21-09(B)(3)(f) and PTI 03-9977]

4. The permittee shall collect and record each year the total VOC emissions, in tons, for all the coatings employed (this is determined by adding all the monthly VOC emissions (from section 3.e) for the calendar year and dividing by 2000 lbs/ton).

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-9977]

### IV. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the VOC content limitation of 0.28 kg VOC/liter of coating solids (based on a monthly, volume-weighted average). All quarterly reports shall be submitted in accordance with paragraph A.1.c of the General Terms and Conditions of this permit.

[Authority for term: OAC rule 3745-77-07(C)(1), 40 CFR Part 60.465(c) and PTI 03-9977]

2. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any monthly record showing the use of noncomplying coatings (i.e., for VOC content). The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days following the end of the calendar month.

[Authority for term: OAC rule 3745-77-07(C)(1), OAC rule 3745-21-09(B)(3)(g) and PTI 03-9977]

#### IV. Reporting Requirements (continued)

3. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any monthly record showing the use of noncomplying cleanup materials (i.e., liquid organic cleanup materials). The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days following the end of the calendar month.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-9977]

4. The permittee shall submit annual reports that specify the total VOC emissions from this emissions unit for the previous calendar year. These reports shall be submitted by January 31 of each year.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-9977]

#### V. Testing Requirements

1. Compliance with the emission limitations in section A.I. of the terms and conditions of this permit shall be determined in accordance with the following methods:

- 1.a Emission Limitation:  
2.6 lbs of VOC per gallon of coating, excluding water and exempt solvents

Applicable Compliance Method:

The permittee shall demonstrate compliance with the limitation above through the monitoring and record keeping requirements required in section A.III.3 of this permit.

[Authority for term: OAC rule 3745-77-07(C)(1), OAC rule 3745-21-09(E) and PTI 03-9977]

- 1.b Emission Limitation:  
0.28 kilogram VOC per liter of coating solids applied (based on a monthly, volume-weighted average)

Applicable Compliance Method:

The permittee shall demonstrate compliance with the limitation above through the monitoring and record keeping requirements required in section A.III.1 of this permit.

[Authority for term: OAC rule 3745-77-07(C)(1), 40 CFR Part 60.462, and PTI 03-9977]

- 1.c Emission Limitation:  
42.0 lbs VOC/hr

Applicable Compliance Method:

The permittee may determine compliance with the hourly emission limitation above by multiplying the maximum coating usage rate (gallons/hr) by the maximum VOC content of all the coatings employed (lbs/gallon).

If required, the permittee shall demonstrate compliance with the above emission limit pursuant to Method 25 of 40 CFR, Part 60, Appendix A.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-9977]

- 1.d Emission Limitation:  
24.44 tons VOC/yr

Applicable Compliance Method:

The permittee shall demonstrate compliance with the emission limitation above through the monitoring and record keeping requirements required in sections A.III.2 and 3. of this permit.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-9977]

## V. Testing Requirements (continued)

- 1.e** Emission Limitations:  
0.10 lb PE/hr  
0.44 ton PE/year

Applicable Compliance Method:

To determine the actual worst case PE rate (E), the following equation may be used for the paint spraying operation:

$E = \text{particulates emission rate (lbs/hr)}$

$E = \text{maximum coating solids usage rate, in pounds per hour} \times (1-TE) \times (1-CE)$

TE = transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used

CE = control efficiency of the control equipment

If required, the permittee shall demonstrate compliance with the hourly emission limit pursuant to Methods 1-5 of 40 CFR Part 60, Appendix A.

Compliance with the annual emission limitation shall be assumed as long as compliance with the hourly emission limitation is maintained (the annual emission limitation was calculated by multiplying the hourly emission limitation by 8760 and dividing by 2000).

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-9977]

- 2.** Formulation data or USEPA Method 24 shall be used to determine the VOC contents of all the coatings employed.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-9977]

## VI. Miscellaneous Requirements

**None**

**B. State Enforceable Section**

**I. Applicable Emissions Limitations and/or Control Requirements**

- The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
dry film lube horizontal roll coater with infrared oven	none	none

**2. Additional Terms and Conditions**

None

**II. Operational Restrictions**

None

**III. Monitoring and/or Record Keeping Requirements**

- The permit to install for this emissions unit K001 was evaluated based on the actual materials (coatings) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Ethyl Alcohol

TLV (mg/m3): 1,880

Maximum Hourly Emission Rate (lbs/hr): 34.5

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 407.1

MAGLC (ug/m3): 44,761.90

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-9977]

### III. Monitoring and/or Record Keeping Requirements (continued)

2. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:
  - a. changes in the composition of the materials used (coatings), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
  - b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
  - c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-9977]

3. If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-9977]

### IV. Reporting Requirements

None

### V. Testing Requirements

None

### VI. Miscellaneous Requirements

None

**Part III - Terms and Conditions for Emissions Units**

**Emissions Unit ID:** AF-CGL (P001)

**Activity Description:** 80 MMBtu/hr Continuous Annealing Furnace with 16 MMBtu/hr aux. heat input (96 MMBtu/hr total)

**A. State and Federally Enforceable Section**

**I. Applicable Emissions Limitations and/or Control Requirements**

- The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
96.0 mmBtu/hr, natural gas-fired continuous annealing furnace, with 16 mmBtu/hr auxiliary natural gas-fired burners [the burners are used to maintain the selective catalytic reduction (SCR) control device operating temperature within the recommended range]	OAC rule 3745-17-07(A)	See A.I.2.a.
	OAC rule 3745-17-11(B)(2)	See A.I.2.b.
	OAC rule 3745-31-05(A)(3) (PTI #03-16048, issued June 17, 2004)	0.10 lb nitrogen oxides (NOx)/mmBtu (See A.I.2.c. and d.)  9.6 lbs NOx/hr (See A.I.2.c. and d.)  42.05 tons NOx/yr  12.4 lbs carbon monoxide (CO)/hr and 54.31 tons CO/yr  1.04 lbs organic compounds (OC)/hr and 4.56 tons OC/yr  0.72 lb particulate emissions (PE)/hr and 3.15 tons PE/yr (See A.I.2.e.)
	Federal Consent Decree  40 CFR, Part 64 - Compliance Assurance Monitoring (CAM)	See A.I.2.f.  See A.II.2. and A.II.3., A.III.2. through A.III.4., A.III.6., A.III.9., A.IV.2. and A.IV.3.

## 2. Additional Terms and Conditions

- 2.a** This emissions unit is exempt from the visible emissions limitations specified in OAC rule 3745-17-07(A), pursuant to OAC rule 3745-17-07(A)(3)(h), because the emissions unit is not subject to the requirements of OAC rule 3745-17-11.
- 2.b** The uncontrolled mass rate of PE from this emissions unit is less than 10 pounds/hour. Therefore, pursuant to OAC rule 3745-17-11(A)(2)(a)(ii), Figure II of OAC rule 3745-17-11 does not apply. In addition, Table I of OAC rule 3745-17-11 does not apply because the facility is located in Putnam County, which is identified as a P-2 county.
- 2.c** The permittee shall employ North American regenerative-type burners with flue gas recirculation and a NOx OUT SCR system with Hauck direct-fired burners to maintain the recommended gas temperatures for NOx emissions reduction. The NOx emissions shall be limited to 0.10 lb NOx/mmBtu, based on a 3-hour rolling average, when this emissions unit is in operation. For this requirement, "in operation" shall mean that the main burners are firing and the product is moving through the continuous annealing furnace. "In operation" shall not include low fuel flow/low temperature furnace conditions, such as idle and furnace temperature ramp-up and ramp-down. During times that the furnace is not "in operation" and the main burners are idling or only the pilot burners are operating, NOx emissions shall not exceed 9.6\* lbs/hr.
- \* The 9.6 pounds NOx per hour limitation shall be based on a 3-hour rolling average.
- 2.d** The NOx analyzers associated with this emissions unit are used as part of the process control system for the SCR unit. The data from the analyzers is used to adjust the urea injection flow rate to optimize the performance of the SCR unit. These analyzers were not installed with the intent of satisfying the requirements specified in 40 CFR Part 60, Appendix B, Performance Specification 2, and they can not be certified as true continuous NOx monitoring systems. Even though the analyzers can not be certified as true continuous NOx monitoring systems, they have demonstrated that they provide accurate NOx emission concentration data as compared to emission concentration data simultaneously obtained through 40 CFR Part 60, Appendix A, Method 7E. As such, the data from the analyzers will be used to ensure ongoing compliance with the NOx emission limitations.
- 2.e** All PE is assumed to be PM10.
- 2.f** The facility agreed and consented to entry into a Consent Decree with the United States of America (Civil Action No. 3:98CV 7749, entered 2/11/98) requiring the permittee to install an SCR unit to continuously control NOx emissions to an emission rate not to exceed 0.10 lbs NOx/mm btu.

## II. Operational Restrictions

- 1.** The permittee shall burn only natural gas in this emissions unit.  
[Authority for term: OAC rule 3745-77-07(A)(1) and PTI 03-16048]
- 2.** The permittee shall continuously monitor and record NOx emissions at the discharge of each SCR unit, when the emissions unit is in operation, and shall continuously maintain NOx emissions within all the applicable limitations contained within this permit.  
[Authority for term: OAC rule 3745-77-07(A)(1), 40 CFR Part 64.3(a) and PTI 03-16048]
- 3.** The average temperature of the exhaust gases immediately before the catalyst bed, for any 3-hour block of time when the emissions unit is in operation, shall not be more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance.  
[Authority for term: OAC rule 3745-77-07(A)(1), 40 CFR Part 64.3(a) and PTI 03-16048]
- 4.** The maximum heat input (including the lance pilot) shall not exceed 96.0 mmBtu per hour.  
[Authority for term: OAC rule 3745-77-07(A)(1) and PTI 03-16048]

### III. Monitoring and/or Record Keeping Requirements

1. For each day during which the permittee burns a fuel other than natural gas, the permittee shall maintain a record of the type and quantity of fuel burned in this emissions unit.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-16048]

2. The urea/gas ratio shall be determined and adjusted on a continuous basis by a primary control circuit based on natural gas flow rate, which shall determine the appropriate urea flow rate to the SCR unit. Additionally, a secondary control circuit shall be utilized consisting of a NO<sub>x</sub> analyzer which shall increase or decrease the urea flow rate according to NO<sub>x</sub> concentrations observed at the discharge of each SCR unit. The purpose of the secondary control circuit is to optimize the efficiency of each SCR control system and minimize ammonia slip to the atmosphere.

[Authority for term: OAC rule 3745-77-07(C)(1), 40 CFR Part 64.3(a) and PTI 03-16048]

3. The permittee shall operate and maintain equipment necessary to continuously monitor the following parameters for the SCR NO<sub>x</sub> control unit while this emissions unit is in operation. The monitoring and recording devices shall be capable of accurately measuring the desired parameters. The monitoring and recording devices shall be calibrated, operated and maintained in accordance with the manufacturer's recommendations, with any modifications deemed necessary by the permittee:

- a. the urea flow rate, in gallons per hour;
- b. the natural gas flow rate, in standard cubic feet per hour;
- c. the SCR inlet temperature, in degrees Fahrenheit;
- d. the number of hours the SCR unit was in operation; and
- e. the number of hours this emissions unit was in operation.

[Authority for term: OAC rule 3745-77-07(C)(1), 40 CFR Part 64.3(a), 40 CFR Part 64.7(b), 40 CFR Part 67.9(b) and PTI 03-16048]

4. Whenever the monitored values for the urea flow rate and SCR inlet temperature deviate from the range specified below, the permittee shall promptly investigate the cause of the deviation. The permittee shall maintain records of the following information for each investigation: the date and time the deviation began and the magnitude of the deviation at that time, the date(s) the investigation was conducted, the names of the personnel who conducted the investigation, and the findings and recommendations.

In response to each required investigation to determine the cause of a deviation, the permittee shall take prompt corrective action to bring the operation of the control equipment within the acceptable ranges specified below, unless the permittee determines that corrective action is not necessary and documents the reasons for that determination and the date and time the deviation ended. The permittee shall maintain records of the following information for each corrective action taken: a description of the corrective action, the date it was completed, the date and time the deviation ended, the total period of time (in minutes) during which there was a deviation, the pressure drop and scrubber water flow rate immediately after the corrective action, and the names of the personnel who performed the work. Investigation and records required by this paragraph does not eliminate the need to comply with the requirements of OAC rule 3745-15-06 if it is determined that a malfunction has occurred.

- 4.a The urea flow rate shall be continuously maintained within the range of 1.5-14 gallons per hour at all times while the emissions unit is in operation, or as established during the most recent performance test that demonstrated the emissions unit was in compliance.

### III. Monitoring and/or Record Keeping Requirements (continued)

- 4.b** The SCR inlet temperature shall be continuously maintained, at all times while the emissions unit is in operation, at a value of not less than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated that the emissions unit was in compliance.

These ranges are effective for the duration of this permit, unless revisions are requested by the permittee and approved in writing by the appropriate Ohio EPA District Office or local air agency. The permittee may request revisions to the ranges based upon information obtained during future NOx emission tests that demonstrate compliance with the allowable NOx emission rate for this emissions unit. In addition, approved revisions to the ranges will not constitute a relaxation of the monitoring requirements of this permit and may be incorporated into this permit by means of a minor modification.

[Authority for term: OAC rule 3745-77-07(C)(1), 40 CFR 64.7(b), 40 CFR Part 64.3(a), 40 CFR 64.9(b) and PTI 03-16048]

- 5.** The permittee shall collect and record the following information each month for this emissions unit:
- a. the total urea usage, in gallons;
  - b. the total natural gas usage, in standard cubic feet;
  - c. the daily urea to natural gas flow ratio (3.a/3.b), in gallons of urea per each standard cubic feet of natural gas;
  - d. the monthly average Btu content of fuel (Btu per standard cubic foot) as specified by the natural gas supplier;
  - e. the heat input rate (b x d), in mmBtu;
  - f. the number of hours and specific hours the emissions unit was "in operation;"
  - g. the number of hours and specific hours the emissions unit was not "in operation;"
  - h. the average hourly heat input rate for this emissions unit (e/f), in mmBtu/hr;
  - i. the number of hours the SCR system associated with this emissions unit was in operation;
  - j. the total number of 3-hour average periods during which the temperature was monitored at the inlet of the SCR unit;
  - k. all 3-hour blocks of time during which the average temperature of the flue gases at the inlet to the SCR unit, when the emissions unit was in operation, was more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance;
  - l. all 3-hour periods during which the NOx emission rate was monitored at the outlet of the SCR unit;
  - m. all 3-hour periods during which the average NOx emission rate was greater than 9.2 pounds NOx per hour; and
  - n. all 3-hour periods during which the average NOx emission rate was greater that 0.10 pound NOx per mmBtu.

[Authority for term: OAC rule 3745-77-07(C)(1), 40 CFR Part 64.3(a), 40 CFR Part 64.9(b)and PTI 03-16048]

### III. Monitoring and/or Record Keeping Requirements (continued)

6. The permittee shall maintain daily records of the following information for this emissions unit:

- a. the total number of hours the emissions unit was in operation;
- b. the total natural gas fuel usage, in mmcu ft.; and
- c. the firing rate, in mmBtu/hr, using the following equation:

firing rate (mmBtu/hr) = [total daily natural gas usage (mmcu ft./day) x (the Btu value from Section A.III.3.d)] / the total number of hours the emissions unit was in operation (from Section 4.c above).

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-16048]

7. The permittee shall operate and maintain the existing equipment to continuously monitor and record NOx emissions from this emissions unit in units of the applicable standard. The NOx analyzers and recording devices shall be calibrated, operated and maintained in accordance with the manufacturer's recommendations and the procedures specified in the permittee's ISO 14001 document titled "Work Instructions for Monitoring, Calibration and Maintenance of O2 and NOx Analyzers."

The permittee shall maintain records of all data obtained by the continuous NOx analyzers including, but not limited to, parts per million NOx on an instantaneous (one-minute) basis, emissions of NOx in units of the applicable standard in the appropriate averaging period (i.e., pounds/hour and pounds/mmBtu for each rolling, 3-hour period), results of daily zero/span calibration checks, and magnitude of manual calibration adjustments.

[Authority for term: OAC rule 3745-77-07(C)(1), 40 CFR Part 64.7(c), 40 CFR Part 64.9(b) and PTI 03-16048]

8. At all times, the permittee shall maintain the monitoring, including but not limited to, maintaining necessary parts for routine repairs of the monitoring equipment.

[Authority for term: OAC rule 3745-77-07(C)(1) and 40 CFR Part 64.7(b)]

9. After approval of monitoring under this part, if the permittee identifies a failure to achieve compliance with an emission limitation or standard for which the approved monitoring did not provide an indication of an excursion or exceedance while providing valid data, or the results of compliance or performance testing document a need to modify the existing indicator ranges or designated conditions, the permittee shall promptly notify the permitting authority and, if necessary, submit a proposed modification to the part 70 or 71 permit to address the necessary monitoring changes. Such a modification may include, but is not limited to, reestablishing indicator ranges or designated conditions, modifying the frequency of conducting monitoring and collecting data, or the monitoring of additional parameters.

[Authority for term: OAC rule 3745-77-07(C)(1) and 40 CFR 64.7(e)]

### III. Monitoring and/or Record Keeping Requirements (continued)

10. The CAM plan for this emissions unit has been developed for NO<sub>x</sub> emissions. The CAM performance indicators for the selective catalytic reduction (SCR) controlling this emissions unit are urea injection flowrate, inlet gas temperature at the SCR, NO<sub>x</sub> ppm measurement and O<sub>2</sub>% measurement post SCR which is based upon the result of site-specific NO<sub>x</sub> emission testing and manufacturer recommendations. When the performance indicators are operating outside the indicator ranges, the permittee shall take corrective action to restore operation of the emissions unit and/or its control equipment to its normal or usual manner of operation as expeditiously as practicable in accordance with good air pollution control practices for minimizing emissions and comply with the reporting requirements specified in Section A.IV.3 below. The emissions unit and control equipment shall be run in accordance with the approved CAM Plan, or any approved revision of the Plan.

SCR operating parameters will be re-verified through periodic emission testing, or if the SCR or emissions units operating conditions change. In addition to periodic monitoring of the SCR operating parameters, the permittee also has an inspection/preventative maintenance program for the SCR. Based on the results of the inspection/preventative maintenance program, repairs to the SCR shall be made as needed. If the current CAM indicators and/or the SCR inspection/preventative maintenance program is considered inadequate, the permittee will develop a Quality Improvement Plan.

[Authority for term: OAC rule 3745-77-07(A)(3)(a), OAC rule 3745-77-07(A)(3)(b), 40 CFR Part 64.3(a), 40 CFR Part 64.6(c), 40 CFR Part 64.7(d) and 40 CFR Part 64.8]

### IV. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports that identify each day when a fuel other than natural gas was burned in this emissions unit. Each report shall be submitted within 30 days after the deviation occurs.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-16048]

2. The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the following
- the 3-hour average NO<sub>x</sub> emission limitation of 9.6 lbs/hr;
  - the 3-hour average NO<sub>x</sub> emission limitation of 0.1 lb/mmBtu;
  - the urea flow rate range, in gallons per hour;
  - the 3-hour average SCR inlet temperature required by section A.II.3;\* and
  - the maximum heat input rate of 96.0 mmBtu per hour.

All quarterly reports shall be submitted in accordance with paragraph A.1.c.ii of the General Terms and Conditions of this permit. These reports shall also contain the total operating time of the emissions unit and the total operating time of the analyzer while the emissions unit was on line and the total NO<sub>x</sub> emissions for the calendar quarter (in tons).

\* Any 3-hour average SCR inlet temperature value that was more than 50 degrees Fahrenheit below the average temperature during the most recent emission testing that demonstrated the emissions unit was in compliance may be considered to be an exceedance only if it occurred concurrently with an exceedance of the 0.10 pound NO<sub>x</sub> per mmBtu or the 9.6 pounds NO<sub>x</sub>/hr limitations (based upon a 3-hour average of the emission rates).

[Authority for term: OAC rule 3745-77-07(C)(1), 40 CFR Part 64.9(a) and PTI 03-16048]

#### IV. Reporting Requirements (continued)

3. If the results of the monitoring or record keeping data indicate that the NO<sub>x</sub> emission limitations may have been exceeded, the permittee shall submit the results of that data, and document any corrective action taken to restore operation of the emissions unit, or its control equipment to its normal or usual manner of operation as expeditiously as practicable in accordance with good air pollution control practices for minimizing emissions. The reports shall be submitted in accordance with General Terms and Condition A.1.c.iii of this permit.

[Authority for term: OAC rule 3745-77-07(C)(1), 40 CFR Part 64.7(d) and 40 CFR Part 64.9(a)]

#### V. Testing Requirements

1. The permittee shall conduct, or have conducted, emission testing for this emissions unit in accordance with the following requirements:
  - a. The emission testing shall be conducted within 12 months prior to permit expiration.
  - b. The emission testing shall be conducted to demonstrate compliance with the allowable mass emission limitations for NO<sub>x</sub> and CO.
  - c. The following test method(s) shall be employed to demonstrate compliance with the allowable mass emission rate(s):
    - i. NO<sub>x</sub> - Methods 1 through 4 and 7 of 40 CFR, Part 60, Appendix A; and
    - ii. CO - Methods 1 through 10 of 40 CFR, Part 60, Appendix A.

Alternative U.S. EPA-approved test methods may be used with prior approval from the Ohio EPA.

- d. The test(s) shall be conducted while the emissions unit is operating at or near its maximum capacity, unless otherwise specified or approved by the appropriate Ohio EPA District Office or local air agency.

\* During the emission testing, the permittee shall also record the urea flow rate and the average temperature of the exhaust gases immediately before the catalyst bed for each run.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-16048]

2. Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the appropriate Ohio EPA District Office or local air agency. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Ohio EPA District Office's or local air agency's refusal to accept the results of the emission test(s).

Personnel from the appropriate Ohio EPA District Office or local air agency shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report on the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the appropriate Ohio EPA District Office or local air agency within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the appropriate Ohio EPA District Office or local air agency.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-16048]

**V. Testing Requirements (continued)**

**3.** Compliance with the emission limitations in section A.I. of the terms and conditions of this permit shall be determined in accordance with the following methods:

**3.a** Emission Limitation:  
0.10 lb NO<sub>x</sub>/mmBtu

Applicable Compliance Method: The permittee shall demonstrate compliance with the emission limitation above based upon the results of emission testing conducted in accordance with 40 CFR, Part 60, Appendix A, Methods 1 through 4 and 7.

Also, the permittee may demonstrate compliance with the emission limitation above based on the record keeping requirements specified in Section A.III.4 of this permit.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-16048]

**3.b** Emission Limitations:  
9.6 lbs NO<sub>x</sub>/hr and 42.05 tons/yr NO<sub>x</sub>

Applicable Compliance Method: The permittee shall demonstrate compliance with the hourly emission limitation above based upon emission testing conducted in accordance with 40 CFR, Part 60, Appendix A, Methods 1 through 4 and 7.

Also, the permittee may demonstrate compliance with the hourly emission limitation above based on the record keeping requirements specified in Section A.III.4 of this permit.

The annual emission limitation was determined by multiplying the hourly limitation by 8760, and then dividing by 2000. Therefore, provided compliance is shown with the hourly limitation, compliance shall also be shown with the annual limitation.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-16048]

**3.c** Emission Limitations:  
12.4 lbs CO/hr and 54.31 TPY CO

Applicable Compliance Method:

The permittee shall demonstrate compliance with the hourly emission limitation above based upon the results of emission testing conducted in accordance with Methods 1 through 4 and 10 of 40 CFR, Part 60, Appendix A.

The annual emission limitation was determined by multiplying the hourly limitation by 8760, and then dividing by 2000. Therefore, provided compliance is shown with the hourly limitation, compliance shall also be shown with the annual limitation.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-16048]

## V. Testing Requirements (continued)

- 3.d** Emission Limitations:  
1.04 lbs OC/hr and 4.56 tons/yr OC

Applicable Compliance Method:

The permittee shall demonstrate compliance with the lbs/hr emission limitation based upon calculations using the maximum rated capacity of the annealing furnace and auxiliary natural gas burners (96 mm Btu/hr), an AP-42 Chapter 1/4 (7/98) emission factor of 11.0 lb OC/10<sup>6</sup> cf of natural gas and 1020 Btu/cf of natural gas.

If required, compliance with the hourly limitation shall be determined using the test methods and procedures described in Methods 1 through 4, and Methods 18, 25, or 25A, as appropriate, of 40 CFR Part 60, Appendix A.

The annual emission limitation was determined by multiplying the hourly limitation by 8760, and then dividing by 2000. Therefore, provided compliance is shown with the hourly limitation, compliance shall also be shown with the annual limitation.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-16048]

- 3.e** Emission Limitations:  
0.72 lb PE/hr and 3.15 tons/yr PE

Applicable Compliance Method:

The permittee shall demonstrate compliance with the lb/hr emission limitation based upon calculations using the maximum rated capacity of the annealing furnace and the auxiliary natural gas burners (96 mm Btu/hr), an AP-42 Chapter 1.4 (7/98) emission factor of 7.6 lb PE/10<sup>6</sup> cf of natural gas and 1020 Btu/cf of natural gas.

If required, the permittee shall demonstrate compliance with the hourly particulate emission limitation in accordance with Methods 1 through 5 of 40 CFR, Part 60, Appendix A.

The annual emission limitation was determined by multiplying the hourly limitation by 8760, and then dividing by 2000. Therefore, provided compliance is shown with the hourly limitation, compliance shall also be shown with the annual limitation.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-16048]

## VI. Miscellaneous Requirements

**None**

**B. State Enforceable Section**

**I. Applicable Emissions Limitations and/or Control Requirements**

- The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
96.0 mmBtu/hr, natural gas-fired continuous annealing furnace, with 16 mmBtu/hr auxiliary natural gas-fired burners [the burners are used to maintain the selective catalytic reduction (SCR) control device operating temperature within the recommended range]	none	none

**2. Additional Terms and Conditions**

**None**

**II. Operational Restrictions**

**None**

**III. Monitoring and/or Record Keeping Requirements**

- The permit to install for this emissions unit was evaluated based on the actual materials (typically coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Ammonia

TLV (ug/m3): 17,000

Maximum Hourly Emission Rate (lbs/hr): 1.82

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 6.5

MAGLC (ug/m3): 404,800

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-16048]

### III. Monitoring and/or Record Keeping Requirements (continued)

2. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:
- a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
  - b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
  - c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

3. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"
- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
  - b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
  - c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-16048]

### IV. Reporting Requirements

None

### V. Testing Requirements

None

### VI. Miscellaneous Requirements

None

### Part III - Terms and Conditions for Emissions Units

**Emissions Unit ID:** AF-CGL2 (P010)

**Activity Description:** 71.8 MMBTU/hr Continuous Annealing Furnace with 5 MMBtu/hr aux. heat input (76.8 MMBtu/hr total)

#### A. State and Federally Enforceable Section

##### I. Applicable Emissions Limitations and/or Control Requirements

- The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
76.8 mmBtu/hr, natural gas-fired continuous annealing furnace, with five 1.0 mmBtu/hr auxiliary natural gas burners [the burners are used to maintain the selective catalytic reduction (SCR) control device operating temperature within the recommended range]	OAC rule 3745-17-07(A)	See A.I 2.a.
	OAC rule 3745-17-11(B)(2)	See A.I 2.b.
	OAC rule 3745-31-05(A)(3) (PTI #03-10957, issued December 4, 2001)	0.06 lb nitrogen oxides (NOx)/mmBtu (See A.I.2.c. and d.)  4.61 lbs NOx/hr (See A.I.2.c. and d.)  20.18 tons NOx/yr
		4.45 lbs carbon monoxide (CO)/hr and 19.49 tons CO/yr
		0.21 lb volatile organic compounds (VOC)/hr and 0.9 ton VOC/yr
		1.03 lbs particulate emissions (PE)/hr and 4.5 tons PE/yr (See A.I.2.e.)
	40 CFR, Part 64 - Compliance Assurance Monitoring (CAM)	3.99 tons ammonia/yr See A.II.3. and A.II.4., A.III.2. through A.III.6., A.III.9., A.IV.2. and A.IV.3.

## 2. Additional Terms and Conditions

- 2.a** This emissions unit is exempt from the visible emissions limitations specified in OAC rule 3745-17-07(A), pursuant to OAC rule 3745-17-07(A)(3)(h), because the emissions unit is not subject to the requirements of OAC rule 3745-17-11.
- 2.b** The uncontrolled mass rate of PE from this emissions unit is less than 10 pounds/hour. Therefore, pursuant to OAC rule 3745-17-11(A)(2)(a)(ii), Figure II of OAC rule 3745-17-11 does not apply. In addition, Table I of OAC rule 3745-17-11 does not apply because the facility is located in Putnam County, which is identified as a P-2 county.
- 2.c** The permittee shall employ the Bloom Model 2320-063 recuperative radiant tube furnace burners with all "air staged air nozzles," and two NOx OUT SCR systems for NOx emissions reduction. The air staged nozzle design along with the two NOx OUT SCR systems shall limit NOx emissions to 0.06 pound NOx/mmBtu of actual heat input, based on a 3-hour rolling average, when this emissions unit is in operation (including lance pilot). "In operation" shall mean that the main burners are firing and the product is moving through the continuous annealing furnace. "In operation" shall not include low fuel flow/low temperature furnace conditions, such as idle and furnace temperature ramp-up and ramp-down. During times that the furnace is not "in operation" and the main burners are idling or only the pilot burners are operating, the 4.61\* lbs/hr NOx limit shall be met at all times.
- \* The 4.61 pounds NOx per hour limitation shall be based on a 3-hour rolling average.
- 2.d** The NOx analyzers associated with this emissions unit are used as part of the process control system for the SCR unit. The data from the analyzers is used to adjust the urea injection flow rate to optimize the performance of the SCR unit. These analyzers were not installed with the intent of satisfying the requirements specified in 40 CFR Part 60, Appendix B, Performance Specification 2, and they can not be certified as true continuous NOx monitoring systems. Even though the analyzers can not be certified as true continuous NOx monitoring systems, they have demonstrated that they provide accurate NOx emission concentration data as compared to emission concentration data simultaneously obtained through 40 CFR Part 60, Appendix A, Method 7E. As such, the data from the analyzers will be used to ensure ongoing compliance with the NOx emission limitations.
- 2.e** All PE is assumed to be PM10.

## II. Operational Restrictions

1. The permittee shall burn only natural gas in this emissions unit.  
[Authority for term: OAC rule 3745-77-07(A)(1) and PTI 03-10957]
2. The maximum heat input (including the lance pilot) shall not exceed 76.8 mmBtu per hour.  
[Authority for term: OAC rule 3745-77-07(A)(1) and PTI 03-10957]
3. The average temperature of the exhaust gases immediately before the catalyst bed, for any 3-hour block of time when the emissions unit is in operation, shall not be lower than 50 degrees below the average SCR temperature recorded during the most recent compliance test.  
[Authority for term: OAC rule 3745-77-07(A)(1), 40 CFR Part 64.3(a) and PTI 03-10957]
4. The permittee shall continuously monitor and record NOx emissions at the discharge of each SCR unit, when the emissions unit is in operation, and shall continuously maintain NOx emissions within all the applicable limitations contained within this permit.  
[Authority for term: OAC rule 3745-77-07(A)(1), 40 CFR Part 64.3(a) and PTI 03-10957]

## III. Monitoring and/or Record Keeping Requirements

1. For each day during which the permittee burns a fuel other than natural gas, the permittee shall maintain a record of the type and quantity of fuel burned in this emissions unit.  
[Authority for term: OAC rule 3745-77-07(A)(1) and PTI 03-10957]

### III. Monitoring and/or Record Keeping Requirements (continued)

2. The urea/gas ratio shall be determined and adjusted on a continuous basis by a primary control circuit based on natural gas flow rate, which shall determine the appropriate urea flow rate to each SCR unit. Additionally, a secondary control circuit shall be utilized consisting of two NO<sub>x</sub> analyzers which shall increase or decrease the urea flow rate according to NO<sub>x</sub> concentrations observed at the discharge of each SCR unit. The purpose of the secondary control circuit is to optimize the efficiency of each SCR control system and minimize ammonia slip to the atmosphere.

[Authority for term: OAC rule 3745-77-07(C)(1), 40 CFR Part 64.3(a) and PTI 03-10957]

3. The permittee shall operate and maintain equipment necessary to continuously monitor the following parameters for the SCR NO<sub>x</sub> control unit while this emissions unit is in operation. The monitoring and recording devices shall be capable of accurately measuring the desired parameters. The monitoring and recording devices shall be calibrated, operated and maintained in accordance with the manufacturer's recommendations, with any modifications deemed necessary by the permittee:
- a. the urea flow rate, in gallons per hour;
  - b. the natural gas flow rate, in standard cubic feet per hour;
  - c. the SCR inlet temperature, in degrees Fahrenheit;
  - d. the number of hours the SCR unit was in operation; and
  - e. the number of hours this emissions unit was in operation.

[Authority for term: OAC rule 3745-77-07(C)(1), 40 CFR Part 64.3(a), 40 CFR Part 64.7(b), 40 CFR Part 64.9(b) and PTI 03-10957]

4. Whenever the monitored values for the urea flow rate and SCR inlet temperature deviate from the range specified below, the permittee shall promptly investigate the cause of the deviation. The permittee shall maintain records of the following information for each investigation: the date and time the deviation began and the magnitude of the deviation at that time, the date(s) the investigation was conducted, the names of the personnel who conducted the investigation, and the findings and recommendations.

In response to each required investigation to determine the cause of a deviation, the permittee shall take prompt corrective action to bring the operation of the control equipment within the acceptable ranges specified below, unless the permittee determines that corrective action is not necessary and documents the reasons for that determination and the date and time the deviation ended. The permittee shall maintain records of the following information for each corrective action taken: a description of the corrective action, the date it was completed, the date and time the deviation ended, the total period of time (in minutes) during which there was a deviation, the pressure drop and scrubber water flow rate immediately after the corrective action, and the names of the personnel who performed the work. Investigation and records required by this paragraph does not eliminate the need to comply with the requirements of OAC rule 3745-15-06 if it is determined that a malfunction has occurred.

- 4.a The urea flow rate shall be continuously maintained within the range of 1.5-14 gallons per hour at all times while the emissions unit is in operation, or as established during the most recent performance test that demonstrated the emissions unit was in compliance.

### III. Monitoring and/or Record Keeping Requirements (continued)

- 4.b** The SCR inlet temperature shall be continuously maintained, at all times while the emissions unit is in operation, at a value of not less than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated that the emissions unit was in compliance.

These ranges are effective for the duration of this permit, unless revisions are requested by the permittee and approved in writing by the appropriate Ohio EPA District Office or local air agency. The permittee may request revisions to the ranges based upon information obtained during future NOx emission tests that demonstrate compliance with the allowable NOx emission rate for this emissions unit. In addition, approved revisions to the ranges will not constitute a relaxation of the monitoring requirements of this permit and may be incorporated into this permit by means of a minor modification.

[Authority for term: OAC rule 3745-77-07(C)(1), 40 CFR 64.7(b), 40 CFR Part 64.3(a), 40 CFR 64.9(b) and PTI 03-10957]

- 5.** The permittee shall collect and record the following information each month for this emissions unit:
- a. the total urea usage, in gallons;
  - b. the total natural gas usage, in standard cubic feet;
  - c. the daily urea to natural gas flow ratio (3.a/3.b), in gallons of urea per each standard cubic feet of natural gas;
  - d. the monthly average Btu content of fuel (Btu per standard cubic foot) as specified by the natural gas supplier;
  - e. the heat input rate (b x d), in mmBtu;
  - f. the number of hours and specific hours the emissions unit was "in operation;"
  - g. the number of hours and specific hours the emissions unit was not "in operation;"
  - h. the average hourly heat input rate for this emissions unit (e/f), in mmBtu/hr;
  - i. the number of hours the SCR system associated with this emissions unit was in operation;
  - j. the total number of 3-hour average periods during which the temperature was monitored at the inlet of the SCR unit;
  - k. all 3-hour blocks of time during which the average temperature of the flue gases at the inlet to the SCR unit, when the emissions unit was in operation, was more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance;
  - l. all 3-hour periods during which the NOx emission rate was monitored at the outlet of the SCR unit;
  - m. all 3-hour periods during which the average NOx emission rate was greater than 4.61 pounds NOx per hour; and
  - n. all 3-hour periods during which the average NOx emission rate was greater that 0.06 pound NOx per mmBtu.

[Authority for term: OAC rule 3745-77-07(C)(1), 40 CFR Part 64.3(a), 40 CFR Part 64.9(b) and PTI 03-10957]

### III. Monitoring and/or Record Keeping Requirements (continued)

6. The permittee shall maintain daily records of the following information for this emissions unit:
- the total number of hours the emissions unit was in operation;
  - the total natural gas fuel usage, in mmcu ft.; and
  - the firing rate, in mmBtu/hr, using the following equation:

firing rate (mmBtu/hr) = [total daily natural gas usage (mmcu ft./day) x (the Btu value from Section A.III.3.d)] / the total number of hours the emissions unit was in operation (from Section 4.c above).

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-10957]

7. The permittee shall operate and maintain the existing equipment to continuously monitor and record NOx emissions from this emissions unit in units of the applicable standard. The NOx analyzers and recording devices shall be calibrated, operated and maintained in accordance with the manufacturer's recommendations and the procedures specified in the permittee's ISO 14001 document titled "Work Instructions for Monitoring, Calibration and Maintenance of O2 and NOx Analyzers."

The permittee shall maintain records of all data obtained by the continuous NOx analyzers including, but not limited to, parts per million NOx on an instantaneous (one-minute) basis, emissions of NOx in units of the applicable standard in the appropriate averaging period (i.e., pounds/hour and pounds/mmBtu for each rolling, 3-hour period), results of daily zero/span calibration checks, and magnitude of manual calibration adjustments.

[Authority for term: OAC rule 3745-77-07(C)(1), 40 CFR Part 64.7(c), 40 CFR Part 64.9(b) and PTI 03-10957]

8. At all times, the permittee shall maintain the monitoring, including but not limited to, maintaining necessary parts for routine repairs of the monitoring equipment.

[Authority for term: OAC rule 3745-77-07(C)(1) and 40 CFR Part 64.7(b)]

9. After approval of monitoring under this part, if the permittee identifies a failure to achieve compliance with an emission limitation or standard for which the approved monitoring did not provide an indication of an excursion or exceedance while providing valid data, or the results of compliance or performance testing document a need to modify the existing indicator ranges or designated conditions, the permittee shall promptly notify the permitting authority and, if necessary, submit a proposed modification to the part 70 or 71 permit to address the necessary monitoring changes. Such a modification may include, but is not limited to, reestablishing indicator ranges or designated conditions, modifying the frequency of conducting monitoring and collecting data, or the monitoring of additional parameters.

[Authority for term: OAC rule 3745-77-07(C)(1) and 40 CFR 64.7(e)]

### III. Monitoring and/or Record Keeping Requirements (continued)

10. The CAM plan for this emissions unit has been developed for NOx emissions. The CAM performance indicators for the selective catalytic reduction (SCR) controlling this emissions unit are urea injection flowrate, inlet gas temperature at the SCR, NOx ppm measurement and O2% measurement post SCR which is based upon the result of site-specific NOx emission testing and manufacturer recommendations. When the performance indicators are operating outside the indicator ranges, the permittee shall take corrective action to restore operation of the emissions unit and/or its control equipment to its normal or usual manner of operation as expeditiously as practicable in accordance with good air pollution control practices for minimizing emissions and comply with the reporting requirements specified in Section A.IV.3 below. The emissions unit and control equipment shall be run in accordance with the approved CAM Plan, or any approved revision of the Plan.

SCR operating parameters will be re-verified through periodic emission testing, or if the SCR or emissions units operating conditions change. In addition to periodic monitoring of the SCR operating parameters, the permittee also has an inspection/preventative maintenance program for the SCR. Based on the results of the inspection/preventative maintenance program, repairs to the SCR shall be made as needed. If the current CAM indicators and/or the SCR inspection/preventative maintenance program is considered inadequate, the permittee will develop a Quality Improvement Plan.

[Authority for term: OAC rule 3745-77-07(A)(3)(a), OAC rule 3745-77-07(A)(3)(b), 40 CFR Part 64.3(a), 40 CFR Part 64.6(c), 40 CFR Part 64.7(d) and 40 CFR Part 64.8]

### IV. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports that identify each day when a fuel other than natural gas was burned in this emissions unit. Each report shall be submitted within 30 days after the deviation occurs.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-10957]

2. The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the following
- the 3-hour average NOx emission limitation of 4.61 lbs/hr;
  - the 3-hour average NOx emission limitation of 0.06 lb/mmBtu;
  - the urea flow rate range, in gallons per hour;
  - the 3-hour average SCR inlet temperature required by section A.II.3;\* and
  - the maximum heat input rate of 76.8 mmBtu per hour.

All quarterly reports shall be submitted in accordance with paragraph A.1.c.ii of the General Terms and Conditions of this permit. These reports shall also contain the total operating time of the emissions unit and the total operating time of the analyzer while the emissions unit was on line and the total NOx emissions for the calendar quarter (in tons).

\* Any 3-hour average SCR inlet temperature value that was more than 50 degrees Fahrenheit below the average temperature during the most recent emission testing that demonstrated the emissions unit was in compliance may be considered to be an exceedance only if it occurred concurrently with an exceedance of the 0.06 pound NOx per mmBtu or the 4.61 pounds NOx/hr limitations (based upon a 3-hour average of the emission rates).

[Authority for term: OAC rule 3745-77-07(C)(1), 40 CFR Part 64.9(a) and PTI 03-16048]

#### IV. Reporting Requirements (continued)

3. If the results of the monitoring or record keeping data indicate that the NO<sub>x</sub> emission limitations may have been exceeded, the permittee shall submit the results of that data, and document any corrective action taken to restore operation of the emissions unit, or its control equipment to its normal or usual manner of operation as expeditiously as practicable in accordance with good air pollution control practices for minimizing emissions. The reports shall be submitted in accordance with General Terms and Condition A.1.c.iii of this permit.

[Authority for term: OAC rule 3745-77-07(C)(1), 40 CFR Part 64.7(d) and 40 CFR Part 64.9(a)]

#### V. Testing Requirements

1. The permittee shall conduct, or have conducted, emission testing for this emissions unit in accordance with the following requirements:
  - a. The emission testing shall be conducted within 12 months prior to permit expiration.
  - b. The emission testing shall be conducted to demonstrate compliance with the allowable mass emission limitations for NO<sub>x</sub> and CO.
  - c. The following test method(s) shall be employed to demonstrate compliance with the allowable mass emission rate(s):

i. NO<sub>x</sub> - Methods 1 through 4 and 7 of 40 CFR, Part 60, Appendix A; and

ii. CO - Methods 1 through 10 of 40 CFR, Part 60, Appendix A.

Alternative U.S. EPA-approved test methods may be used with prior approval from the Ohio EPA.

d. The test(s) shall be conducted while the emissions unit is operating at or near its maximum capacity, unless otherwise specified or approved by the appropriate Ohio EPA District Office or local air agency.

\* During the emission testing, the permittee shall also record the urea flow rate and the average temperature of the exhaust gases immediately before the catalyst bed for each run.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-10957]

2. Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the appropriate Ohio EPA District Office or local air agency. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Ohio EPA District Office's or local air agency's refusal to accept the results of the emission test(s).

Personnel from the appropriate Ohio EPA District Office or local air agency shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report on the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the appropriate Ohio EPA District Office or local air agency within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the appropriate Ohio EPA District Office or local air agency.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-10957]

3. Compliance with the emission limitations in section A.I. of the terms and conditions of this permit shall be determined in accordance with the following methods:

**V. Testing Requirements (continued)**

**3.a** Emission Limitation:  
0.06 lb NO<sub>x</sub>/mmBtu

Applicable Compliance Method:

The permittee shall demonstrate compliance with the emission limitation above based upon the results of emission testing conducted in accordance with 40 CFR, Part 60, Appendix A, Methods 1 through 4 and 7.

Also, the permittee may demonstrate compliance with the emission limitation above based on the record keeping requirements specified in Section A.III.4 of this permit.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-10957]

**3.b** Emission Limitations:  
4.61 lbs NO<sub>x</sub>/hr and 20.18 tons/yr

Applicable Compliance Method: The permittee shall demonstrate compliance with the hourly emission limitation above based upon the results of emission testing conducted in accordance with 40 CFR, Part 60, Appendix A, Methods 1 through 4 and 7.

Also, the permittee may demonstrate compliance with the hourly limitation above based on the record keeping requirements specified in Section A.III.4 of this permit.

The annual emission limitation was determined by multiplying the hourly limitation by 8760, and then dividing by 2000. Therefore, provided compliance is shown with the hourly limitation, compliance shall also be shown with the annual limitation.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-10957]

**3.c** Emission Limitations:  
1.03 lbs PE/hr and 4.5 tons/yr

Applicable Compliance Method:

The permittee may determine compliance with the hourly limitation above by multiplying an emission factor (from AP-42, Fifth Edition, Table 1.4-2 (revised 7/98)) of 7.6 lbs PE (filterable)/mm cu. ft of natural gas by the emissions unit's maximum hourly fuel consumption rate (mmcu ft./hr).

If required, the permittee shall demonstrate compliance with the hourly particulate emission limitation in accordance with the procedures and methods specified in Methods 1 through 5 of 40 CFR Part 60, Appendix A.

The annual emission limitation was determined by multiplying the hourly limitation by 8760, and then dividing by 2000. Therefore, provided compliance is shown with the hourly limitation, compliance shall also be shown with the annual limitation.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-10957]

## V. Testing Requirements (continued)

**3.d** Emission Limitations:  
0.21 lb VOC/hr and 0.9 ton/yr

Applicable Compliance Method:

The permittee may determine compliance with the hourly limitation above by multiplying an emission factor (from AP-42, Fifth Edition, Table 1.4-2 (revised 7/98)) of 5.5 lbs VOC/mm<sup>3</sup> cu. ft of natural gas by the emissions unit's maximum hourly fuel consumption rate (mm<sup>3</sup> cu. ft./hr).

If required, compliance with the hourly limitation shall be determined using the test methods and procedures described in Methods 1 through 4, and Methods 18, 25, or 25A, as appropriate, of 40 CFR Part 60, Appendix A.

The annual emission limitation was determined by multiplying the hourly limitation by 8760, and then dividing by 2000. Therefore, provided compliance is shown with the hourly limitation, compliance shall also be shown with the annual limitation.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-10957]

**3.e** Emission Limitations:  
4.45 lbs CO/hr and 19.49 tons/yr

Applicable Compliance Method:

The permittee shall demonstrate compliance with the hourly emission limitation above based upon the results of emission testing conducted in accordance with Methods 1 through 4 and 10 of 40 CFR, Part 60, Appendix A.

The annual emission limitation was determined by multiplying the hourly limitation by 8760, and then dividing by 2000. Therefore, provided compliance is shown with the hourly limitation, compliance shall also be shown with the annual limitation.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-10957]

**3.f** Emission Limitation:  
3.99 tons ammonia/yr

The limitation above was established at the emissions unit's potential to emit, calculated as follows:

$$\text{ammonia emissions (tons/year)} = \text{FGR} \times (0.0442/1000000) \times (8760 /2000)**$$

where:

FGR = total flue gas flow rate, in dscfh

SLP = maximum ammonia slip (12.5 ppm<sub>d</sub>)

\* conversion factor from grams/liter to lbs/cubic foot

\*\* conversion factor (to convert from lbs/hr to tons/year)

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-10957]

## VI. Miscellaneous Requirements

**None**

**B. State Enforceable Section**

**I. Applicable Emissions Limitations and/or Control Requirements**

- The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
76.8 mmBtu/hr, natural gas-fired continuous annealing furnace, with five 1.0 mmBtu/hr auxiliary natural gas burners [the burners are used to maintain the selective catalytic reduction (SCR) control device operating temperature within the recommended range]	none	none

**2. Additional Terms and Conditions**

**None**

**II. Operational Restrictions**

**None**

**III. Monitoring and/or Record Keeping Requirements**

- The permit to install for this emissions unit was evaluated based on the actual materials (typically coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Ammonia

TLV (mg/m3): 17,000

Maximum Hourly Emission Rate (lbs/hr): 0.91

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 0.4172

MAGLC (ug/m3): 404.8

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-10957]

### III. Monitoring and/or Record Keeping Requirements (continued)

2. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:
  - a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
  - b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
  - c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

3. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"
  - a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
  - b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
  - c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

[Authority for term: OAC rule 3745-77-07(C)(1) and PTI 03-10957]

### IV. Reporting Requirements

None

### V. Testing Requirements

None

### VI. Miscellaneous Requirements

None

\*\*\*\*\*

**THIS IS THE LAST PAGE OF THE PERMIT**

\*\*\*\*\*

# Statement of Basis For Title V Permit

Part I - General	
Company Name	Pro-Tec Coating Company
Premise Number	03-69-00-0025
What makes this facility a Title V facility?	NOx, CO
Has each insignificant emissions unit been reviewed to confirm it meets the definition in OAC rule 3745-77-01 (U)?	Yes
Were there any "common control" issues associated with this facility? If yes, provide a summary of those issues and explain how the DAPC decided to resolve them.	No
Please identify the affected unit(s) and associated PTI, if applicable, along with a brief description of any changes to the permit document that qualify as a minor permit modification per OAC rule 3745-77-08(C)(1)	<p>P001 PTI 03-16048 issued June 17, 2004 as an administrative modification to increase the maximum firing rate and the respective emission rates for the pollutants. Company did not physically modify the emissions unit, the unit was always capable of firing at this emission rate.</p> <p>B001, B002, B043, B044 PTI 03-14070 (Chapter 31 modification of PTI 03-6093 issued August 31, 2000) issued August 28, 2003 to physically and permanently derate the maximum capacity of each boiler from a heat input of 20.9 to 14.7 mmBtu/hr.</p> <p>B001, B002, B043, B044 PTI 03-14070 (modification) issued November 8, 2007 to adjust NOx limits to comply Consent Decree with the United States of America - Civil Action No. 3:98CV 7749.</p>
Please identify the affected unit(s) and associated PTI, if applicable, along with a brief description of any changes to the permit document that qualify as a significant permit modification per OAC rule 3745-77-08(C)(3)	N/A
Please identify the affected unit(s) and associated PTI, if applicable, along with a brief description of any changes to the permit document that qualify as a reopening per OAC rule 3745-77-08(D)	N/A
Please identify the affected unit(s) and associated PTI, if applicable, along with a brief description of any changes to the permit document resulting from a renewal per OAC rule 3745-77-08(E)	P001 & P010 - addition of CAM terms; B001, B002, B043, B044 - addition of subpart Dc monitoring & reporting term; For all emissions units (B001, B002, B043, B044, K001, P001 & P010) added authority terms and PTI issuance dates.

Part II (State and Federally Enforceable Requirements)			
Term and Condition (paragraph)	Basis		Comments
	SIP (3745-)	Other	

C

**Instructions for Part II:**

Each paragraph in Part II must be identified and the remainder of the table completed. If the SIP (not including 31-05) is the basis for the term and condition, identify the specific rule. If the SIP is not the basis for the term and condition, place an "N" in the column under "SIP." If the basis for the term and condition is something other than the SIP, including 3745-31-05, NSPS or MACT, a "Y" should be noted in the "Other" column, and if not, an "N" should be noted. Whether the basis for the term and condition is the "SIP" or "Other," an explanation of each term and condition in Part II must be provided in the "Comments" section.

Part III (Requirements Within the State and Federally Enforceable Section)															
Any unusual requirements or aspects of the terms and conditions in Part III that are not self-explanatory should be explained in the appropriate comment field or in a paragraph following the table for Part III.															
EU(s)	Limitation	Basis		ND	OR	M	St	ENF	R	St	Rp	St	ET	Misc	Comments
		SIP (3745-)	Other												
B001, B002, B043, B044	0.033 lb NOx/mmbtu	N	Y	Y	Y	Y	N	Y	Y	N	Y	N	N	N	Basis-Consent decree  ND-emission limitation specified is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3)  OR-unit restricted to combustion of only natural gas, monitoring, record keeping, reporting requirements specified.  ET- none per Ohio EPA engineering guide 16  CAM is currently not applicable

B001, B002, B043, B044	0.49 lb NOx/hr, 2.15 tons NOx/yr	N	Y	N	Y	Y	N	N	Y	N	Y	N	N	N	<p>Basis-OAC rule 3745-31-05 All terms and conditions have been transferred from the PTI.</p> <p>OR-unit restricted to combustion of only natural gas, monitoring, record keeping, reporting requirements specified.</p> <p>ET- none per Ohio EPA engineering guide 16</p> <p>CAM is not currently applicable.</p>
B001, B002, B043, B044	0.54 lb CO/hr, 2.4 tons CO/yr	N	Y	N	Y	Y	N	N	Y	N	Y	N	N	N	<p>Basis-OAC rule 3745-31-05 All terms and conditions have been transferred from the PTI.</p> <p>OR-unit restricted to combustion of only natural gas, monitoring, record keeping, reporting requirements specified.</p> <p>ET- none per Ohio EPA engineering guide 16</p> <p>CAM is not currently applicable.</p>
B001, B002, B043, B044	0.11 lb PE/hr, 0.5 ton PE/yr	N	Y	N	Y	Y	N	N	Y	N	Y	N	N	N	<p>Basis-OAC rule 3745-31-05 All terms and conditions have been transferred from the PTI.</p> <p>OR-unit restricted to combustion of only natural gas, monitoring, record keeping, reporting requirements specified.</p> <p>ET-The M/R and Rp requirements are sufficient to demonstrate compliance.</p> <p>CAM is currently not applicable</p>
B001, B002, B043, B044	20% opacity except as provided by rule	17- 07(A)(1)	N	N	Y	Y	N	N	Y	N	Y	N	N	N	<p>OR-unit restricted to combustion of only natural gas, monitoring, record keeping, reporting requirements specified.</p> <p>ET-The M/R and Rp requirements are sufficient to demonstrate compliance without requiring formal Method 9 readings be conducted.</p> <p>CAM is currently not applicable</p>

B001, B002, B043, B044	NONE	18-06	N	Y	Y	Y	N	N	Y	N	Y	N	N	N	ND-no SO2 emission limitation established because this emissions unit only employs natural gas as fuel.  OR-unit restricted to combustion of only natural gas, monitoring, record keeping, reporting requirements specified.  ET-no emission limitation established  CAM is currently not applicable
B001, B002, B043, B044	NONE	17-10(B)(1)	N	Y	N	N	N	N	N	N	N	N	N	N	ND-emission limitation established by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3)  M/R, Rp, ET - no emission limitation established
B001, B002, B043, B044	NONE	23-06(B)	N	Y	N	N	N	N	N	N	N	N	N	N	ND-permittee has satisfied the "latest available control techniques and operating practices" required pursuant to OAC rule 3745-23-06(B) by committing to comply with BAT.  M/R, Rp, ET - no emission limitation established
B001, B002, B043, B044	NONE	21-08(B)	N	Y	N	N	N	N	N	N	N	N	N	N	ND-permittee has satisfied the "best available control techniques and operating practices" required pursuant to OAC rule 3745-21-08(B) by committing to comply with BAT.  M/R, Rp, ET - no emission limitation established
K001	2.6 lbs VOC/gal- water	21-09(E)	N	N	N	Y	N	N	Y	N	Y	N	Y	N	CAM is currently not applicable
K001	0.28 kg VOC/lit solids	Part 60, Subpart TT	N	N	N	Y	N	N	Y	N	Y	N	Y	N	CAM is currently not applicable
K001	42.0 lbs VOC/hr	N	Y	N	N	N	N	N	N	N	N	N	N	N	Basis-OAC rule 3745-31-05 All terms and conditions have been transferred from the PTI.  M/R, Rp and ET- Emission limit represents PTE  CAM is currently not applicable

K001	24.44 tpy	N	Y	N	N	Y	N	N	Y	N	Y	N	N	N	<p>Basis-OAC rule 3745-31-05 All terms and conditions have been transferred from the PTI.</p> <p>ET-The M/R and Rp requirements are sufficient to demonstrate compliance.</p> <p>CAM is currently not applicable.</p>
K001	0.1 lb PE/hr, 0.44 tpy	N	Y	N	N	N	N	N	N	N	N	N	N	N	<p>Basis-OAC rule 3745-31-05 All terms and conditions have been transferred from the PTI.</p> <p>M, R, Rp-limits based on particulate in coating, monitoring would not aid in compliance determination</p> <p>ET-no emissions testing required pursuant to EG#16, compliance demonstrated through use of coating calculations</p> <p>CAM is currently not applicable</p>
P001	0.72 lb PE/hr; 3.15 tpy	31-05	N	N	Y	Y	N	N	Y	N	Y	N	N	N	<p>Basis-OAC rule 3745-31-05 All terms and conditions have been transferred from the PTI.</p> <p>OR-unit restricted to combust only natural gas, monitoring, record keeping, reporting requirements specified</p> <p>ET-calculations using AP42 emissiion factors at maximum capacity and the M/R &amp; Rp requirements are sufficient to demonstrate compliance without requiring formal Method 9 readings being conducted.</p> <p>CAM is currently not applicable</p>
P001	0.10 lb NOx/mmbtu	N	Y	N	Y	Y	N	Y	Y	N	Y	N	Y	N	<p>Basis-Consent decree</p> <p>OR- permittee required to install a selective catalytic reduction control device to continuously control Nox emissions to the specified restriction.</p> <p>CAM is applicable and CAM plan has been submitted.</p>
P001	9.6 lbs Nox/hr, 42.05 tpy	N	Y	N	Y	Y	N	N	Y	N	Y	N	Y	N	<p>Basis-OAC rule 3745-31-05 All terms and conditions have been transferred from the PTI.</p> <p>OR- permittee required to install a selective catalytic reduction control device to continuously control Nox emissions to the specified restriction.</p> <p>CAM is applicable and CAM plan has been submitted.</p>

P001	1.04 lbs OC/hr, 4.56 tpy	N	Y	N	Y	Y	N	N	Y	N	Y	N	N	N	<p>Basis-OAC rule 3745-31-05 All terms and conditions have been transferred from the PTI.</p> <p>OR-unit restricted to combust only natural gas, monitoring, record keeping, reporting requirements specified</p> <p>ET-AP42 emission factors adequate to show compliance</p> <p>CAM is currently not applicable</p>
P001	12.4 lbs CO/hr, 54.31 tpy	N	Y	N	y	y	n	n	y	n	y	n	y	n	<p>Basis-OAC rule 3745-31-05 All terms and conditions have been transferred from the PTI.</p> <p>OR-unit restricted to combust only natural gas, monitoring, record keeping, reporting requirements specified</p> <p>CAM is currently not applicable</p>
P010	1.03 lbs PE/hr, 4.5 tpy	N	Y	N	Y	Y	N	N	Y	N	Y	N	N	N	<p>Basis-OAC rule 3745-31-05 All terms and conditions have been transferred from the PTI.</p> <p>OR-unit restricted to combust only natural gas, monitoring, record keeping, reporting requirements specified</p> <p>ET-calculations using AP42 emissiion factors at maximum capacity and the M/R &amp; Rp requirements are sufficient to demonstrate compliance without requiring formal Method 9 readings being conducted.</p> <p>CAM is currently not applicable</p>
P010	0.06 lb NOx/mmbtu	N	Y	N	Y	Y	N	N	Y	N	Y	N	Y	N	<p>Basis-OAC rule 3745-31-05 All terms and conditions have been transferred from the PTI.</p> <p>OR- permittee required to install a selective catalytic reduction control device to continuously control Nox emissions to the specified restriction.</p> <p>CAM is applicable and CAM plan has been submitted.</p>
P010	4.61 lbs Nox/hr, 20.18 tpy	N	Y	N	Y	Y	N	N	Y	N	Y	N	Y	N	<p>Basis-OAC rule 3745-31-05 All terms and conditions have been transferred from the PTI.</p> <p>OR- permittee required to install a selective catalytic reduction control device to continuously control Nox emissions to the specified restriction.</p> <p>CAM is applicable and CAM plan has been submitted.</p>

P010	0.21 lb VOC/hr, 0.90 tpy	N	Y	N	Y	Y	N	N	Y	N	Y	N	N	N	Basis-OAC rule 3745-31-05 All terms and conditions have been transferred from the PTI.  OR-unit restricted to combust only natural gas, monitoring, record keeping, reporting requirements specified  ET-AP42 emission factors adequate to show compliance  CAM is currently not applicable
P010	4.45 lbs CO/hr, 19.49 tpy	N	Y	N	y	y	n	n	y	n	y	n	y	n	Basis-OAC rule 3745-31-05 All terms and conditions have been transferred from the PTI.  OR-unit restricted to combust only natural gas, monitoring, record keeping, reporting requirements specified  CAM is currently not applicable
P010	3.99 tons ammonia/year	N	Y	N	N	N	N	N	N	N	N	N	N	N	Basis-OAC rule 3745-31-05 All terms and conditions have been transferred from the PTI.  M, R, Rp, ET calculations based on PTE, therefore no monitoring, record keeping and reporting requirements necessary.  CAM is currently not applicable.
P001 P010	CAM plan	N	Y	N	N	Y	N	N	Y	N	Y	N	N	N	Basis-40 CFR Part 64

EU = emissions unit ID

ND = negative declaration (i.e., term that indicates that a particular rule(s) is (are) not applicable to a specific emissions unit)

OR = operational restriction

M = monitoring requirements

St = streamlining term used to replace a PTI monitoring, record keeping, or reporting requirement with an equivalent or more stringent requirement

ENF = did noncompliance issues drive the monitoring requirements?

R = record keeping requirements

Rp = reporting requirements

ET = emission testing requirements (not including compliance method terms)

Misc = miscellaneous requirements

**C Instructions for Part III:**

C All non-insignificant EUs must be included in this table. For each EU, or group of similar EUs, each emission limitation and control requirement specified in section A.I.1 and A.I.2 of the permit must be identified and the remainder of the table completed.

C If the SIP (not including OAC rule 3745-31-05) is the basis for the term and condition, identify the specific rule. If the SIP is not the basis for the term and condition, place an "N" in the

column under "SIP." If the basis for the term and condition is something other than the SIP, including OAC rule 3745-31-05, NSPS or MACT, a "Y" should be noted in the "Other" column, and if not, an "N" should be noted. If the basis for the term and condition is "Other," an explanation of the basis must be provided in the "Comments" section. If OAC rule 3745-31-05 is cited in the "Other" column, please indicate in the "Comments" section whether or not all of the requirements have been transferred from the permit to install.

- To complete the remainder of the table after "Basis," except for the "Comments" section, simply specify a "Y" for yes or an "N" for no. For the "M," "R," "Rp," and "ET" columns, if "N" is specified, there should be a brief explanation in the "Comments" section as to why there are no requirements. If a brief explanation is provided in the "Comments" section, please do not simply indicate that monitoring or testing requirements are not necessary. An explanation of why a requirement is not necessary should be specified.

When periodic monitoring requirements are established to satisfy the provisions of OAC rule 3745-77-07(A)(3)(a)(ii), the basis for the requirements must be explained. Whenever Engineering Guides have been used to establish the periodic monitoring requirements, the applicable Engineering Guide may be referenced in the "Comments" section. An example that should be clarified would be the situation where it has been determined that control equipment parametric monitoring will be used to evaluate ongoing compliance in lieu of performing frequent emission tests. In this situation, Engineering Guide #65 would be referenced along with the fact that the parametric monitoring range (or minimum value) corresponded to the range (or minimum value) documented during the most recent emission tests that demonstrated that the emissions unit was in compliance. If streamlining language is included in the "Monitoring," "Record Keeping," or "Reporting" requirements sections of the permit, explain which requirements are being streamlined (mark appropriate column above) and provide a brief explanation of why the streamlined term is equal to or more stringent than the "Monitoring," "Record Keeping," or "Reporting" requirements specified in the permit to install. If Engineering Guide #16 was used as the basis for establishing an emission test frequency, a simple note referencing the Engineering Guide in the "Comments" section would be sufficient.

Also, if a "Y" is noted under "OR," "Misc.," "St," "ND," or "ENF" an explanation of the requirements must be provided in the "Comments" section. In addition to a general explanation of the "OR," "Misc.," "St," "ND," and/or "ENF" the following must be provided:

1. For an operational restriction, clarify if appropriate monitoring, record keeping, and reporting requirements have been specified for the operational restriction and indicate whether or not CAM is currently applicable.
2. If a control plan and schedule is included in the "Miscellaneous Requirements" section of the permit, provide an explanation in the "Comments" section of the violation, basis for the violation, and the company's proposed control plan and schedule.
3. If the "ND" column above is marked, please identify the particular rule(s) that is (are) not applicable to the specified emissions unit.
2. If the "ENF" column above is marked, please provide a brief explanation of the noncompliance issue(s) which prompted the use of the specified monitoring requirement.

An explanation is not required if an "N" is noted in the "OR," "Misc.," "St," "ND," or "ENF" columns.

**C** **Additional information for modifications** - Several types of modifications, as defined by rule, may be processed concurrently. Please provide enough of a description for someone wishing to review the changes to the permit language to be able to identify where the change is made in the permit document. This brief description should be identified in the appropriate row in the first table of this form by replacing the "N/A" in the applicable row(s). Please also indicate if the modification is being initiated by an appeal by including the ERAC case number in the "Comments" area. Please update the term-specific text in the SOB as warranted (full insertion or replacement is acceptable; bold italic and strike out is not needed). Note all modification/reopening rows should remain "N/A" when developing the SOB during the initial permit development. Note: APA's and Off-permit changes do not need to be noted in the SOB.