State of Ohio Environmental Protection Agency

Street Address:
Lazarus Gov. Center
122 S. Front Street
Columbus, OH 43215

TELE: (614) 644-3020 **FAX:** (614) 644-2329

Mailing Address:
Lazarus Gov. Center
P.O. Box 1049
Columbus, OH 43216-1049

05/27/99

CERTIFIED MAIL

RE: Draft Title V Chapter 3745-77 permit

02-85-00-0270
Mt. Eaton Landfill
Freeman Mullet
P.O. Box 256
Mt. Eaton, OH 44659

Dear Freeman Mullet:

You are hereby notified that the Ohio Environmental Protection Agency has prepared the enclosed draft of the Title V permit for the facility referenced above. The purpose of this draft is to solicit public comments. A public notice concerning the draft will appear in the Ohio EPA Weekly Review and the major newspaper in the county where the facility is located. Comments and/or a request for a public hearing from the public and any affected parties will be accepted by Northeast District Office within 30 days of the date of publication in the newspaper. You will be notified in writing if a public hearing is scheduled.

A decision on processing the Title V permit will be made after consideration of written public comments and oral testimony (if a public hearing is conducted). After the comment period, you will be provided with a Preliminary Proposed Title V permit and an opportunity to comment prior to the Proposed Title V permit submittal to USEPA.

If you have any questions or comments concerning this draft Title V permit, please contact Northeast District Office.

Very truly yours,

Thomas G. Rigo

Thomas G. Rigo, Manager
Field Operations and Permit Section
Division of Air Pollution Control

cc: USEPA
Jim Orlemann, DAPC Engineering
Michael Ahern, DAPC PMU
Northeast District Office

Ohio EPA
State of Ohio Environmental Protection Agency

TITLE V PERMIT

Issue Date: 05/27/99

DRAFT

Effective Date:

Expiration Date:

This document constitutes issuance to:

Mt. Eaton Landfill
P.O. Box 336
Mt. Eaton, OH 44659

of a Title V permit for Facility ID: 02-85-00-0270

Emissions Unit ID (Company ID)/
Emissions Unit Activity Description:
F001 (Roads and Parking)
Fugitive Dust: Access roads and parking lots for daily operations and contruction activities. Locations change as needed. 7.3 acres.

F002 (Operations)
Fugitive Dust and Methane Gas: Daily waste placement and daily covering operations

F003 (Storage Piles & Material Handling)
Storage piles & material handling for covering and capping operations

You will be contacted approximately eighteen (18) months prior to the expiration date regarding the renewal of this permit. If you are not contacted, please contact the appropriate Ohio EPA District Office or local air agency listed below. This permit and the authorization to operate the air contaminant sources (emissions units) at this facility shall expire at midnight on the expiration date shown above. If a renewal permit is not issued prior to the expiration date, the permittee may continue to operate pursuant to OAC rule 3745-77-04(A) and in accordance with the terms of this permit beyond the expiration date, provided that a complete renewal application is submitted no earlier than eighteen (18) months and no later than one-hundred eighty (180) days prior to the expiration date.

Described below is the current Ohio EPA District Office or local air agency that is responsible for processing and administering your Title V permit:

Northeast District Office
2110 East Aurora Road
Twinsburg, OH 44087
(330) 425-9171

OHIO ENVIRONMENTAL PROTECTION AGENCY

Christopher Jones
Director

PART I - GENERAL TERMS AND CONDITIONS

A. State and Federally Enforceable Section

1. Monitoring and Related Recordkeeping and Reporting Requirements

a. Except as may otherwise be provided in the terms and conditions for a specific emissions unit, the permittee shall maintain records that include the following, where applicable, for any required monitoring under this permit:

   i. The date, place (as defined in the permit), and time of sampling or measurements.
   ii. The date(s) analyses were performed.
   iii. The company or entity that performed the analyses.
   iv. The analytical techniques or methods used.
   v. The results of such analyses.
   vi. The operating conditions existing at the time of sampling or measurement.

b. Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

c. Except as may otherwise be provided in the terms and conditions for a specific emissions unit, the permittee shall submit required reports in the following manner:

   i. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
   ii. Quarterly written reports of (i) any deviations from federally enforceable emission limitations, operational restrictions, and control device operating parameter limitations, excluding deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06, that have been detected by the testing, monitoring and recordkeeping requirements specified in this permit, (ii) the probable cause of such deviations, and (iii) any corrective actions or preventive measures taken, shall be promptly made to the appropriate Ohio EPA District Office or local air agency. These quarterly written reports shall satisfy the requirements of OAC rule 3745-77-07(A)(3)(c)(i) and (ii) pertaining to the submission of monitoring reports every six months and OAC rule 3745-77-07(A)(3)(c)(iii) pertaining to the prompt reporting of all deviations except malfunctions, which shall be reported in accordance with OAC rule 3745-15-06. The written reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.) See B.8 below if no deviations occurred during the quarter.
   iii. Written reports, which identify any deviations from the federally enforceable monitoring, recordkeeping, and reporting requirements contained in this permit shall be submitted to the appropriate Ohio EPA District Office or local air agency every six months, i.e., by January 31 and July 31 of each year for the previous six calendar months. These semi-annual written reports shall satisfy the requirements of OAC rule 3745-77-07(A)(3)(c)(i) and (ii) pertaining to the reporting of any deviations related to the monitoring, recordkeeping, and reporting

requirements. If no deviations occurred during a six-month period, the permittee shall submit a semi-annual report, which states that no deviations occurred during that period.

iv. Each written report shall be signed by a responsible official certifying that, based on information and belief formed after reasonable inquiry, the statements and information in the report are true, accurate, and complete.

2. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction, i.e., upset, of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. (The definition of an upset condition shall be the same as that used in OAC rule 3745-15-06(B)(1) for a malfunction.) The verbal and written reports submitted pursuant to OAC rule 3745-15-06 shall satisfy the requirements of OAC rule 3745-77-07(A)(3)(c)(iii) pertaining to the prompt reporting of deviations caused by malfunctions or upsets.

Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emission unit(s) that is (are) served by such control system(s).

3. Risk Management Plans

If the permittee is required to develop and register a risk management plan pursuant to section 112(r) of the Clean Air Act, as amended, 42 U.S.C. 7401 et seq. ("Act"), the permittee shall comply with the requirement to register such a plan.

4. Title IV Provisions

If the permittee is subject to the requirements of 40 CFR Part 72 concerning acid rain, the permittee shall ensure that any affected emissions unit complies with those requirements. Emissions exceeding any allowances that are lawfully held under Title IV of the Act, or any regulations adopted thereunder, are prohibited.

5. Severability Clause

A determination that any term or condition of this permit is invalid shall not invalidate the force or effect of any other term or condition thereof, except to the extent that any other term or condition depends in whole or in part for its operation or implementation upon the term or condition declared invalid.

6. General Requirements

a. The permittee must comply with all terms and conditions of this permit. Any noncompliance with the federally enforceable terms and conditions of this permit constitutes a violation of the Act, and is grounds for enforcement action or for permit revocation, revocation and reissuance, or modification, or for denial of a permit renewal application.

b. It shall not be a defense for the permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the federally enforceable terms and conditions of this permit.

c. This permit may be modified, reopened, revoked, or revoked and reissued, for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or revocation, or of a notification of planned changes or anticipated noncompliance does not stay any term and condition of this permit.

d. This permit does not convey any property rights of any sort, or any exclusive privilege.

e. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon request, the permittee shall also furnish to the Director or an authorized representative of the Director, copies of records required to be kept by this permit. For information claimed to be confidential in the submittal to the Director, if the Administrator of the U.S. EPA requests such information, the permittee may furnish such records directly to the Administrator along with a claim of confidentiality.

7. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78.

8. Marketable Permit Programs

No revision of this permit is required under any approved economic incentive, marketable permits, emissions trading, and other similar programs or processes for changes that are provided for in this permit.

9. Reasonably Anticipated Operating Scenarios

The permittee is hereby authorized to make changes among operating scenarios authorized in this permit without notice to the Ohio EPA, but, contemporaneous with making a change from one operating scenario to another, the permittee must record in a log at the permitted facility the scenario under which the permittee is operating. The permit shield provided in these general terms and conditions shall apply to all operating scenarios authorized in this permit.

10. Reopening for Cause

This Title V permit will be reopened prior to its expiration date under the following conditions:

a. Additional applicable requirements under the Act become applicable to one or more emissions units covered by this permit, and this permit has a remaining term of three or more years. Such a reopening shall be completed not later than eighteen months after promulgation of the applicable requirement. No such reopening is required if the effective date of the requirement is later than the date on which the permit is due to expire, unless the original permit or any of its terms and conditions has been extended pursuant to paragraph (E)(1) of OAC rule 3745-77-08.

b. This permit is issued to an affected source under the acid rain program and additional requirements (including excess emissions requirements) become applicable. Upon approval by the Administrator, excess emissions offset plans shall be deemed to be incorporated into the permit, and shall not require a reopening of this permit.

c. The Director of the Ohio EPA or the Administrator of the U.S. EPA determines that the federally applicable requirements in this permit are based on a material mistake, or that inaccurate statements were made in establishing the emissions standards or other terms and conditions of this permit related to such federally applicable requirements.

d. The Administrator of the U.S. EPA or the Director of the Ohio EPA determines that this permit must be revised or revoked to assure compliance with the applicable requirements.

11. Federal and State Enforceability

Only those terms and conditions designated in this permit as federally enforceable, that are required under the Act, or any of its applicable requirements, including relevant provisions designed to limit the potential to emit of a source, are enforceable by the Administrator of the U.S. EPA, the State, and citizens under the Act. All other terms and conditions of this permit shall not be federally enforceable and shall be enforceable under State law only.

12. Compliance Requirements

a. Any document (including reports) required to be submitted and required by a federally applicable requirement in this Title V permit shall include a certification by a responsible official that, based on information and belief formed after reasonable inquiry, the statements in the document are true, accurate, and complete.

b. Upon presentation of credentials and other documents as may be required by law, the permittee shall allow the Director of the Ohio EPA or an authorized representative of the Director to:

i. At reasonable times, enter upon the permittee's premises where a source is located or the emissions-related activity is conducted, or where records must be kept under the conditions of this permit.
ii. Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit, subject to the protection from disclosure to the public of confidential information consistent with paragraph (E) of OAC rule 3745-77-03.
iii. Inspect at reasonable times any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit.
iv. As authorized by the Act, sample or monitor at reasonable times substances or parameters for the purpose of assuring compliance with the permit and applicable requirements.

c. The permittee shall submit progress reports to the appropriate Ohio EPA District Office or local air agency concerning any schedule of compliance for meeting an applicable requirement. Progress reports shall be submitted semiannually, or more frequently if specified in the applicable requirement or by the Director of the Ohio EPA. Progress reports shall contain the following:

i. Dates for achieving the activities, milestones, or compliance required in any schedule of compliance, and dates when such activities, milestones, or compliance were achieved.
ii. An explanation of why any dates in any schedule of compliance were not or will not be met, and any preventive or corrective measures adopted.

d. Compliance certifications concerning the terms and conditions contained in this permit that are federally enforceable emission limitations, standards, or work practices, shall be submitted to the appropriate Ohio EPA District Office or local air agency in the following manner and with the following content:

i. Compliance certifications shall be submitted annually on a calendar year basis. The annual certification shall be submitted on or before April 30th of each year during the permit term.
ii. Compliance certifications shall include the following:

(a) An identification of each term or condition of this permit that is the basis of the certification.
(b) The permittee's current compliance status.
(c) Whether compliance was continuous or intermittent.
(d) The method(s) used for determining the compliance status of the source currently and over the required reporting period.
(e) Such other facts as the Director of the Ohio EPA may require in the permit to determine the compliance status of the source.

iii. Compliance certifications shall contain such additional requirements as may be specified pursuant to sections 114(a)(3) and 504(b) of the Act.

13. Permit Shield

a. Compliance with the terms and conditions of this permit (including terms and conditions established for alternate operating scenarios, emissions trading, and emissions averaging, but excluding terms and conditions for which the permit shield is expressly prohibited under OAC rule 3745-77-07) shall be deemed compliance with the applicable requirements identified and addressed in this permit as of the date of permit issuance.

b. This permit shield provision shall apply to any requirement identified in this permit pursuant to OAC rule 3745-77-07(F)(2), as a requirement that does not apply to the source or to one or more emissions units within the source.

14. Operational Flexibility

The permittee is authorized to make the changes identified in OAC rule 3745-77-07(H)(1)(a) to (H)(1)(c) within the permitted stationary source without obtaining a permit revision, if such change is not a modification under any provision of Title I of the Act [as defined in OAC rule 3745-77-01(JJ)], and does not result in an exceedance of the emissions allowed under this permit (whether expressed therein as a rate of emissions or in terms of total emissions), and the permittee provides the Administrator of the U.S. EPA and the appropriate Ohio EPA District Office or local air agency with written notification within a minimum of seven days in advance of the proposed changes, unless the change is associated with, or in response to, emergency conditions. If less than seven days notice is provided because of a need to respond more quickly to such emergency conditions, the permittee shall provide notice to the Administrator of the U.S. EPA and the appropriate District Office of the Ohio

EPA or local air agency as soon as possible after learning of the need to make the change. The notification shall contain the items required under OAC rule 3745-77-07(H)(2)(d).

15. Emergencies

The permittee shall have an affirmative defense of emergency to an action brought for noncompliance with technology-based emission limitations if the conditions of OAC rule 3745-77-07(G)(3) are met. This emergency defense provision is in addition to any emergency or upset provision contained in any applicable requirement.

16. Off Permit Changes

The owner or operator of a Title V source may make any change in its operations or emissions at the source that is not specifically addressed or prohibited in the Title V permit, without obtaining an amendment or modification of the permit, provided that the following conditions are met:

a. The change does not result in conditions that violate any applicable requirements or that violate any existing federally enforceable permit term or condition;

b. The permittee provides contemporaneous written notice of the change to the director and the administrator, except that no such notice shall be required for changes that qualify as insignificant emission levels or activities as defined in OAC rule 3745-77-01(U). Such written notice shall describe each such change, the date of such change, any change in emissions or pollutants emitted, and any federally applicable requirement that would apply as a result of the change;

c. The change shall not qualify for the permit shield under OAC rule 3745-77-07(F);

d. The permittee shall keep a record describing all changes made at the source that result in emissions of a regulated air pollutant subject to an applicable requirement, but not otherwise regulated under the permit, and the emissions resulting from those changes; and

e. The change is not subject to any applicable requirement under Title IV of the Act or is not a modification under any provision of Title I of the Act.

Paragraph (I) of rule 3745-77-07 of the Administrative Code applies only to modification or amendment of the permittee's Title V permit. The change made may require a permit to install under Chapter 3745-31 of the Administrative Code if the change constitutes a modification as defined in that Chapter. Nothing in paragraph (I) of rule 3745-77-07 of the Administrative Code shall affect any applicable obligation under Chapter 3745-31 of the Administrative Code.

(For further clarification, the permittee can refer to Engineering Guide #63 that is available in their STARSHIP software package.)

17. Compliance Method Requirements

Nothing in this permit shall alter or affect the ability of any person to establish compliance with, or a violation of, any applicable requirement through the use of credible evidence to the extent authorized by law. Nothing in this permit shall be construed to waive any

defenses otherwise available to the permittee, including but not limited to, any challenge to the Credible Evidence Rule (see 62 Fed. Reg. 8314, Feb. 24, 1997), in the context of any future proceeding.

B. State Only Enforceable Section

1. Permit to Install Requirement

Prior to the "installation" or "modification" of any "air contaminant source," as those terms are defined in OAC rule 3745-31-01, a permit to install must be obtained from the Ohio EPA pursuant to OAC Chapter 3745-31.

2. Reporting Requirements Related to Monitoring and Recordkeeping Requirements

The permittee shall submit required reports in the following manner:

a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.

b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

5. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

6. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

7. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

8. Additional Reporting Requirements When There Are No Deviations of <u>Federally Enforceable</u> Emission Limitations, Operational Restrictions, or Control Device Operating Parameter Limitations (See Section A of This Permit)

If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters.

Part II - Specific Facility Terms and Conditions

A. State and Federally Enforcable Section

None

B. State Only Enforceable Section

1. The following insignificant emissions units are located at this facility:

Z001 - 10,000-gallon Leachate Storage Tank

Z002 - 10,000-gallon Diesel Storage Tank

Z003 - 8.0 HP Emergency Generator

Z004 - 2.5 HP Emergency Generator

Z005 - 35 HP Emergency Water Pump

Z006 - 290 HP Emergency Water Pump

Z007 - Part Washer

Z008 - Parts Washer

Z009 - 2,000 gallon Waste Oil Tank

Each insignificant emissions unit at this facility must comply with all applicable State and federal regulations, as well as any emission limitations and/or control requirements contained within a Permit to Install for the emissions unit.

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Roads and Parking (F001)

Activity Description: Fugitive Dust: Access roads and parking lots for daily operations and contruction activities. Locations change as needed. 7.3 acres.

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/ Requirements	Applicable Emissions Limitations/Control Measures
Landfill roadways and parking areas	OAC rule 3745-17-08	This rule does not apply, per OAC 3745-17-08(A)(1).
	OAC rule 3745-17-07	This rule does not apply, per OAC 3745-17-07 (B)(11).

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/ Requirements	Applicable Emissions Limitations/Control Measures
Landfill roadways and parking areas	OAC rule 3745-31-05 PTI 02-6705	See Section B.I.2. There shall be no visible particulate emissions from any paved roadway or parking area except for a period of time not to exceed one minute during any 60-minute observation period. There shall be no visible particulate emissions from any unpaved roadway or parking area except for a period of time not to exceed three minutes during any 60-minute observation period.

2. Additional Terms and Conditions

2.a The paved roadways and parking areas that are covered by this permit and subject to the requirements of OAC rule 3745-31-05 are listed below:

Paved Roadways:

All landfill paved roadways

Paved Parking Areas:

All landfill paved parking areas

2.b The unpaved roadways and parking areas that are covered by this permit and subject to the requirements of OAC rule 3745-31-05 are listed below:

Unpaved Roadways:

All landfill unpaved roadways

Unpaved Parking Areas:

All landfill unpaved parking areas

2.c The permittee shall employ best available control measures on all paved roadways and paved parking areas for the purpose of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee's permit application, the permittee has committed to treat the paved roadways and parking areas by establishing and enforcing 10 mph speed zones and/or sweeping at sufficient treatment frequencies to ensure compliance. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.

2. Additional Terms and Conditions (continued)

2.d The permittee shall promptly remove, in such a manner as to minimize or prevent resuspension, earth and/or other material from paved streets onto which such material has been deposited by trucking or earth moving equipment or erosion by water or other means.

2.e The permittee shall employ best available control measures on all unpaved roadways and parking areas for the purpose of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee's permit application, the permittee has committed to treat the unpaved roadways and parking areas by watering at sufficient treatment frequencies and resurfacing as needed to ensure compliance. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.

2.f The needed frequencies of implementation of the control measures shall be determined by the permittee's inspections pursuant to the monitoring section of this permit. Implementation of the control measures shall not be necessary for a paved roadway or unpaved roadway or parking area that is covered with snow and/or ice or if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements. Implementation of any control measure may be suspended if unsafe or hazardous driving conditions would be created by its use.

2.g Any unpaved roadway or parking area, which during the term of this permit is paved or takes the characteristics of a paved surface due to the application of certain types of dust suppressants, may be controlled with the control measure(s) specified above for the paved surfaces. Any unpaved roadway or parking area that takes the characteristics of a paved roadway or parking area due to the application of certain types of dust suppressants shall remain subject to the visible emission limitation for unpaved roadways and parking areas. Any unpaved roadway or parking areas that is paved shall be subject to the visible emission limitation for paved roadways and parking areas.

2.h Open-bodied vehicles transporting materials likely to become airborne shall have such materials covered at all times if the control measure is necessary for the materials being transported.

II. Operational Restrictions

1. Brine shall not be used as a dust suppressant unless written permission is obtained from the Ohio EPA.

2. Waste oil shall not be used as a dust suppressant.

III. Monitoring and/or Record Keeping Requirements

1. Except as otherwise provided in this section, the permittee shall perform inspections of the roadways and parking areas in accordance with the following frequencies:

roadway and/or parking area	minimum inspection frequency
paved roadways and parking areas	daily
unpaved roadways and parking areas	daily

2. The purpose of the inspections is to determine the need for implementing the above-mentioned control measures. The inspections shall be performed during representative, normal traffic conditions. No inspection shall be necessary for a roadway or parking area that is covered with snow and/or ice if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements. Any required inspection that is not performed due to any of the above-identified events shall be performed as soon as such event(s) has (have) ended, except if the next required inspection is within one week.

3. The permittee may, upon receipt of written approval from the Northeast District Office of the Ohio EPA, modify the above-mentioned inspection frequencies if operating experience indicates that less frequent inspections would be sufficient to ensure compliance with the above-mentioned applicable requirements. Such modified inspection frequencies would not be considered a minor or significant modification that would be subject to the Title V permit modification requirements in paragraphs (C)(1) and (C)(3) of OAC rule 3745-77-08.

III. Monitoring and/or Record Keeping Requirements (continued)

4. The permittee shall maintain records of the following information:

a. the date and reason any required inspection was not performed, including those inspections that were not performed due to snow and/or ice cover or precipitation;

b. the date of each inspection where it was determined by the permittee that it was necessary to implement the control measures;

c. the dates the control measures were implemented; and

d. on a calendar quarter basis, the total number of days the control measures were implemented and the total number of days where snow and/or ice cover or precipitation were sufficient to not require the control measures.

The information required in 4.d. shall be kept separately for (i) the paved roadways and parking areas and (ii) the unpaved roadways and parking areas, and shall be updated on a calendar quarter basis within 30 days after the end of each calendar quarter.

IV. Reporting Requirements

1. The permittee shall submit deviation reports that identify any of the following occurrences:

a. each day during which an inspection was not performed by the required frequency, excluding an inspection which was not performed due to an exemption for snow and/or ice cover or precipitation; and

b. each instance when a control measure, that was to be implemented as a result of an inspection, was not implemented.

2. The deviation reports shall be submitted in accordance with the reporting requirements of the General Terms and Conditions of this permit.

V. Testing Requirements

1. Compliance with the visible emissions limitation for the unpaved roadways and unpaved parking areas identified above shall be determined in accordance with Test Method 22 as set forth in Appendix on Test Methods in 40 CFR, Part 60 (Standards of Performance for New Stationary Sources), as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(4)(a) through (B)(4)(c) of OAC rule 3745-17-03.

2. Compliance with the visible emissions limitation for the paved roadways and paved parking areas identified above shall be determined in accordance with Test Method 22 as set forth in Appendix on Test Methods in 40 CFR, Part 60 (Standards of Performance for New Stationary Sources), as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(4)(a) through (B)(4)(c) of OAC rule 3745-17-03.

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Operations (F002)

Activity Description: Fugitive Dust and Methane Gas: Daily waste placement and daily covering operations

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/ Requirements	Applicable Emissions Limitations/Control Measures
Load-in of municipal solid waste (MSW) at a MSW landfill	OAC rule 3745-17-08	This rule does not apply, per OAC 3745-17-08 (A)(1).
	OAC rule 3745-17-07	This rule does not apply, per OAC 3745-17-07 (B)(11).
Capture and control of non-methane organic compounds (NMOC)	40 CFR Part 60, Subpart WWW	See sections A.I.2.a through A.V below.

2. Additional Terms and Conditions

2.a If an active gas collection system is employed, the following requirements shall be satisfied, as specified in 40 CFR Part 60.752(b)(2)(ii)(A):

i. The system shall be designed to handle the maximum expected gas flow rate from the entire area of the landfill that warrents control over the intended use period of the gas control or treatment system equipment.

ii. The system shall collect gas from each area, cell, or group of cells in the landfill in which the initial solid waste has been placed for a period of 5 years or more if active, or 2 years or more if closed or at final grade.

iii. The system shall collect gas at a sufficient extraction rate.

iv. The system shall be designed to minimize off-site migration of subsurface gas.

2. Additional Terms and Conditions (continued)

2.b If the collected gas is to be vented to an open flare, the open flare shall be designed and operated as follows:

i. The flare shall be designed for and operated with no visible emissions, except for periods not to exceed a total of 5 minutes during any 2 consecutive hours.

ii. The flare shall be operated with a flame present at all times.

iii. The permittee shall comply with either the requirements in paragraph (a) and (b) or the requirements in paragraph (c):

(a) Flares shall be used only with the net heating value of the gas being combusted being 11.2 MJ/scm (300 Btu/scf) or greater if steam-assisted or air-assisted; or with the net heating value of the gas being combusted being 7.45 MJ/scm (200 Btu/scf) or greater if the flare is nonassisted. The net heating value of the gas being combusted shall be determined as follows:

Ht = k x (the summation of Ci Hi for i=1 through i=n)
Where,
Ht = net heating value of the sample, MJ/scm; where the net enthalpy per mole of off gas is based on combustion at 25 degrees C and 760 mm Hg, but the standard temperature for determining the volume corresponding to one mole is 20 degrees C;

k = constant, 1.740 x 10-7 (1/ppm) (g mole/scm) (MJ/kcal) where the standard temperature for (g mole/scm) is 20 degrees C.

Ci = concentration of sample component i in ppm on a wet basis, as measured for organics by Reference Method 18 and measured for hydrogen and carbon monoxide by ASTM D1946-77; and

Hi = net heat of combustion of sample component i, kcal/g mole at 25 degrees C and 760 mm Hg. The heats of combustion may be determined using ASTM D2382-76 (incorporated by reference as specified in section 60.17) if published values are not available or cannot be calculated.

2. Additional Terms and Conditions (continued)

(b) A steam-assisted and nonassisted flare shall be designed for and operated with an exit velocity of less than 18.3 m/sec. (60 ft/sec), except:

(i) steam-assisted and nonassisted flare shall be designed for and operated with an exit velocity of equal to or greater than 18.3 m/sec, but less than 122 m/sec (400 ft/sec) are allowed if the net heating value of the gas being combusted is greater than 37.3 MJ/scm (1,000 Btu/scf); and

(ii) steam-assisted and nonassisted flare shall be designed for and operated with an exit velocity of less than the velocity, Vmax, and less than 122 m/sec (400 ft/sec) are allowed; as determined by

Log10(Vmax) = (Ht + 28.8)/31.7
where
Vmax = maximum permitted velocity, m/sec
28.8 = constant
31.7 = constant
Ht = the net heating value as determined in section A.I.2.b.iii.a. above

(c) Flares shall be used that have a diameter of 3 inches or greater, are nonassisted, have a hydrogen content of 8.0 percent (by volume), or greater, and are designed for and operated with an exit velocity less than 37.2 m/sec (122 ft/sec) and less than the velocity, Vmax, as determined by the following equation:

Vmax = (Xh2 - K1) * K2
where:
Vmax = maximum permitted velocity, m/sec
K1 = constant, 6.0 volume-percent hydrogen
K2 = constant, 3.9 (m/sec)/volume-percent hydrogen
Xh2 = the volume-percent of hydrogen, on a wet basis, as calculated by using the American Society for Testing and Materials (ASTM) Method D1946-77.

iv. Air-assisted flare shall be designed for and operated with an exit velocity of less than the velocity, Vmax, as determined by the following equation:

Vmax = 8.706 + 0.7084 (Ht)
where
Vmax = maximum permitted velocity, m/sec
8.706 = constant
0.7084 = constant
Ht = the net heating value as determined in section A.I.2.b.iii.a. above

2.c If an active gas collection system is employed, the collection and control system may be capped or removed provided that all of the following conditions, as specified in 40 CFR Part 60.752(b)(2)(v), are met:

i. The landfill shall be no longer accepting solid waste and be permanently closed (pursuant to 40 CFR Part 258.60).

ii. The collection and control system shall have been in operation a minimum of 15 years.

iii. The calculated NMOC gas produced by the landfill shall be less than 55 TPY on three successive test dates. The test dates shall be no less than 90 days apart, and no more than 180 days apart.

II. Operational Restrictions

1. The permittee shall not accept or dispose of any friable asbestos or friable asbestos-containing materials. The receipt of any friable asbestos or friable asbestos-containing waste without proper approval of the Ohio EPA is a violation of the NESHAP for Asbestos (40 CFR Part 61, Subpart M) and OAC Chapter 3745-31.

II. Operational Restrictions (continued)

2. If the landfill is active or still accepting waste, the permittee shall operate the collection system such that gas is collected from each area, cell, or group of cells in the MSW landfill in which solid waste has been in place for 5 years or more. If the landfill is closed or at final grade, the permittee shall operate the collection system such that gas is collected from each area, cell, or group of cells in the MSW landfill in which solid waste has been in place for 2 years or more.

3. If an active collection system is employed, the permittee shall operate the collection system with negative pressure at each wellhead except under the following conditions:

a. A fire or increased well temperature. (The permittee shall record instances when positive pressure occurs in efforts to avoid a fire.)

b. Use of a geomembrane or synthetic cover. (The permittee shall develop acceptable pressure limits in the design plan.)

c. A decommissioned well. (A well may experience a static positive pressure after shutdown to accommodate for declining flows. All design changes shall be approved by the Director of Ohio EPA.)

4. If an active collection system is employed, the permittee shall operate each interior wellhead in the collection system with a landfill gas temperature less than 55 degrees Celsius and with either a nitrogen level less than 20% or an oxygen level less than 5%. The permittee may establish a higher operating temperature, nitrogen, or oxygen value at a particular well. A higher operating value demonstration shall show supporting data that the elevated parameter does not cause fires or significantly inhibit anaerobic decomposition by killing methanogens.

5. The permittee shall operate the collection system so that the membrane concentration is less than 500 parts per million above background at the surface of the landfill.

6. If an active collection system is employed, the permittee shall operate the collection system such that all collected gases are vented to a control system designed and operated in compliance with A.I.2. In the event the collection or control system is inoperable, the gas mover system shall be shut down and all valves in the collection and control system contributing to venting of the gas to the atmosphere shall be closed within one hour.

7. If an active collection system and open flare control system are employed, the permittee shall operate the flare at all times when the collected gas is routed to the system.

8. If an active collection system and open flare control system are employed, a pilot flame shall be maintained at all times in the flare's pilot light burner.

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall maintain records of the annual NMOC emission rate. These records shall be maintained until the landfill is closed, and shall be made available for review by the Director or his/her representative during normal business hours.

2. If an active gas collection system is employed, the permittee shall install a sampling port and a thermometer or other temperature measuring device at each wellhead and record the following information on a monthly basis:

a. the gauge pressure in the gas collection header at each individual well;

b. the nitrogen or oxygen concentration in the landfill gas; and

c. the temperature of the landfill gas.

III. Monitoring and/or Record Keeping Requirements (continued)

3. The permittee shall monitor surface concentrations of methane on a quarterly basis, if an active gas collection system is employed, as follows:

a. Monitor surface concentrations of methane along the entire perimeter of the collection area and along a serpentine pattern spaced 30 meters apart (or a site-specific established spacing) for each collection area.

b. The background concentration shall be determined by moving the probe inlet upwind and downwind outside the boundary of the landfill at a distance of at least 30 meters from the perimeter wells.

c. Surface emission monitoring shall be performed in accordance with section 4.3.1 of Method 21 of Appendix A of 40 CFR Part 60, except that the probe inlet shall be placed within 5 to 10 centimeters off the ground. Monitoring shall be performed during typical meteorological conditions.

d. Any reading of 500 parts per million or more above background at any location shall be recorded as a monitored exceedance and the actions specified below shall be taken. As long as the specified actions are taken, the exceedance is not a violation of the operational requirements listed in A.II.5.:

i. The location of each monitored exceedance shall be marked and the location recorded.

ii. Cover maintenance or adjustments to the vacuum of the adjacent wells to increase the gas collection in the vicinity of each exceedance shall be made and the location shall be remonitored within 10 calendar days of detecting the exceedance.

iii. If the remonitoring of the location shows a second exceedance, additional corrective action shall be taken and the location shall be monitored again within 10 days of the second exceedance. If the remonitoring shows a third exceedance for the same location, a new well or other collection device shall be installed within 120 calendar days of the initial exceedance.

An alternative remedy to the exceedance, such as upgrading the blower, header pipes or control device , and a corresponding timeline for installation may be submitted to the Ohio EPA for approval. No further monitoring of that location is required until the action specified has been taken.

iv. Any location that initially showed an exceedance but has a methane concentration less than 500 ppm methane above background at the 10-day remonitoring specified above shall be remonitored 1 month from the initial exceedance. If the 1-month remonitoring shows a concentration less than 500 parts per million above background, no further monitoring of that location is required until the next quarterly monitoring period. If the 1- month remonitoring shows an exceedance, the actions specified above shall be taken.

4. If an active gas collection system is employed and an open flare is employed for control, the permittee shall install, calibrate, maintain, and operate according to the manufacturer's specifications the following equipment:

a. a heat sensing device, such as an ultraviolet beam sensor or thermocouple, at the pilot light or the flame itself to indicate the continuous presence of a flame; and

b. a gas flow rate measuring device that shall record the flow to the control device at least every 15 minutes.

5. For an active gas collection system, if a gas flow rate measuring device is not installed then the permittee shall secure the bypass line valve in the closed position with a car-seal or a lock-and-key configuration. A visual inspection of the seal or closure mechanism shall be performed at least once every month to ensure that the valve is maintained in the closed position and that the gas flow is not diverted through the bypass line.

III. Monitoring and/or Record Keeping Requirements (continued)

6. The permittee shall maintain the following information for the life of the control equipment as measured during the initial performance test or compliance demonstration:

a. The maximum expected gas generation flow rate as calculated based on the following:

i. For sites with unknown year-to-year solid waste acceptance rate:

Qm = 2Lo x R x {(e to the power -kc) - (e to the power -kt)}
where,
Qm = maximum expected gas generation flow rate, cubic meters per year
Lo = methane generation potential, cubic meters per megagram solid waste
R = average annual acceptance rate, megagrams per year
k = methane generation rate constant, per year
t = age of the landfill at equipment installation plus the time the owner or operator intends to use the gas mover equipment or active life of the landfill, whichever is less (If the equipment is installed after closure, t is the age of the landfill at installation), years
c = time since closure, years (for an active landfill c = 0 and (e to the power -kc) = 1)

ii. For sites with known year-to-year solid waste acceptance rate:

Qm = Summation of 2kLoMi x (e to the power -kti for i=1 through i=n)
where,
Qm = maximum expected gas generation flow rate, cubic meters per year
k = methane generation rate constant, per year
Lo = methane generation potential, cubic meters per megagram solid waste
Mi = mass of solid waste in the i th section, megagrams
ti = age of the i th section, years

iii. If a collection and control system has been installed, actual flow data may be used to project the maximum expected gas generation flow rate instead of, or in conjunction with, the equations in paragraph A.III.5.i. and ii. If the landfill is still accepting waste, the actual measured flow data will not equal the maximum expected gas generation rate, so calculations using the equations in paragraphs A.III.5.a.i. or ii. or other methods shall be used to predict the maximum expected gas generation rate over the intended period of use of the gas control system equipment. (The permittee may use another method to determine the maximum gas generation flow rate, if the method has been approved by the Ohio EPA.);

b. the density of wells, horizontal collectors, surface collectors, or other gas extraction devices determined using the procedures specified in 40 CFR Part 60.759(a)(1);

c. the flare type (i.e., steam-assisted, air-assisted, or non-assisted);

d. all visible emission readings;

e. heat content determinations of the gas;

f. flow rate or bypass flow rate measurements;

g. exit velocity determinations made during the performance test as specified in 40 CFR Part 60.18; and

h. continuous records of the flare pilot flame or flame monitoring and records of all periods of operations during which the flare pilot flame or flare flame is absent.

III. Monitoring and/or Record Keeping Requirements (continued)

7. If an open flare control sytem is employed the pemittee shall properly install, operate, and maintain a device to continuously monitor the flare pilot flame when the emissions unit is in operation. The monitoring device and any recorder shall be installed, calibrated, operated and maintained in accordance with the manufacturer's recommendations, instructions and operating manuals.

The permittee shall record the following information each day:

a. all periods during which there was no pilot flame;

b. the downtime for the flare and monitoring equipment when the collection and control system is in operation.

8. The permittee shall maintain, for the life of the collection system, an up-to-date, readily accessible plot map showing each existing and planned collector in the system and providing a unique identification location label for each collector.

9. The permittee shall keep for at least 5 years up-to-date, readily accessible, on-site records of the maximum design capacity of the landfill, the current amount of solid waste in-place, and the year-to-year waste acceptance rate. Off-site records may be maintained if they are retrievable within 4 hours. Either hardcopy or electronic formats are acceptable. These records, may be also required by the Ohio EPA, Division of Solid and Infectious Waste Management, and shall satisfy this permit condition.

10. The permittee shall conduct surface testing around the perimeter of the collection area along a pattern that traverses the landfill at 30-meter intervals and where visual observations indicate elevated concentrations of landfill gas, such as distressed vegetation and cracks or seeps in the cover.

IV. Reporting Requirements

1. By September 11, 1999, the permittee shall submit a collection and control design plan in accordance with 40 CFR 60.752(b)(2)(i) to the Northeast District Office of the Ohio EPA.

2. Within 18 months of the design plan submittal, a collection and control system shall be installed, in accordance with 40 CFR 60.752(b)(2)(ii).

3. Any breakdown or malfunction of the landfill gas collection and control system resulting in the emission of raw landfill gas emissions to the atmosphere shall be reported to the Northeast District Office of the Ohio EPA within one hour after the occurrence, or as soon as reasonably possible, and immediate remedial measures shall be undertaken to correct the problem and prevent further emissions to the atmosphere.

4. The permittee shall submit an NMOC annual emission rate report to the Northeast District Office of the Ohio EPA. The report shall include all the data, calculations, sample reports and measurements used to estimate the annual emissions.

5. The permittee shall submit a closure report to the Northeast District Office of the Ohio EPA within 30 days of waste acceptance cessation. The Ohio EPA may request additional information as may be necessary to verify that permanent closure has taken place in accordance with the requirements of 40 CFR Part 258.60. If a closure report has been submitted to the Ohio EPA, no additional wastes may be placed into the landfill without filing a notification of modification as described in 40 CFR Part 60.7(a)(4).

6. The permittee shall submit an equipment removal report to the Northeast District Office of the Ohio EPA 30 days prior to removal or cessation of operation of the control equipment. The equipment removal report shall contain the information specified in 40 CFR Part 60.757(e)(1). The Ohio EPA may request additional information as may be necessary to verify that all of the conditions for removal in 40 CFR Part 60.752(b)(2)(v) have been met.

IV. Reporting Requirements (continued)

7. If an active collection system is employed, the permittee shall submit deviation reports that identify any of the following occurrences:

a. any record which indicates that the gauge pressure in the gas collection header at each individual well was positive;

b. any record which indicates that the nitrogen or oxygen concentration in the landfill was greater than 20% or 5%, respectively;

c. any record which indicates that the temperature of the landfill gas was greater than 55 degrees Celsius;

d. any record which indicates that the surface concentration of methane was greater than 500 parts per million above background;

e. all periods during which the flare pilot flame was not functioning properly (the reports shall include the date, time, and duration of each such period); and

f. all periods when the gas stream is diverted from the control device through a bypass line or the indication of bypass flow or any record which indicates that the bypass line valve was not maintained in the closed position.

The deviation reports shall be submitted in accordance with the reporting requirements of the General Terms and Conditions of this permit.

8. The permittee shall submit annual reports which include the following:

a. all periods when the collection system was not operating in excess of 5 days; and

b. any record indicating the date of installation and the location of each well or collection system expansion added pursuant to 40 CFR 60.755(a)(3), (b), and (c)(4).

These reports shall be submitted by January 31 of each year.

9. If an active collection and control system are employed, the permittee shall submit the following information with the initial performance test report required pursuant to 40 CFR Part 60.8:

a. a diagram of the collection system showing collection system positioning including all wells, horizontal collectors, surface collectors, or other gas extraction devices, including the locations of any areas excluded from collection and the proposed sites for the future collection system expansion;

b. the data upon which the sufficient density of wells, horizontal collectors, surface collectors, or other gas extraction devices and the gas mover equipment sizing are based;

c. the documentation of the presence of asbestos or nondegradable material for each area from which collection wells have been excluded based on the presence of asbestos or nondegradable material;

d. the sum of the gas generation flow rate for all areas from which collection wells have been excluded based on nonproductivity and the calculations of gas generation flow rate for each excluded area;

e. the provisions for increasing gas mover equipment capacity with increased gas generation flow rate, if the present gas mover equipment is inadequate to move the maximum flow rate expected over the life of the landfill; and

f. the provisions for the control of off-site migration.

V. Testing Requirements

1. The NMOC emissions described in these terms and conditions shall be determined as specified in 40 CFR 60.754.

V. Testing Requirements (continued)

2. Emission Limitation: No visible emissions from the flare, except for periods not to exceed a total of 5 minutes during any 2 consecutive hours.

Applicable Compliance Method: Compliance shall be demonstrated through visible emission observations performed in accordance with 40 CFR Part 60, Appendix A, Method 22, and procedures specified in 40 CFR Part 60.18.

3. The nitrogen level shall be determined using Method 3C of 40 CFR Part 60, Appendix A, unless an alternative test method is established as allowed by 40 CFR Part 60.752(b)(2)(i).

4. The oxygen level shall be determined by an oxygen meter using Method 3A of 40 CFR Part 60, Appendix A, unless an alternative test method is established as allowed by 40 CFR Part 60.752(b)(2)(i), except that:

a. the span shall be set so that the regulatory limit is between 20% and 50% of the span;

b. a data recorder is not required;

c. only two calibration gases are required, a zero and span, and ambient air may be used as the span;

d. a calibration error check is not required; and

e. the allowable sample bias, zero drift, and calibration drift are plus or minus 10%.

5. The permittee shall conduct or have conducted, within 90 days after the installation of the collection and control system, an initial performance test to demonstrate that the flare can operate in conformance with the requirements specified in 40 CFR Part 60.18. The net heating value of the gas being combusted in the flare and the actual exit velocity of the flare shall be determined in accordance with the procedures and methods specified in 40 CFR Part 60.18. The visible emission evaluation shall be conducted in accordance with the procedures specified in Section A.V.2.

6. After the installation of a collection and control system in compliance with 40 CFR Part 60.755, the permittee shall calculate the NMOC emission rate for the purposes of determining when the system can be removed as provided in 40 CFR Part 60.752(b)(2)(v) in accordance with the equation and procedures specified in 40 CFR Part 60.754(b), (b)(1), and (b)(2). The permittee may use another method to determine landfill gas flow rate and NMOC concentration if the method has been approved by the Ohio EPA as provided in 40 CFR Part 60.752(b)(2)(i)(B).

VI. Miscellaneous Requirements

1. Authority to Enter

Pursuant to the authority in OAC rule 3745-77-07(C)(2) or ORC 3704.03(L), any representative of the Director may, upon presentation of proper identification, enter at any reasonable time upon any portion of the property where this landfill is located, including any improvements thereon, to make inspections, take samples, conduct tests and examine records or reports pertaining to any emissions of air contaminants and any monitoring equipment, emissions control equipment or methods. No operator or agent of this landfill shall act in any manner to refuse, hinder, or thwart this legal right of entry.

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/ Requirements	Applicable Emissions Limitations/Control Measures
Load-in of municipal solid waste (MSW) at a MSW landfill	OAC rule 3745-31-05 PTI 02-6705	best available control measures that are sufficient to minimize or eliminate visible emissions of fugitive dust.

2. Additional Terms and Conditions

2.a The landfill areas that are covered by this permit and subject to the requirements of OAC rule 3745-31-05 are listed below:

entire landfill surface area

2.b The permittee shall employ best available control measures for the load-in of solid wastes. All truckloads of solid waste shall be unloaded in a manner which will minimize the drop height of the solid wastes. Any dusty materials or wastes likely to become airborne shall be watered as necessary prior to or during dumping. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.

2.c The above-mentioned control measures shall be employed for each load-in of solid waste if the permittee determines, as a result of the inspection conducted pursuant to the monitoring section of this permit, that the control measures are necessary to ensure compliance with the above-mentioned applicable requirements. Any required implementation of the control measures shall continue during any such operation until further observation confirms that use of the measures is unnecessary.

II. Operational Restrictions

1. There shall be no open burning, in violation of OAC Chapter 3745-19, at this facility.

III. Monitoring and/or Record Keeping Requirements

1. Except as otherwise provided in this section, the permittee shall perform inspections of the landfill operation areas in accordance with the following frequencies:

landfill areas	minimum inspection frequency
entire landfill surface area	daily

2. The purpose of the inspections is to determine the need for implementing the above-mentioned control measures. The inspections shall be performed during representative, normal operating conditions. No inspection shall be necessary for an operating area that is covered with snow and/or ice or if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements. Any required inspection that is not performed due to any of the above-identified events shall be performed as soon as such event(s) has (have) ended, except if the next required inspection is within one week.

III. Monitoring and/or Record Keeping Requirements (continued)

3. The permittee may, upon receipt of written approval from the Northeast District Office of the Ohio EPA, modify the above-mentioned inspection frequencies if operating experience indicates that less frequent inspections would be sufficient to ensure compliance with the above-mentioned applicable requirements. Such modified inspection frequencies would not be considered a minor or significant modification that would be subject to the Title V permit modification requirements in paragraphs (C)(1) and (C)(3) of OAC rule 3745-77-08.

4. The permittee shall maintain records of the following information:

a. the date and reason any required inspection was not performed, including those inspections that were not performed due to snow and/or ice cover or precipitation;

b. the date of each inspection where it was determined by the permittee that it was necessary to implement the control measures;

c. the dates the control measures were implemented; and

d. on a calendar quarter basis, the total number of days the control measures were implemented and the total number of days where snow and/or ice cover or precipitation were sufficient to not require the control measures.

The information shall be kept updated on a calendar quarter basis within 30 days after the end of each calendar quarter.

IV. Reporting Requirements

1. The permittee shall submit deviation reports that identify any of the following occurrences:

a. each day during which an inspection was not performed by the required frequency, excluding an inspection which was not performed due to an exemption for snow and/or ice cover or precipitation; and

b. each instance when a control measure, that was to be implemented as a result of an inspection, was not implemented.

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Storage Piles & Material Handling (F003)

Activity Description: Storage piles & material handling for covering and capping operations

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/ Requirements	Applicable Emissions Limitations/Control Measures
Soil storage piles	OAC rule 3745-17-08(B)	This rule does not apply, per OAC 3745-17-08(A)(1).
	OAC rule 3745-17-07(B)	This rule does not apply, per OAC 3745-17-07(B)(11)(e).

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/ Requirements	Applicable Emissions Limitations/Control Measures
Soil storage piles: Load-in, load-out and wind erosion	OAC rule 3745-31-05 PTI 02-12888	No visible emissions except for a period of time not to exceed one minute during any sixty-minute observation. 6.74 tons of particulate matter per year.

2. Additional Terms and Conditions

2.a The storage piles that are covered by this permit and subject to the requirements of OAC rule 3745-31-05 are listed below:

All storage piles

2.b The permittee shall employ best available control measures on all load-in and load-out operations associated with the storage piles for the purpose of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee's permit application, the permittee has committed to process material with an inherently high moisture content, minimize drop heights, and, if necessary, apply additional water. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.

2.c The above-mentioned control measure(s) shall be employed for each load-in and load-out operation of each storage pile if the permittee determines, as a result of the inspection conducted pursuant to the monitoring section of this permit, that the control measure(s) are necessary to ensure compliance with the above-mentioned applicable requirements. Any required implementation of the control measure(s) shall continue during any such operation until further observation confirms that use of the measure(s) is unnecessary.

2.d The permittee shall employ best available control measures for wind erosion from the surfaces of all storage piles for the purpose of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee's permit application, the permittee has committed to treat each storage pile with water at a sufficient treatment frequency and/or process high moisture content material to ensure compliance. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.

2.e The above-mentioned control measure(s) shall be employed for wind erosion from each pile if the permittee determines, as a result of the inspection conducted pursuant to the monitoring section of this permit, that the control measure(s) are necessary to ensure compliance with the above-mentioned applicable requirements. Implementation of the control measure(s) shall not be necessary for a storage pile that is covered with snow and/or ice or if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements.

2.f Implementation of the above-mentioned control measures in accordance with the terms and conditions of this permit is appropriate and sufficient to satisfy the requirements of OAC rule 3745-31-05.

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

1. Except as otherwise provided in this section, the permittee shall perform inspections of each load-in and load-out operation at each storage pile in accordance with the following frequencies:

storage pile identification	minimum load-in and load-out inspection frequency
all storage piles	daily

2. Except as otherwise provided in this section, the permittee shall perform inspections of the wind erosion from pile surfaces associated with each storage pile in accordance with the following frequencies:

storage pile identification	minimum inspection frequency
all storage piles	daily

3. No inspection shall be necessary for wind erosion from the surface of a storage pile when the pile is covered with snow and/or ice and for any storage pile activity if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements. Any required inspection that is not performed due to any of the above identified events shall be performed as soon as such event(s) has (have) ended, except if the next required inspection is within one week.

4. The purpose of the inspections is to determine the need for implementing the control measures specified in this permit for load-in and load-out of a storage pile, and wind erosion from the surface of a storage pile. The inspections shall be performed during representative, normal storage pile operating conditions.

5. The permittee may, upon receipt of written approval from the Ohio EPA, Northeast District Office, modify the above-mentioned inspection frequencies if operating experience indicates that less frequent inspections would be sufficient to ensure compliance with the above-mentioned applicable requirements. Such modified inspection frequencies would not be considered a minor or significant modification that would be subject to the Title V permit modification requirements in paragraphs (C)(1) and (C)(3) of OAC rule 3745-77-08.

6. The permittee shall maintain records of the following information:

a. the date and reason any required inspection was not performed due to snow and/or ice cover or precipitation;

b. the date of each inspection where it was determined by the permittee that it was necessary to implement the control measures;

c. the dates the control measures were implemented; and,

d. on a calendar quarter basis, the total number of days the control measures were implemented and, for wind erosion from pile surfaces, the total number of days where snow and/or ice cover or precipitation were sufficient to not require the control measure(s).

The information required in 6.d. shall be kept separately for (i) the load-in operations, (ii) the load-out operations, and (iii) the pile surfaces (wind erosion), and shall be updated on a calendar quarter basis within 30 days after the end of each calendar quarter.

IV. Reporting Requirements

1. The permittee shall submit deviation reports that identify any of the following occurrences:

a. each day during which an inspection was not performed by the required frequency, excluding an inspection which was not performed due to an exemption for snow and/or ice cover or precipitation; and,

b. each instance when a control measure, that was to be implemented as a result of an inspection, was not implemented.

V. Testing Requirements

1. Compliance with the visible emissions limitation for the storage piles identified above shall be determined in accordance with Test Method 22 as set forth in Appendix on Test Methods in 40 CFR, Part 60 (Standards of Performance for New Stationary Sources), as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(4)(a) through (B)(4)(c) of OAC rule 3745-17-03.

2. Compliance with the annual mass emission rate for PM shall be determined by using the equations and methods in AP-42, section 13.2.4, "Aggregate Handling and Storage Piles" as they appeared in the January 1995 version or a more recent version.

VI. Miscellaneous Requirements

None

****

THIS IS THE LAST PAGE OF THE PERMIT

****