3745-266-107 Standards to control hydrogen chloride and chlorine gas emissions.

- (A) General. The owner or operator <u>mustshall</u> comply with the hydrogen chloride and chlorine gas controls provided by paragraph (B), (C), or (E) of this rule.
- (B) Screening limits.
  - (1) "Tier I" feed rate screening limits. Feed rate screening limits are specified for total chlorine in appendix <u>IA</u> to this rule as a function of terrain-adjusted effective stack height and terrain and land use in the vicinity of the facility. The feed rate of total chlorine and chloride, both organic and inorganic, in all feed streams, including hazardous waste, fuels, and industrial furnace feed stocks must shall not exceed the levels specified.
  - (2) "Tier II" emission rate screening limits. Emission rate screening limits for hydrogen chloride and chlorine gas are specified in appendix <u>HB</u> to this rule as a function of terrain-adjusted effective stack height and terrain and land use in the vicinity of the facility. The stack emission rates of hydrogen chloride and chlorine gas <u>mustshall</u> not exceed the levels specified.
  - (3) <u>Definitions Descriptions</u> and limitations. The <u>definitions descriptions</u> and limitations provided by paragraph (B) of rule 3745-266-106 of the Administrative Code for the following terms also apply to the screening limits provided by paragraphs (B) to (B)(4)(c) of this rule: terrain-adjusted effective stack height, good engineering practice stack height, terrain type, land use, and criteria for facilities not eligible to use the for screening limits.
  - (4) Multiple stacks. Owners and operators of facilities with more than one on-site stack from a boiler, industrial furnace, incinerator, or other thermal treatment unit subject to controls on hydrogen chloride or chlorine gas emissions under a hazardous waste facility installation and operation permit or interim standards controls <a href="mailto:mustshall">mustshall</a> comply with the "Tier I" and "Tier II" screening limits for those stacks assuming all hazardous waste is fed into the device with the worst-case stack based on dispersion characteristics.
    - (a) The worst-case stack is determined by procedures provided in paragraph (B)(6) of rule 3745-266-106 of the Administrative Code.

(b) Under "Tier I,", the total feed rate of chlorine and chloride to all subject devices mustshall not exceed the screening limit for the worst-case stack.

- (c) Under "Tier II,", the total emissions of hydrogen chloride and chlorine gas from all subject stacks mustshall not exceed the screening limit for the worst-case stack.
- (C) "Tier III" site-specific risk assessments.
  - (1) General. Conformance with the "Tier III" controls <u>mustshall</u> be demonstrated by emissions testing to determine the emission rate for hydrogen chloride and chlorine gas, air dispersion modeling to predict the maximum annual average off-site ground level concentration for each compound, and a demonstration that acceptable ambient levels are not exceeded.
  - (2) Acceptable ambient levels. Appendix <u>IA</u> to rule 3745-266-109 of the Administrative Code lists the reference air concentrations for hydrogen chloride (seven micrograms per cubic meter) and chlorine gas (0.4 micrograms per cubic meter).
  - (3) Multiple stacks. Owners and operators of facilities with more than one on-site stack from a boiler, industrial furnace, incinerator, or other thermal treatment unit subject to controls on hydrogen chloride or chlorine gas emissions under a hazardous waste facility installation and operation permit or interim standards controls mustshall conduct emissions testing and dispersion modeling to demonstrate that the aggregate emissions from all such on-site stacks do not result in an exceedance of the acceptable ambient levels for hydrogen chloride and chlorine gas.
- (D) Averaging periods. The hydrogen chloride and chlorine gas controls are implemented by limiting the feed rate of total chlorine and chloride in all feedstreams, including hazardous waste, fuels, and industrial furnace feed stocks. Under "Tier I,"; the feed rate of total chloride and chlorine is limited to the "Tier I" screening limits. Under "Tier II" and "Tier III,"; the feed rate of total chloride and chlorine is limited to the feed rates during the trial burn (for new facilities or a permit by rule facility applying for a permit) or the compliance test (for permit by rule facilities). The feed rate limits are based on either:
  - (1) An hourly rolling average as <u>defineddescribed</u> in paragraph (E)(6) of rule 3745-266-102 of the Administrative Code; or.

- (2) An instantaneous basis not to be exceeded at any time.
- (E) "Adjusted Tier I" feed rate screening limits. The owner or operator may adjust the feed rate screening limit provided by appendix <u>IA</u> to this rule to account for site-specific dispersion modeling. Under this approach, the adjusted feed rate screening limit is determined by back-calculating from the acceptable ambient level for chlorine gas provided by appendix <u>IA</u> to rule 3745-266-109 of the Administrative Code using dispersion modeling to determine the maximum allowable emission rate. This emission rate becomes the "Adjusted Tier I" feed rate screening limit.
- (F) Emissions testing. Emissions testing for hydrogen chloride and chlorine gas <u>mustshall</u> be conducted using the procedures described in method 0050 or 0051, U.S. EPA publication SW-846.
- (G) Dispersion modeling. Dispersion modeling mustshall be conducted according to the provisions of paragraph (H) of rule 3745-266-106 of the Administrative Code.
- (H) Enforcement. For the purposes of permit enforcement, compliance with the operating requirements specified in the permit (under rule 3745-266-102 of the Administrative Code) will be regarded as compliance with this rule. However, evidence that compliance with those permit conditions is insufficient to ensure compliance with the requirements of this rule may be "information" justifying modification of a permit under rule 3745-50-51 of the Administrative Code.

[Comment: For dates of non-regulatory government publications, publications of recognized organizations and associations, federal rules, and federal statutory provisions referenced in this rule, see rule 3745-50-11 of the Administrative Code titled "Incorporated by reference."]

Effective: 10/31/2015

Five Year Review (FYR) Dates: 07/01/2015 and 07/01/2020

## CERTIFIED ELECTRONICALLY

Certification

10/07/2015

Date

Promulgated Under: 119.03 Statutory Authority: 3734.12 Rule Amplifies: 3734.12

Prior Effective Dates: 12/07/2004, 09/05/2010

Appendix <u>IA</u> to rule 3745-266-107 of the Administrative Code

Tier I Feed Rate Screening Limits for Total Chlorine								
Terrain-adjusted effective	Noncomplex Terrain		Complex Terrain					
stack height (mmeters)	Urban (grams/hour) (g/hr)	Rural (g/hr)	(g/hr)					
4	8.2E+01	8.2E+01 4.2E+01						
6	9.1E+01	4.8E+01	2.8E+01					
8	1.0E+02 5.3E+01		4.1E+01					
10	1.2E+02	6.2E+01	5.8E+01					
12	1.3E+02 7.7E+0		7.2E+01					
14	1.5E+02	9.1E+01	9.1E+01					
16	1.7E+02	1.2E+02	1.1E+02					
18	1.9E+02	1.4E+02	1.2E+02					
20	2.1E+02	1.8E+02	1.3E+02					
22	2.4E+02	2.3E+02	1.4E+02					
24	2.7E+02	2.9E+02	1.6E+02					
26	3.1E+02	3.7E+02	1.7E+02					
28	3.5E+02	4.7E+02	1.9E+02					
30	3.9E+02	5.8E+02	2.1E+02					
35	5.3E+02	9.6E+02	2.6E+02					
40	6.2E+02	1.4E+03	3.3E+02					
45	8.2E+02	2.0E+03	4.0E+02					
50	1.1E+03	2.6E+03	4.8E+02					
55	1.3E+03	3.5E+03	6.2E+02					
60	1.6E+03	4.6E+03	7.7E+02					
65	2.0E+03	6.2E+03	9.1E+02					
70	2.3E+03	7.2E+03	1.1E+03					
75	2.5E+03	8.6E+03	1.2E+03					
80	2.9E+03	1.0E+04	1.3E+03					
85	3.3E+03	1.2E+04	1.4E+03					
90	3.7E+03	1.4E+04	1.6E+03					
95	4.2E+03	1.7E+04	1.8E+03					
100	4.8E+03	2.1E+04	2.0E+03					
105	5.3E+03	2.4E+04	2.3E+03					
110	6.2E+03	2.9E+04	2.5E+03					
115	7.2E+03	3.5E+04	2.8E+03					
120	8.2E+03	4.1E+04	3.2E+03					

[Comment: For dates of non-regulatory government publications, publications of recognized organizations and associations, federal rules, and federal statutory provisions referenced in this rule, see rule 3745-50-11 of the Administrative Code titled "Incorporated by reference."]

## Appendix $\underline{HB}$ to rule 3745-266-107 of the Administrative Code

Tier II Emission Rate Screening Limits for Free Chlorine and Hydrogen Chloride								
Terrain-	Noncomplex terrain				Complex terrain			
adjusted					Values for use in urban			
effective	Values for u	ırban areas	n areas Values for rural areas		and rural areas			
stack ht.	Cl <sub>2</sub> (grams per							
(mmeters)	hour) (g/hr)	HCl (g/hr)	Cl <sub>2</sub> (g/hr)	HCl (g/hr)	Cl <sub>2</sub> (g/hr)	HCl (g/hr)		
4	8.2E+01	1.4E+03	4.2E+01	7.3E+02	1.9E+01	3.3E+02		
6	9.1E+01	1.6E+03	4.8E+01	8.3E+02	2.8E+01	4.9E+02		
8	1.0E+02	1.8E+03	5.3E+01	9.2E+02	4.1E+01	7.1E+02		
10	1.2E+02	2.0E+03	6.2E+01	1.1E+03	5.8E+01	1.0E+03		
12	1.3E+02	2.3E+03	7.7E+01	1.3E+03	7.2E+01	1.3E+03		
14	1.5E+02	2.6E+03	9.1E+01	1.6E+03	9.1E+01	1.6E+03		
16	1.7E+02	2.9E+03	1.2E+02	2.0E+03	1.1E+02	1.8E+03		
18	1.9E+02	3.3E+03	1.4E+02	2.5E+03	1.2E+02	2.0E+03		
20	2.1E+02	3.7E+03	1.8E+02	3.1E+03	1.3E+02	2.3E+03		
22	2.4E+02	4.2E+03	2.3E+02	3.9E+03	1.4E+02	2.4E+03		
24	2.7E+02	4.8E+03	2.9E+02	5.0E+03	1.6E+02	2.8E+03		
26	3.1E+02	5.4E+03	3.7E+02	6.5E+03	1.7E+02	3.0E+03		
28	3.5E+02	6.0E+03	4.7E+02	8.1E+03	1.9E+02	3.4E+03		
30	3.9E+02	6.9E+03	5.8E+02	1.0E+04	2.1E+02	3.7E+03		
35	5.3E+02	9.2E+03	9.6E+02	1.7E+04	2.6E+02	4.6E+03		
40	6.2E+02	1.1E+04	1.4E+03	2.5E+04	3.3E+02	5.7E+03		
45	8.2E+02	1.4E+04	2.0E+03	3.5E+04	4.0E+02	7.0E+03		
50	1.1E+03	1.8E+04	2.6E+03	4.6E+04	4.8E+02	8.4E+03		
55	1.3E+03	2.3E+04	3.5E+03	6.1E+04	6.2E+02	1.1E+04		
60	1.6E+03	2.9E+04	4.6E+03	8.1E+04	7.7E+02	1.3E+04		
65	2.0E+03	3.4E+04	6.2E+03	1.1E+05	9.1E+02	1.6E+04		
70	2.3E+03	3.9E+04	7.2E+03	1.3E+05	1.1E+03	1.8E+04		
75	2.5E+03	4.5E+04	8.6E+03	1.5E+05	1.2E+03	2.0E+04		
80	2.9E+03	5.0E+04	1.0E+04	1.8E+05	1.3E+03	2.3E+04		
85	3.3E+03	5.8E+04	1.2E+04	2.2E+05	1.4E+03	2.5E+04		
90	3.7E+03	6.6E+04	1.4E+04	2.5E+05	1.6E+03	2.9E+04		
95	4.2E+03	7.4E+04	1.7E+04	3.0E+05	1.8E+03	3.2E+04		
100	4.8E+03	8.4E+04	2.1E+04	3.6E+05	2.0E+03	3.5E+04		
105	5.3E+03	9.2E+04	2.4E+04	4.3E+05	2.3E+03	3.9E+04		
110	6.2E+03	1.1E+05	2.9E+04	5.1E+05	2.5E+03	4.5E+04		
115	7.2E+03	1.3E+05	3.5E+04	6.1E+05	2.8E+03	5.0E+04		
120	8.2E+03	1.4E+05	4.1E+04	7.2E+05	3.2E+03	5.6E+04		

[Comment: For dates of non-regulatory government publications, publications of recognized organizations and associations, federal rules, and federal statutory provisions referenced in this rule, see rule 3745-50-11 of the Administrative Code titled "Incorporated by reference."]