

3745-56-54 Monitoring and Inspection.

- (A) During construction or installation, liners [except in the case of existing portions or piles exempt from paragraph (A) of rule 3745-56-51 of the Administrative Code] and cover systems (e.g., membranes, sheets, or coatings) must be inspected for uniformity, damage, and imperfections (e.g., holes, cracks, thin spots, or foreign materials). Immediately after construction or installation:
 - (1) Synthetic liners and covers must be inspected to ensure tight seams and joints and the absence of tears, punctures, or blisters; and
 - (2) Soil-based and admixed liners and covers must be inspected for imperfections including lenses, cracks, channels, root holes, or other structural non-uniformities that may cause an increase in the permeability of the liner or cover.

- (B) While a waste pile is in operation, it must be inspected weekly and after storms to detect evidence of any of the following:
 - (1) Deterioration, malfunctions, or improper operation of run-on and run-off control systems; and
 - (2) Proper functioning of wind dispersal control systems, where present; and
 - (3) The presence of leachate in and proper functioning of leachate collection and removal systems, where present.

- (C) An owner or operator required to have a leak detection system under paragraph (C) of rule 3745-56-51 of the Administrative Code must record the amount of liquids removed from each leak detection system sump at least once each week during the active life and closure period.

Effective: 12/07/2004

119.032 review dates: Exempt

Promulgated under: 119.03

Statutory authority: 3734.12

Rule amplifies: 3734.12

Prior effective dates: 01/07/1983, 08/30/1984, 12/30/1989