

3745-57-84

Inspections of drip pads.

(A) During construction or installation, liners and cover systems (e.g., membranes, sheets, or coatings) ~~shall~~must be inspected for uniformity, damage and imperfections (e.g., holes, cracks, thin spots, or foreign materials). Immediately after construction or installation, liners ~~shall~~must be inspected and certified as meeting the requirements of rule 3745-57-83 of the Administrative Code by ~~an independent qualified, registered~~ a qualified professional engineer. This certification ~~shall~~must be maintained at the facility as part of the facility operating record. After installation, liners and covers shall be inspected to ensure tight seams and joints and the absence of tears, punctures, or blisters.

(B) While a drip pad is in operation, it ~~shall~~must be inspected weekly and after storms to detect evidence of any of the following:

- (1) Deterioration, malfunctions or improper operation of run-on and run-off control systems;
- (2) The presence of leakage in and proper functioning of leak detection system.
- (3) Deterioration or cracking of the drip pad surface.

~~[Note: See paragraph (M) of rule 3745-57-83 of the Administrative Code for remedial action required if deterioration or leakage is detected.]~~

[Comment: See paragraph (M) of rule 3745-57-83 of the Administrative Code for remedial action required if deterioration or leakage is detected.]

Effective: 09/05/2010

R.C. 119.032 review dates: Exempt

CERTIFIED ELECTRONICALLY

Certification

07/23/2010

Date

Promulgated Under: 119.03
Statutory Authority: 3734.12
Rule Amplifies: 3734.12
Prior Effective Dates: 09/02/1997