

3745-67-29 Special requirements for ignitable or reactive waste.

Ignitable or reactive waste shall not be placed in a surface impoundment unless the waste and impoundment satisfy all applicable requirements of Chapter 3745-270 of the Administrative Code, and:

- (A) The waste is treated, rendered, or mixed before or immediately after placement in the impoundment so that:
 - (1) The resulting waste, mixture, or dissolution of material no longer meets the definition of ignitable or reactive waste under rules 3745-51-21 and 3745-51-23 of the Administrative Code; and
 - (2) Paragraph (B) of rule 3745-65-17 of the Administrative Code is complied with; or
- (B)
 - (1) The waste is managed in such a way that it is protected from any material or conditions which may cause it to ignite or react; and
 - (2) The owner or operator obtains a certification from a qualified chemist or engineer that, to the best of his knowledge and opinion, the design features or operating plans of the facility will prevent ignition or reaction; and
 - (3) The certification and the basis for it are maintained at the facility; or
- (C) The surface impoundment is used solely for emergencies.

Effective: 12/07/2000

119.032 review dates: Exempt

Promulgated under: 119.03

Statutory authority: 3734.12

Rule amplifies: 3734.12

Prior effective dates: 04/15/1981, 01/07/1983, 01/30/1986, 02/11/1992