

*** DRAFT – NOT FOR FILING ***

3745-506-702

Construction and demolition debris facility - ground water corrective actions program monitoring schedule.

The ground water monitoring wells that are part of the ground water corrective actions program shall be monitored and analyzed on a semiannual basis in accordance with the following:

- (A) For a facility that has a leachate monitoring system that can be used for conducting the leachate sampling required by Chapter 3745-400 or 3745-520 of the Administrative Code, the ground water monitoring wells shall be monitored and the samples analyzed for the following parameters:
- (1) Arsenic, chromium, and copper as described in paragraph (A) of rule 3745-506-703 of the Administrative Code.
 - (2) Ammonia, calcium, chloride, magnesium, potassium, sodium, and sulfate as described in paragraph (B) of rule 3745-506-703 of the Administrative Code.
 - (3) The parameters that have been detected in the facility's leachate.
 - (4) The waste-derived constituents and C&DD-derived constituents determined in accordance with rules 3745-506-500 and 3745-506-510 of the Administrative Code to be in each release.
- (B) For a facility not described in paragraph (A) of this rule, the ground water monitoring wells shall be monitored and the samples analyzed for the parameters listed in rule 3745-506-703 of the Administrative Code and for the C&DD-derived constituents determined in accordance with rules 3745-506-500 and 3745-506-510 of the Administrative Code to be in each release.