

*** DRAFT – NOT FOR FILING ***

3745-520-622

Select C&DD layer.

(A) An owner or operator shall place select C&DD as the first layer disposed on a filter layer that is above a leachate collection system drainage layer. The select C&DD layer shall meet the following criteria:

(1) The select C&DD layer shall not contain asbestos-containing waste materials.

(2) The select C&DD layer shall not be comprised of fines or small particles that can restrict the flow of leachate to the leachate collection system drainage layer or clog the leachate management system.

(3) The select C&DD layer shall be placed in the following manner:

(a) As a single lift so that a minimum distance of five feet is created between the liner system and the next lift of material to be disposed.

(b) Be spread but not compacted.

(c) In a manner that protects the liner system and leachate collection system from intrusion of objects during operation of the C&DD facility.

(d) In a manner that does not damage the liner system or leachate collection system. At a minimum, material shall not be placed by pushing the material down a slope.

(B) An individual who is not the equipment operator shall be present at all times during placement of the select C&DD layer to observe placement of the select C&DD layer and confirm the leachate management system and the liner system are not damaged.

(C) An owner or operator shall submit notification to the licensing authority at least three days prior to the placement of the select C&DD layer.

(D) An owner or operator shall record in the log of operations the following information verifying the completion of placement of the select C&DD layer within a phase:

(1) The date that the select C&DD layer was placed.

(2) The phase where the select C&DD layer was placed.

(3) The thickness of the select C&DD layer.

(4) The composition of the material used for the select C&DD layer.